THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. 1.00 [25.4] PANDUIT MAXIMUM |##<u>|</u> WE I GHT PART CABLE DIA. lbs. (g)/100pcs NUMBER\* in. (mm) 1.00 0.63 TEAR TAB [25.4] [16.0] 0.37 0.64 LWC38-A (9.5)(292)FULL SCALE NOTES: \*1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION, FOR PACKAGE SIZE. TO APPLY LATCHING WIRE CLIP: 2) MOUNT IS DESIGNED TO SUPPORT I. REMOVE PROTECTIVE LINER 0.50 lbs [ 227g ] MAX WEIGHT ON 2. PLACE IN DESTRED LOCATION
3. APPLY PRESSURE TO TOP OF
LATCHING WIRE CLIP A CLEAN DRY SMOOTH SURFACE. 0.56 NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY PANDUIT WITH RESPECT TO ADHESIVE BOND PERFORMANCE, AMONG [14.2] OTHER THINGS, THE CONDITIONS UNDER WHICH THESE MOUNTS MAY BE APPLIED, AND/OR THE SURFACE TO WHICH THEY MAY BE APPLIED, ARE BEYOND PANDUITS CONTROL. ADHESIVE BACKING: PRESSURE SENSITIVE FOAM 0.04 [1.0] THICK WITH PROTECTIVE LINER TO DIMENSIONS IN BRACKETS ARE METRIC [ mm ] EXTEND BEYOND EDGE FORMING A TEAR TAB. CAD FILENAME/LAYERS G00160BA\_PB\_LWC38A\_01 TINLEY PARK, ILLINOIS LWC38-A. LATCHING WIRE CLIP UNLESS OTHERWISE SPECIFIED, UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: ALL DIMENSIONS ARE GIVEN (.X) ±0.05 [1.3] (.XXX) ±0.010 [0.25] IN INCHES, THIRD ANGLE PROJECTION. (.XX) ±0.02 [0.5] ANGLES ± 5. DRAWN BY JRL MAT'L: 1-7-98 CGSM CHANGED NOTE 3 ON APPLICATION INSTR. GB0160BA 1 2X DATE DRAWING NO. NYLON 6/6 DWG 11-11-93 JRL INITIAL RELEASE GB0160BA R 11-11-93 CHK 'D GB0160BA CHK DESCRIPTION ECN - R SUP REV DATE BY CUST