

tesa® ACXplus 7055

ACXplus High Transparency 1000µm

PRODUCT INFORMATION

Product Description

tesa® ACXplus 7055 is a transparent acrylic core tape. It consists of a high-performance acrylic system and is primarily characterised by its Bonding Power, Stress Dissipation and its Temperature and Weather Resistance.

Due to the high transparency it is especially suitable for constructive bonding of transparent and translucent materials such as glass or

The visco-elastic, solid acrylic core compensates different thermal elongation of bonded parts.

Main Application

Bonding of transparent and translucent materials in the following Industries:

- · Sign manufacturing
- Deco Glass Panels
- Partition Walls

Technical Data

- Backing material
- Colour
- Total thickness
- Type of adhesive
- solid acrylic
- transparent
- 1000 µm pure acrylic
- Elongation at break
- Temperature resistance long term
- 100 °C Temperature resistance (20 min) 200 °C

Adhesion to

- Steel (initial)
- Aluminium (initial)
- Glass (initial)
- PMMA (initial)
- 15.0 N/cm
- 13.0 N/cm 16.0 N/cm

13.0 N/cm

- Steel (after 3 days)
- Aluminium (after 3 days)
- Glass (after 3 days) PMMA (after 3 days)
- 24.0 N/cm 17.0 N/cm

0

24.0 N/cm

24.0 N/cm

1000 %

- **Properties**
- Tack
- Ageing resistance (UV)
- Humidity resistance
- Resistance to chemicals

- Softener resistance
- Static shear resistance at 23°C
- Static shear resistance at 70°C
- T-block

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

++

For latest information on this product please visit http://l.tesa.com/?ip=07055

Page 1 of 2 / As of 10/06/13

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707

tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle, Singapore 629621

Phone: +65 (68) 612 026 Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesa-asia.com tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.



tesa® ACXplus 7055

ACXplus High Transparency 1000µm

PRODUCT INFORMATION

Additional Info

PV 22 = White PE coated paper liner tesa® ACXplus branded

PV 24 = Blue filmic liner

Adhesion values to glass are not part of the product specification.

For latest information on this product please visit http://l.tesa.com/?ip=07055

Page 2 of 2 / As of 10/06/13

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard 164 Gul Circle, Charlotte, N.C. 28209 United States of America
Phone: +1 (704) 554 0707
Phone: +65 (68) 612 026
Fax: +1 (704) 553 5634
http://www.tesatape.com
http://www.tesa-asia.com

tesa tape Asia Pacific Pte. Ltd.

Singapore 629621

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.