


P.C.B. MOUNTING PLAN



SCHEMATIC

## TECHNICAL CHARACTERISTICS

### SPECIFICATION

>Rating:	50mA, 12VDC
>Contact Resistance:	
Initial:	100mOHM max.
After Life Test:	20HM max.
>Insulation Resistance:	min. 100MOHM at 500VDC
>Dielectric Strength:	250VAC for 1 minute
>Stroke:	0.25 + 0.2 mm / - 0.1 mm
>Bounce:	10ms max.

### MATERIAL

>Cover:	Stainless Steel
>Stem:	LCP UL 94V-0
>Frame:	PA9T UL 94V-0, color Black
>Contact:	Stainless Steel with silver
>Terminal:	Brass with silver plating

### SOLDERING INFORMATION

>Terminal in THT version
>Wave 260°C 10sec. max
>Hand soldering under 350°C for 3 sec. max

### ENVIRONMENTAL

>Storage condition:	-40°C ~ +85°C
>Operation condition:	-40°C ~ +85°C
>Compliance:	Lead Free, ROHS, Reach

### PACKAGING INFORMATION

>Bulk




PN	Force	Color of Stem	Life cycle	-043		-050		-070		-095		-130	
				H	Ø D	H	Ø D	H	Ø D	H	Ø D	H	Ø D
430 186 xxx 716	160g ± 50gr	Black	1.000.000	4.3	3.5	5.0	3.5	7.0	3.0	9.5	3.0	13.0	3.0
430 156 xxx 726	260g ± 50gr	White	200.000										
430 156 xxx 736	360g ± 50gr	Salmon	200.000										

Scale - 3:1

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

				<b>GENERAL TOLERANCE</b> .x = +/- 0,2 .xx = +/- 0,15			Basic material				
					Date	Name	DESCRIPTION  WS-TATV 6x6mm Switch, THT version				
				Drawn	09-09-14	Jelisarow					
				Checked	09-09-14	Hsu					
d	material change	14-08-19	AL								
c	revised MatchCode	14-07-24	AL	 Würth Elektronik eiCan			Scale 3:1		Position		SIZE  A4
b	Bounce 10ms max.	14-04-11	DaF				Drawing.- No. 4301x6xxx7x6				
a	warning text	11-10-28	WJ								
REV	FILE	DATE	BY	EDV NO 4301x6xxx7x6.dft			System :Solid Edge V20				