SOURIAU

8D Series Range Extension

A Universal Platform

Esterline
Connection Technologies

8D Series Range Extension

Introduction

Since the early 80's, Souriau is a major supplier of 38999 Series III, the screw-coupled version of MIL-DTL-38999. Present on the main international programs, Souriau has developed a range of products that meet the performance required in extreme environments (civil and military aeronautics, ground, industrial, marine and offshore).

Always pushing the boundaries in term of innovation, Souriau's teams have continuously improved this range of connectors. Today Souriau remains innovative with cadmium free and RoHS solutions. In 2009 Souriau was the first to be QPL qualified for Zinc Nickel plating.

This product family is in accordance with MIL-DTL-38999 Series III, EN 3645, CECC (standard for bronze shell), and also meets many customers' standards (Rolls Royce, ABS, BACC, ...)

Contents

8D Standard Series

- Introduction 03
- 8D Series - Product overview 06
- 8D Series - A superior concept 07
- Technical features 08
- Contact layouts 10
- Ordering information 17

8D Series Range Extension

- micro38999 24
- RoHS solution 24
- Double Flange 25
- Integrated Clinch Nut 25
- High Density 26
- PCB Contact without Shoulder 26
- Power Contact 27
- High Power Contact 27
- Quadrax Contact 28
- ELIO® Contact 28
- Rack & Panel 29
- 230V Connector 29
- Reinforced Sealing 30
- Hermetic Version 30
- RJ45/USB 31
- 8TFD: Filter Connector 31
- 8D8/8D9 Series 32
- 8DB: Bulkhead 32

© 2013 - SOURIAU

ESRI

8D Series

Standard Series

- 8D Series - Product overview 06
- 8D Series - A superior concept 07
- Technical features 08
- Contact layouts 10
- Ordering information:
  - Souriau part numbers 17
  - MIL-DTL-38999 Series III part numbers 18
  - EN3645 part numbers 19
  - BACC part numbers 20
  - Souriau JVS (bronze) part numbers 21
  - CECC part numbers 21

8D Series - Product overview

Standard Series

- **5 different materials**
- **A full platform that matches any environment**
- **Different platings** (including RoHS & Cadmium free platings)



Derived Series

- **Various possibilities of range extension & shell variant from Standard Series**
- **The only limit is your imagination: Consult us !**



© 2013 - SOURIAU

8D Series - A superior concept

A full range of contacts

- Multi-contact technology provides versatile connectors



- Various contact styles
  - Crimp
  - Solder cup
  - PC tails
  - Wire wrap
  - PCB contacts without shoulder
- Common cavity for all #8 contacts

Metallic clips

- Unique clip retention technology
- High performance contact retention system:
  - Insure high temperature withstanding
  - Provides superior strength in vibrations
  - Better retention characteristics than plastic clips



High performance sealing

- IP67
- Each contact cavity is individually sealed

Accessories available

- Protective caps, backshells, tools, ...

© 2013 - SOURIAU

8D Series

Description

- High contact density layouts available HD
- Screw coupling, Shell size from 9 to 25
- Contact protection: 100% Scoop proof
- Protected by cadmium, nickel, green zinc cobalt or black zinc nickel plating
- RFI - EMI shielding and shell to shell continuity
- Accessories available (protective caps, backshells, etc…)
- Hermetic versions
- High power up to 850A
- Optical layouts
- 230V layouts available (ABS22-19, ABS22-20, ABS22-21 & ABS22-22 qualified)

Applications

- Civil and Military Aerospace
- Marine and Offshore Equipment
- Defense and Ground Military
- Industrial

Standards

- MIL-DTL-38999 Series III
- EN3645
- BACC63CT/CU; BACC63DB/DC

Technical features

Mechanical

- **Shell:**
  Aluminum, composite, stainless steel, bronze

- **Shell plating:**
  . Aluminum shell:
  Cadmium olive drab (W)
  Nickel (F)
  Black zinc nickel (Z)
  Green zinc cobalt (ZC)
  . Composite shell:
  Cadmium olive drab (J)
  Nickel (M)
  Without plating (X)
  . Stainless steel shell:
  Passivated (K)
  Nickel (S)
  . Titanium shell:
  Without plating (TT)
  Nickel (TF)
  . Bronze shell:
  Without plating

- **Insulator:** Thermoplastic

- **Grommet and interfacial seal:**
  Silicone elastomer

- **Contacts:** Copper alloy

- **Contacts plating:** Gold over nickel plated

- **Endurance:**
  . 500 mating cycles all materials
  . 1500 mating cycles for composite connectors with specifics contacts

- **Shock:**
  300g, 3 ms according EN 2591-D2 method A

- **Vibration:**
  . Sinus:
  . 10 à 2000 Hz, 3x12 hrs
  (60g, 140 - 2000 Hz) with T° cycling
  . Random:
  . 50 to 2000 Hz, 2x8 Hrs
  (1g2/ Hz, 100 - 2000Hz) at T° max.
  . 25 to 2000 Hz, 2x8 Hrs
  (5g2/ Hz, 100 - 300Hz) at ambiant T°
  Test with accessories in acc with EN2591-D3

- **Contact retention:**

Contacts size	22	20	16	12	8	4
Min force in N	44	67	111	111	111	200

Weight comparison

Example for a plug shell size 15

Materials	Weight	
Stainless steel	58.80 g	42% lighter
Titanium	33.90 g	40% lighter
Aluminum	20.35 g	30% lighter
Composite	14.30 g	

© 2013 - SOURIAU

8D Series

Electrical

• **Test voltage rating (Vrms)**

Service	sea level	at 21000 m
R	400	N/A
M	1 300	800
N	1 000	600
I	1 800	1 000
II	2 300	1 000

• **Contact resistance**

Contacts size	26	22	20	16	12	8	4
Resistance mΩ	16	14.6	7.3	3.8	3.5	3	2

• **Insulation resistance:**
≥ 5 000 MΩ (under 500 Vdc)

• **Contact rating:**

Contacts size	26	22	20	16	12	8	4
Rating (A)	3	5	7.5	13	23	45	80

• **Shell continuity**
. Aluminum shell:
Cadmium olive drab (W): 2.5 mΩ
Nickel (F): 1 mΩ
Black zinc nickel (Z): 2.5 mΩ
Green zinc cobalt (ZC): 2.5 mΩ
. Composite shell:
Cadmium olive drab (J): 3 mΩ
Nickel (M): 3 mΩ
. Stainless steel shell:
Passivated (K): 10 mΩ
Nickel (S): 1 mΩ
. Titanium shell:
Without plating (TT): 10 mΩ
Nickel (TF): 1 mΩ
. Bronze shell:
Without plating: 5 mΩ

• **Shielding:**
. Aluminum shell:
F: 65 db at 10 GHz
Z, F & W: 85 db at 1 GHz
Z & W: 50 db at 10 GHz
ZC: Consult us
. Composite shell:
J & M: 85 db at 1 GHz
. Stainless steel shell:
K: 45 db at 10 GHz
S: 65 db at 10 GHz
. Titanium shell:
TT: 45 db at 10 GHz
TF: 65 db at 10 GHz
. Bronze shell:
85 db at 10 GHz

Climatics

• **Temperature range:**
. Aluminum shell:
W: -65°C +175°C
F: -65°C +200°C
Z: -65°C +200°C
ZC: -65°C +175°C
. Composite shell:
J: -65°C +175°C
M: -65°C +200°C
Without plating (X): -65°C +175°
. Stainless steel shell:
K: -65°C +200°C
S: -65°C +200°C
. Titanium shell:
TT: -65°C +200°C
TF: -65°C +200°C
. Bronze shell:
Without plating: -65°C +175°C

• **Sealing:**
Mated connectors meet altitude immersion requirements of MIL-DTL-38999.

• **Salt spray:**
. Aluminum shell:
W: 500 Hrs
F: 48 Hrs
Z: 500 Hrs
ZC: 250 Hrs
. Composite shell:
J: 2000 Hrs
M: 2000 Hrs
Without plating (X): 2000 Hrs
. Stainless steel shell:
K: 500 Hrs
S: 500 Hrs
. Titanium shell:
TT: 500 Hrs
TF: 48 Hrs
. Bronze shell:
Without plating: 500 Hrs

Resistance to fluids

• **According to MIL-DTL-38999 standard**
. Gasoline: JP5 (OTAN F44)
. Mineral hydraulic fluid: MIL-H-5606 (OTAN H515)
. Synthetic hydraulic fluid: Skydrol 500 B4

• **LD4 (SAE AS 1241)**
. Mineral lubricating: MIL-L-7870A (OTAN 0142)
. Synthetic lubricating: MIL-L-23699 (OTAN 0156), MIL-L-7808
. Cleaning fluid: MIL-DTL-25769 diluted
. De-icing fluid: MIL-A-8243
. Extinguishing fluid: Bromochloromethane
. Cooling fluid: Coolanol

© 2013 - SOURIAU

8D Series

Contact layouts

- Contact #22D
- Contact #20
- Contact #16
- Contact #12
- Contact #10
- Contact #8 Coax or Concentric Twinax - consult us, Concentric Twinax = Triax
- Contact #8 Power
- Contact #8 Quadrax
- Contact ELIO® (fiber optic)
- Contact #4 Power

09 / A

01



1 Optical position

05



1#8 Quadrax

12 HD



12#26 Service R

35



6#22D Service M

98



3#20 Service I

11 / B

01



1#12 Service II all series excepted JVS

01



1#8 Coax Service I only for JVS

02



2#16 Service I

02



2 Optical positions

04



4#20 Service I

05



5#20 Service I

12



1#12 Service II only for JVS

22



4#22D Service M

26 HD



26#26 Service R

35



13#22D Service M

80

1#8 Concentric Twinax Service I

80
Spec 251



1#8 Power

81



1#8 Quadrax

98



6#20 Service I

99



7#20 Service I

ELIO® fiber optic Ethernet Quadrax HD High Density layout

Note: Concentric Twinax = Triax

© 2013 - SOURIAU

Contact layouts

13 / C

03



3#16
Service I

04



4#16
Service I

04



4 Optical positions

08



8#20
Service I

26



2#12
6#22D
Service M

35

22#22D
Service M

43 HD



43#26
Service R

98



10#20
Service I

15 / D

05



5#16
Service II

06



6 Optical positions

15



1#16
14#20
Service I

18



18#20
Service I

19



19#20
Service I

35



37#22D
Service M

97



4#16
8#20
Service I

ELIO® fiber optic Ethernet Quadrax HD High Density layout

© 2013 - SOURIAU

Contact layouts

17 / E

02



38#22D
1#8 Concentric Twinax
Service M

02
Spec 251



38#22D
1#8 Power

06



6#12
Service I

08



8#16
Service II

20



4#12
16#22D
Service M

22



2#12
2#8 Concentric Twinax
Service M

22
Spec 251

2#12
2#8 Power

26



26#20
Service I

35



55#22D
Service M

75



2#8 Concentric Twinax
Service M

75
Spec 251



2#8 Power

80



2#12
2#8 Quadrax

81



38#22D
1#8 Quadrax

82



2#8 Quadrax

99



2#16
21#20
Service I

19 / F

08



8 Optical positions

11



11#16
Service II

18



14#22D
4#8 Concentric Twinax
Service M

18
Spec 251

14#22D
4#8 Power

28



26#20
2#16
Service I

32



32#20
Service I

35



66#22D
Service M

84



14#22D
4#8 Quadrax

H1



1#00
High power

ELIO® fiber optic Ethernet Quadrax Note: Concentric Twinax = Triax

© 2013 - SOURIAU

Contact layouts

21 / G

11



11#12
Service I

12



12 Optical positions

16



16#16
Service II

20



18#20
2#8 Concentric Twinax
Service M

20
Spec 251

18#20
2#8 Power

35



79#22D
Service M

39



2#16
37#20
Service I

41



41#20
Service I

42



2#4 Power
Service I

48



4#8 Power
Service I

59



55#22D
4#12
Service M

72



6#16
2#4 Power
Service I

75



4#8 Concentric Twinax
Service M

75
Spec 251

4#8 Power

77



17#22D
2#8 Concentric Twinax
Service M

77
Spec 251

17#22D
2#8 Power

78



17#22D
2#8 Quadrax

80



18#20
2#8 Quadrax

84



4#8 Quadrax

23 / H

06



6#8 Concentric Twinax
Service M

06
Spec 251

6#8 Power
Service M

21



21#16
Service II

32



32#20
Service I

35



100#22D
Service M

53



53#20
Service I

54



4#12, 9#16
40#22D
Service M

55



55#20
Service I

86



6#8 Quadrax

H1



1#000
High power

ELIO® fiber optic Ethernet Quadrax

Note: Concentric Twinax = Triax

© 2013 - SOURIAU

8D Series

Contact layouts

25 / J

04



48#20
8#16
Service I

07



97#22D
2#8 Concentric Twinax
Service M

07
Spec 251



97#22D
2#8 Power

08

8#8 Concentric Twinax
Service M

08
Spec 251

8#8 Power

11

2#20
9#10
Service N

17



36#22D
6#8 Concentric Twinax

17
Spec 251



36#22D
6#8 Power

19



19#12
Service I

20*

10#20, 13#16
4#12 Coax
3#8 Concentric Twinax
Service N

20*
Spec 251

10#20
13#16, 4#12
3#8 Power

24



12#16
12#12
Service I

24



24 Optical positions

29

29#16
Service I

35



128#22D
Service M

37



37#16
Service II

41



22#22D, 3#20
11#16, 2#12
3#8 Concentric Twinax
Service M

41
Spec 251

22#22D, 3#20
11#16, 2#12
3#8 Power

43



23#20
20#16
Service I

44

4#16
4#4 Power
Service I

46

40#20, 4#16
2#8 Coax
Service I

46
Spec 251

40#20, 4#16
2#8 Power
Service I

61



61#20
Service I

80

10#20
13#16
4#12 Coax
3#8 Quadrax

81

22#22D
3#20, 11#16
2#12
3#8 Quadrax

82



97#22D
2#8 Quadrax

86



40#20
4#16
2#8 Quadrax

87



36#22D
6#8 Quadrax

88



8#8 Quadrax

90

40#20, 4#16
2#8 Concentric Twinax
Service I

H1



1#0000
High power

ELIO® fiber optic Ethernet Quadrax * For classes F, W, K, S only Note: Concentric Twinax = Triax

© 2013 - SOURIAU

Contact layouts (matrix)

Shell size	Layout	MIL-DTL-38999 (QPL) Aluminum, Stainless steel & Composite	8D Titanium	JVS-CECC Bronze connector	Hermetics	EN3645	BACC63 CT/CU DB/DC	Number of contacts	#26	#22D	#20	#16	#12	#10	#8	#4	Fiber optic or High power
09 / A	09-01							1									1 Optic.
	09-05 (1)							1							1 Qdx		
	09-12							12	12								
	09-35	Q		Q		Q	Q	6		6							
	09-98	Q		Q		Q	Q	3			3						
11 / B	11-01							1					1				
	11-01							1							1 Coax		
	11-02	Q		Q		Q	Q	2				2					
	11-02							2									2 Optic.
	11-04	Q					Q	4			4						
	11-05	Q		Q		Q	Q	5			5						
	11-12							1					1				
	11-22							4		4							
	11-26							26	26								
	11-35	Q		Q		Q	Q	13		13							
	11-80							1							1 Twx		
	11-80 sp 251							1							1 Pow		
	11-81							1							1 Qdx		
	11-98	Q		Q		Q	Q	6			6						
	11-99	Q		Q		Q	Q	7			7						
13 / C	13-03							3									
	13-04	Q		Q		Q	Q	4				4					
	13-04							4									4 Optic.
	13-08	Q		Q		Q	Q	8			8						
	13-26			Q		Q		8		6			2				
	13-35	Q		Q		Q	Q	22		22							
	13-43							43	43								
	13-98	Q		Q		Q	Q	10			10						
15 / D	15-05	Q		Q		Q	Q	5				5					
	15-06							6									6 Optic
	15-15	Q		Q		Q	Q	15			14	1					
	15-18	Q		Q		Q	Q	18			18						
	15-19	Q		Q		Q	Q	19			19						
	15-35	Q		Q		Q	Q	37		37							
	15-97	Q		Q		Q	Q	12			8	4					
17 / E	17-02					Q	Q	39		38					1 Twx		
	17-02 sp 251							39		38					1 Pow		
	17-06	Q		Q		Q	Q	6					6				
	17-08	Q		Q		Q	Q	8				8					
	17-20							20		16			4				
	17-22							4					2		2 Twx		
	17-22 sp 251							4					2		2 Pow		
	17-26	Q		Q		Q	Q	26			26						
	17-35	Q		Q		Q	Q	55		55							
	17-75							2							2 Twx		
	17-75 sp 251							2							2 Pow		
	17-80							4					2		2 Qdx		
	17-81							39		38					1 Qdx		
	17-82						Q	2							2 Qdx		
	17-99	Q		Q		Q	Q	23			21	2					
19 / F	19-08							8									8 Optic.
	19-11	Q		Q		Q	Q	11				11					
	19-18	Q					Q	18		14					4 Twx		
	19-18 sp 251																
	19-28	Q		Q			Q	28			26	2					
	19-32	Q		Q		Q	Q	32			32						
	19-35	Q		Q		Q	Q	66		66							
	19-84							18		14					4 Qdx		
	19-H1							1									1 #00

Souriau's layout

Q Souriau's layout & Layout according to corresponding norm

(1) Grounded insert only - Please consult us

#8 **Pow:** Power; **Qdx:** Quadrax; **Twx:** Concentric Twinax

© 2013 - SOURIAU

Contact layouts (matrix)

Shell size	Layout	MIL-DTL-38999 (QPL) Aluminum, Stainless steel & Composite	8D Titanium	JVS-CECC Bronze connector	Hermetics	EN3645	BACC63 CT/CU DB/DC	Number of contacts	#26	#22D	#20	#16	#12	#10	#8	#4	Fiber optic or High power
21 / G	21-11	Q		Q		Q	Q	11					11				
	21-12							12									12 Optic
	21-16	Q		Q		Q	Q	16				16					
	21-20					Q		20			18				2 Twx		
	21-20 sp 251							20			18				2 Pow		
	21-35	Q		Q		Q	Q	79		79							
	21-39	Q		Q		Q	Q	39			37	2					
	21-41	Q		Q		Q	Q	41			41						
	21-42							2								2 Pow	
	21-48			Q				4							4 Pow		
	21-59							59		55			4				
	21-72							8				6				2 Pow	
	21-75	Q				Q	Q	4							4 Twx		
	21-75 sp 251							4							4 Pow		
	21-77							19		17					2 Twx		
	21-77 sp 251							19		17					2 Pow		
	21-78						Q	19		17					2 Qdx		
	21-80							20			18				2 Qdx		
	21-84						Q	4							4 Qdx		
23 / H	23-06							6							6 Twx		
	23-06 sp 251							6							6 Pow		
	23-21	Q		Q		Q	Q	21				21					
	23-32	Q						32			32						
	23-35	Q		Q		Q	Q	100		100							
	23-53	Q		Q		Q	Q	53			53						
	23-54					Q		53		40		9	4				
	23-55	Q		Q		Q	Q	55			55						
	23-86							6							6 Qdx		
	23-H1							1									1 #000
25 / J	25-04	Q				Q	Q	56			48	8					
	25-07	Q				Q	Q	99		97					2 Twx		
	25-07 sp 251							99		97					2 Pow		
	25-08	Q		Q (2)		Q	Q	8							8 Twx		
	25-08 sp 251							8							8 Pow		
	25-11	Q				Q	Q	11			2			9			
	25-17							42		36					6 Twx		
	25-17 sp 251							42		36					6 Pow		
	25-19	Q		Q		Q	Q	19					19				
	25-20	Q		3)		Q (4)	Q (5)	30			10	13	4 (6)		3 Twx		
	25-20 sp 251							30			10	3	4		3 Pow		
	25-24	Q		Q		Q	Q	24				12	12				
	25-24							24									24 Optic.
	25-29	Q		Q		Q	Q	29				29					
	25-35	Q		Q		Q	Q	128		128							
	25-37	Q				Q	Q	37				37					
	25-41							41		22	3	11	2		3 Twx		
	25-41 sp 251							41		22	3	11	2		3 Pow		
	25-43	Q		Q		Q	Q	43			23	20					
	25-44							8				4				4 Pow	
	25-46	Q				Q	Q	46			40	4			2 Coax		
	25-46 sp 251							46			40	4			2 Pow		
	25-61	Q		Q		Q	Q	61			61						
	25-80							30			10	13	4		3 Qdx		
	25-81							41		22	3	11	2		3 Qdx		
	25-82							99		97					2 Qdx		
	25-86							46			40	4			2 Qdx		
	25-87							42		36					6 Qdx		
	25-88							8							8 Qdx		
	25-90							46			40	4			2 Twx		
	25-H1							1									1 #0000

Souriau's layout

Q Souriau's layout & Layout according to corresponding norm

(2) For CECC, layout 25-08 only delivered without contact

(3) For classes F, W, S, K only

(4) For classes F, W, K only

(5) Qualified BACC63DB/DC only

(6) 4 #12 coax (2+2)

#8 **Pow:** Power; **Qdx:** Quadrax; **Twx:** Concentric Twinax

© 2013 - SOURIAU

Souriau part numbers

Basic Series	8D	0		11	W	35	P	N			L

Shell style:
- **0:** Square flange receptacle
- **1:** In line receptacle (Aluminum only)
- **7:** Jam nut receptacle (Aluminum, Stainless steel & Titanium only)
- **5:** Plug with RFI shielding

Type:
- **None:** Connectors with standard crimp contacts.
- **L:** Receptacle with long PC tail (male and female size #22D, #20).
- **C:** Receptacle with short PC tail (male and female #22D, #20, #16).
- **S:** Receptacle with specific PC tail (male et female #22D)
- **W:** Receptacle with male contacts #22D for wire wrap (3 wraps)
- **T:** Receptacle with male contacts #20 for wire wrap (2 wraps)
- **P:** Receptacle with solder cup - only available for Reinforced sealing Series (see page 75) - male and female size #22D; male #16 & #12; female #16 & #12 and male female #20 please consult us

Shell size: 09, 11, 13, 15, 17, 19, 21, 23, 25

Plating:
- **W:** Olive drab cadmium (Aluminum only)
- **F:** Nickel (Aluminum only)
- **ZC:** Green zinc cobalt (Aluminum only)
- **Z:** Black zinc nickel (Aluminum only)
- **J:** Olive drab cadmium (Composite only)
- **M:** Nickel (Composite only)
- **X:** Without plating (Composite only)
- **K:** Passivated (Stainless steel only)
- **S:** Nickel (Stainless steel only)
- **TT:** Without plating (Titanium only)
- **TF:** Nickel (Titanium only)

Contact layout: See pages 10 to 13

Contact type:
- **P:** Pin (500 mating/unmating)
- **S:** Socket (500 mating/unmating)
- **H:** Pin (1500 mating/unmating - Composite only)
- **J:** Socket (1500 mating/unmating - Composite only)
- **A:** Connector supplied less pin contact or with specific contacts (connector marking: A + orientation)
- **B:** Connector supplied less socket contact or with specific contacts (connector marking: B + orientation)

Orientation: N, A, B, C, D, E, T, V

Specification:
- **046:** Tinned straight PC tail
- **251:** Connector provided with power contacts (layouts with contact #8)
- **022:** Fuel tank
- **600:** 230V qualified connector (stainless steel & composite, T or V orientation mandatory - Consult us for available layouts)

Special custom:
- **None:** Standard plastic cap
- **M:** Antistatic plastic cap

L: For P or S contact type only, connectors delivered without contacts, connectors marking P or S plus orientation

Note: Stainless steel plug with reinforced locking available, please consult us.

© 2013 - SOURIAU

MIL-DTL-38999 Series III part numbers

Basic Series	D38999	20	W	B	35	P	N	L

Shell style:
- **20:** Square flange receptacle
- **24:** Jam nut receptacle (Aluminum & Stainless steel only)
- **26:** Plug with RFI shielding

Plating:
- **Z:** Black zinc nickel (Aluminum)
- **W:** Olive drab cadmium (Aluminum)
- **F:** Nickel (Aluminum)
- **J:** Olive drab cadmium (Composite)
- **M:** Nickel (Composite)
- **K:** Passivated (Stainless steel)
- **S:** Nickel (Stainless steel)

Shell size: 09=**A**, 11=**B**, 13=**C**, 15=**D**, 17=**E**, 19=**F**, 21=**G**, 23=**H**, 25=**J**

Contact layout: See pages 15 & 16 for layout according to MIL-DTL-38999

Contact type:
- **P:** Pin
- **S:** Socket
- **A:** Connector supplied less pin contact or with specific contacts (connector marking: A + orientation)
- **B:** Connector supplied less socket contact or with specific contacts (connector marking: B + orientation)

Orientation: N, A, B, C, D, E

L: For P or S contact type only, connector delevired without contacts, connector marking P or S (without L)

Note: To place a MIL connectors order delivered without MIL removable crimp contacts and keep P or S plus orientation marking, it must be specify clearly on the order (by adding a suffix L at the end of the P/N or specified in comment).

© 2013 - SOURIAU

EN3645 part numbers

Basic Series	EN3645	W	6	G	N	35	B	N
Plating: **W:** Olive drab cadmium (Aluminum) **F:** Nickel (Aluminum) **J:** Olive drab cadmium (Composite) **M:** Nickel (Composite) **K:** Stainless steel passivated (Stainless steel)								
Shell style: **0:** Square flange receptacle **6:** Plug **7:** Jam nut receptacle (Aluminum & Stainless steel only)								
Shell size: 09=**A**, 11=**B**, 13=**C**, 15=**D**, 17=**E**, 19=**F**, 21=**G**, 23=**H**, 25=**J**								
Grounding: **N:** Standard insert not grounded								
Contact layout: See pages 15 & 16 for layout according to EN3645								
Contact type: **M:** Pin **F:** Socket **A:** Connector supplied less pin contact **B:** Connector supplied less socket contact								
Orientation: N, A, B, C, D, E								

© 2013 - SOURIAU

BACC part numbers

Basic Series: **BACC63CT:** 8D5*M (composite plug) **BACC63CU:** 8D0*M (composite square flange receptacle) **BACC63DB:** 8D5*K (stainless steel plug) **BACC63DC:** 8D0*K (stainless steel square flange receptacle)	**BACC63CT**	**13**	**-**	**98**	**P**	**N**	**H**
Shell size: **09**=A, **11**=B, **13**=C, **15**=D, **17**=E, **19**=F, **21**=G, **23**=H, **25**=J							
Plating & grounding: **-:** Nickel plated, ungrounded **G:** Nickel plated, grounded **D:** Cadmium plated, ungrounded **C:** Cadmium plated, grounded							
Contact layout: See pages 15 & 16 for layout according to BACC							
Contact type: **P:** Pin **S:** Socket							
Orientation: **N, A, B, C, D, E**							
Specification: **None:** With contacts **H:** Without contact & without filler plug							

© 2013 - SOURIAU

Souriau JVS (bronze) part numbers

Basic Series	JVS	16	A	11	35	P	N	-

Shell style:
00: Square flange receptacle
07: Jam nut receptacle
16: Plug with RFI shielding

Material:
A: Bronze housing material

Shell size:
09, 11, 13, 15, 17, 19, 21, 23, 25

Contact layout:
See pages 10 to 14

Contact type:
P: Pin **A:** Connector supplied less pin contact or with specific contacts (connector marking: A + orientation)
S: Socket **B:** Connector supplied less socket contact or with specific contacts (connector marking: B + orientation)

Orientation:
N, A, B, C, D, E

Specification:
251: Connector provides with power contacts (layouts with contacts #8)
CI: Printed board mounting contacts
LI: Receptacle with long PC tail (pin or socket #22D)
L: For P or S contact type only, connectors delivered without contacts, connectors marking P or S plus orientation

CECC part numbers

Basic Series	C 752 002	B	B	98	M	C	N	A	0	1	G

Shell style:
A: Plug
B: Square flange receptacle
C: Jam nut receptacle

Shell size:
09=**A**, 11=**B**, 13=**C**, 15=**D**, 17=**E**, 19=**F**, 21=**G**, 23=**H**, 25=**J**

Contact layout:
See pages 15 & 16 for layout according to CECC

Contact type:
M: Pin
F: Socket

Type of contact termination:
C: Crimp contact

Orientation:
N, A, B, C, D, E

Shell material:
A: Aluminum bronze

Supply code:
0: Connectors supplied with contacts
1: Connectors supplied without contacts

Assessment level:
1: Level 1

Performance level:
G: Level G

Note: C 752 002 refers to the abbreviated form of the CECC 75 201-002 type designation.

© 2013 - SOURIAU

Series

8D Series

Range Extension

- micro38999 24
- RoHS solution 24
- Double Flange 25
- Integrated Clinch Nut 25
- High Density 26
- PCB Contact without Shoulder 26
- Power Contact 27
- High Power Contact 27
- Quadrax Contact 28
- ELIO® Contact 28
- Rack & Panel 29
- 230V Connector 29
- Reinforced Sealing 30
- Hermetic Version 30
- RJ45/USB 31
- 8TFD: Filter Connector 31
- 8D8/8D9 Series 32
- 8DB: Bulkhead 32

8D Series Range Extension

Product range extension

micro38999

A complete miniature range: threaded (8DA), break away (8BA) & bayonet (8LTA). Space saving with scoop proof connector for harsh applications.

A compact solution:
. Diameter up to 45% smaller than size 9 (D38999).
. Up to 50% shorter.
. Integrated backshell: Cost and space saving.

A high density solution:
. With #26 contacts (according to 39029).
. 5 layouts (size 3, 5 and 7 with #22 & #26).

Excellent features:
. Designed for D38999 requirements.
. IP67 sealing when mated.
. Stainless steel shell (1500 matings) & aluminum shell (500 matings).

RoHS and Cadmium free:
. Available in zinc nickel (RoHS) plating, as well as nickel and olive drab cadmium.

See «micro38999, A Complete Miniature Range» catalog on www.souriau.com

RoHS Solution

The RoHS alternative to cadmium !
SOURIAU Zinc Nickel: the best in terms of price and performance for aerospace & defense equipment.

SOURIAU Black Zinc Nickel:
. A unique alternative plating process to cadmium.

RoHS compliant:
. A unique SOURIAU plating process compliant with RoHS regulations for cadmium and Cr6+.

The first QPL qualified:
. SOURIAU Zn Ni is the first product which has been qualified by US Defense standards organization (DLA Land and Maritime).

High corrosion resistance:
. 500 hours salt spray.

Available in mass production:
. Available for 38999 Series I, II and III aluminum range.

See «RoHS Black Zinc Nickel - The Cadmium Free Solution» catalog on www.souriau.com

© 2013 - SOURIAU

Product range extension

Double Flange

Double flange solution for PCB mount.
Specially designed for PCB applications in harsh environments, decoupling vibration from the board.

Excellent mechanical performance:
. Standoffs integrated into the connector.
. No risk of breaking contacts and no risk of micro-cuts.

Design flexibility:
. Square flange or Jam nut versions available.
. Versatile contact length options.

A wide range:
. Available in aluminum with a range of layouts from shell size 9 to 25.

User friendly:
. Easy to assemble & time saving.

See «38999 Series III - Double Flange» product news on www.souriau.com

Integrated Clinch Nut

Integrated clinch nut solution for box mount.
Equivalent mounting retention of the receptacle ensured with only 4 clinch nuts. Designed for severe applications.

User friendly:
. Easy to install.

Selflocking:
. Fast and secure.

Reduced mounting hardware:
. Elimination of nuts and washers.

See «38999 Series III - Clinch Nut» product news on www.souriau.com

© 2013 - SOURIAU

8D Series Range Extension

Product range extension

High Density

SOURIAU offers a robust & reliable High Density solution derived from 38999 Series I, Series III & VG96912.

3 shell sizes available:
. Provides flexibility according to your application.

A reliable & robust solution:
. Same well proven design as standard 38999 & VG96912.

Significant space saving:
. Twice the number of contacts compared to size 13-35 with 22 contacts.
. Two shell sizes smaller than a partially populated size 17-35 with 55 cavities.

See «High Density Connectors» product news on www.souriau.com

PCB Contact without Shoulder

Pin & socket PCB contacts without shoulder #22D & #20 as per MIL-DTL-38999 Series I, II & III. Contacts without shoulder allows a more flexible mounting on variable PCB thicknesses or depths.

Ruggedized contacts:
. Material: copper alloy
. Finish: gold per MIL-G-45204 type I class 1 over nickel plate
. Sleeve: stainless steel

Flexible mounting:
. Various PCB thicknesses.
. Multiple PCB positioning.

See «PCB contacts without shoulder» product news on www.souriau.com

© 2013 - SOURIAU

8D Series Range Extension

Product range extension

Power Contact

Power supply in harsh environments. Designed to be used in severe environments, fluid resistance, high shock and vibration.

A unique contact design with a braid socket:
. 20 contact points for a #4 contact vs 2 or 3 for a standard socket.
. Allowing 20 % more current as compared to standard socket.
. Excellent vibration withstanding.
. Insure excellent crimping

A versatile individual sealing on the cable:
. Sealing on the cable done thanks to a sealing boot.
. Same connector can accomodate a wild range of cable diameter.

A contact technology integrated in well proven standard AeroMil connectors:
. Up to 260°C service temperature,
. Up to 60G vibration withstanding.
. Shell available in, aluminium, composite, Stainless steel, Titanium & Bronze.

See «8D Series - MIL-DTL-38999» catalog on www.souriau.com

High Power Contact

38999 High Power (up to 850A). Designed to meet the harshest military requirement where high power and shielding are needed.

3 aluminum shell sizes available:
. Size 19 (450A max); size 23 (650A max); size 25 (850A max).
. Different finish: cadmium, zinc nickel, electroless nickel.
. Threaded coupling.

Superior contact technology equipped with a silver plated braid:
. High contact endurance.
. Low contact resistance.
. No microcut under vibration.

Modular design for easy installation:
. Removable backshell: straight, right angle or bus bar.
. Backshell termination: for thread or shrink boot.
. Possible to crimp various cable (Ø from 50 to185mm).

Safety

See «38999 Series III - High Power Contacts» product news on www.souriau.com

Product range extension

Quadrax Contact

Quadrax contacts for full duplex ethernet link with robust MIL-DTL-38999 compliant screw coupling system for networks & high vibration environments.

High speed:
. One Quadrax contact replace two concentric Twinax contacts.
. Data rate up to 1 Gbit/sec.

A wide range:
. Compatible with all Souriau standard 38999 shells, plating and inserts (with at least one #8 cavity).

A flexible range:
. Available in 100 and 150 ohms (grounded or not).

A versatile technology:
. Quadrax layouts compatible with all #8 contacts type: power, coax, concentric twinax, fiber optic.

See «Quadrax Contact - Up to Cat6» catalog on www.souriau.com

ELIO® Contact

ELIO® contact: ruggedized and user friendly fiber optic technology. Easy mounting optical link for severe applications.

Flight proven:
. The only Airbus qualified fiber optic technology: ABS 1379, ABS 12 13. ARINC 801 and EN4531 qualified.

Robust connection:
. Withstanding the most severe vibrations with excellent optical performance (0.3 dB).

User friendly contact:
. Easy cleaning: no part to remove.
. No tool needed for insertion/extraction of the contacts.

A wide range available:
. In all planforms with #8 cavities. Up to 24 ELIO® contacts in 38999 size 25.

See «ELIO® Fiber Optic Technology» catalog on www.souriau.com

© 2013 - SOURIAU

Product range extension

Rack & Panel

Sealed rack & panel for blind connection. A 100% scoop proof connector with quick connection in hard-to-reach areas.

Blind connection:
. Easy & fast connection without any coupling/uncoupling between a float-mounting unit & a fixed unit

Float-mounting unit - rack:
. Female crimp contacts.
. Mounting on the cabinet side.
. Angular orientation with a key.
. Possibility to supply rear accessories.

Misalignment catching:
. Longitudinal, axial and angular.



See «38999 Series I - Rack & Panel 8LT» product news on www.souriau.com

230V Connector

The use of higher voltage to reduce cable weight has lead to the development of double voltage connectors.

Robust design and materials:
. In high altitude un-pressurized areas, higher voltages increase electrical partial discharges ➔ Risk of contact short circuits. Our 230V connector avoids this risk !

No possible mismatch:
. Specific T and V clocking to avoid mating with a non 230V qualified counterpart.

Flexible offering:
. Available in standard watertight and hermetic connectors with the same performance.
. Available in composite and stainless steel shells.

See «230 Volt EN3645 Derived Connectors» product news on www.souriau.com

© 2013 - SOURIAU

8D Series Range Extension

Product range extension

Reinforced Sealing

Cost effective sealing solution, the best value for money.
To be used when enhanced sealing is needed in harsh environments and as an alternative to hermetic glass bead.

Weight saving:
. Lightweight compared with hermetic versions.

Excellent shock resistance:
. Better than hermetic glass seals.
. Filtered receptacle are generally standard length.

High performances:
. Reinforced sealing receptacle with male or female straight PC tails.
. High hermiticity performance: 10^{-7} atm.cm^3/s.
. 100 % scoop proof.
. High density connectors.
. Lower profile for compactness.

See «8D Series - MIL-DTL-38999» catalog on www.souriau.com

Hermetic Version

Glass sealed connector (helium leakage test).
Low profile for compacity requirements.

As per MIL-DTL-38999:
. Inert glass insulator.
. High hermeticity performance.
. Ideal for high pressure environments.
. Low profile.
. Nickel plating upon request.

Various shell types:
. Box mounting flange receptacle.
. Jam nut receptacle.
. Solder mounting receptacle.

See «8D Series Hermetic Connectors» product news on www.souriau.com

© 2013 - SOURIAU

Product range extension

RJ45/USB

Ethernet Connectors for Harsh Environments.
Rugged RJ45, USB-A/USB-B solutions.

RJ45 / USB connectors:
. A & B types, connectors available on MIL-C-26482 Series I, MIL-DTL-38999 Series III.

IP67 sealing:
. In mated conditions.

USB data transmission:
. USB - A & B types - according to the «Bus» specification, Rev 2.0.

RJ45 data transmission:
. RJ45 - 10 BaseT, 100 BaseTX and 1000 BaseT networks, CAT 5E per TAI/EIA 568B and ClassD per ISO/IEC 11801.

See «8D Series - MIL-DTL-38999» catalog on www.souriau.com

8TFD: Filter Connector

EMI-RFI filters and lightning protection in composite light-weight shell.

Space saving:
. Complete filter solution in standard shell.
. No need for filter PCB inside equipment.
. Smaller equipment envelope required.

Excellent filter performance:
. Excellent performance, comparable to aluminum shell EMI-RFI filter connectors.

Highly corrosion resistant:
. 2000 hours salt spray in either nickel or olive drab finish.

Wide range of layouts available:
. SOURIAU EMI-RFI Filter 38999 Series III connectors are available in aluminum, marine bronze, and stainless steel shells.

© 2013 - SOURIAU

8D Series Range Extension

Product range extension

8D8/8D9 Series

8D8: high vibration performance push-pull connector.
8D9: lanyard release, high performance 38999 quick release.

A wide range with excellent performances:
. MIL-DTL-38999 layouts and contacts
. MIL-DTL-38999 Series electric performances
. Scoop proof
. Compatible with standard backshells 38999 Series III
. Very high performance coupling with ball locking concept, check of locking by free ring when mated.

Easy to connect-disconnect:
. 8D8: ideal for restricted space mating.
. 8D9: simple push to connect - pull to disconnect.

High vibration performance:
. Up to 44g
. 8D8: ideal for mil-aero and space applications.
. 8D9: ideal for missiles, inter-stage separation, space probes, UAVs.

See «8D8/8D9 Series - 38999 Push pull/Quick release» catalog on www.souriau.com

8DB: Bulkhead

"Double Receptacle" mounted on panel allows cable plug connection on both sides of the bulkhead. Create a permanent sealed barrier on your panel suitable for pressurized or depressurized areas.

Easy integration:
. Standard 38999 mounting interface (square flange, jam nut)..
. Easy modular assembly and connection.
. Time saving for maintenance.
. The ideal interconnect solution for aircraft pressurized/non pressurized panels.

Reinforced sealing:
. Feedthrough sealing even when unmated (10^{-6} atm.cm^3/s).
. Permanent sealing barrier on panel (O rings).
. Glass fused hermetic version available ($<10^{-8}$ atm.cm^3/s) for fuel tanks/space systems.

A large platform available:
. All 38999 Series III layouts (signal and power contacts).

See «38999 Series III - Bulkhead Feedthrough» catalog on www.souriau.com

© 2013 - SOURIAU

SOURIAU

www.souriau.com

contactmilaero@souriau.com

Esterline

Connection Technologies

© Copyright SOURIAU July 2013 - All information in this document presents only general particulars and shall not form part of any contract. All rights reserved to SOURIAU for changes without prior notification or public announcement. Any duplication is prohibited, unless approved in writing.