


Low Leakage Schottky Barrier Rectifier**Main product characteristics**

I_O	1A
V_{RRM}	20V
$T_{j(MAX)}$	125°C
$V_{F(MAX)}$	0.455V
$I_{R(MAX)}$	10 μ A

Features and benefits

- Low forward voltage drop
- Low profile package height
- Efficient heat path with integral locking bottom metal tab
- Low thermal resistance DO-216AA package

**Description and applications**

Single schottky rectifier assembled in Powermite 1[®] package which features a full metallic bottom that eliminates possibility of solder flux entrapment during assembly. The package also incorporates a unique locking tab which acts as an efficient heat path from die to mounting plane for external heat sinking with very low thermal resistance junction to case (bottom).

This product is suitable for use in switching and regulating power supplies and also charge pump circuits.

Absolute maximum ratings⁽¹⁾

Symbol	Parameter	Value	Unit
V_{RRM} V_{RWM} V_R	Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	20	V
$V_{R(RMS)}$	RMS Reverse Voltage	14	V
I_O	Average rectified forward output current ($T_C = 135^\circ\text{C}$)	1.0	A
I_{FRM}	Peak repetitive forward current (100kHz square wave, $T_C = 135^\circ\text{C}$)	2.0	A
I_{FSM}	Non repetitive peak forward surge current (8.3ms single half sine wave)	50	A
dV/dt	Voltage rate of change (at max V_R)	10000	V/ μ s
T_{STG}	Storage temperature	-55 to +150	°C
T_J	Junction temperature	-55 to +125	°C

⁽¹⁾ All ratings at 25°C unless specified otherwise

Low Leakage Schottky Barrier Rectifier

Characteristics

Static Electrical Characteristics


Symbol	Parameter	Test Conditions		Typ	max	Units
$V_F^{(2)}$	Maximum forward voltage	$T_J = 25^\circ\text{C}$	$I_F = 0.1\text{ A}$		0.455	V
			$I_F = 1.0\text{ A}$		0.530	
			$I_F = 3.0\text{ A}$		0.595	
		$T_J = 100^\circ\text{C}$	$I_F = 0.1\text{ A}$		0.360	
			$I_F = 1.0\text{ A}$		0.455	
			$I_F = 3.0\text{ A}$		0.540	
$I_R^{(2)}$	Maximum instantaneous reverse current	$T_J = 25^\circ\text{C}$	$V_R = 20\text{V}$		10	μA
			$V_R = 10\text{V}$		1.0	
			$V_R = 5\text{V}$		0.5	
		$T_J = 100^\circ\text{C}$	$V_R = 20\text{V}$		1600	
			$V_R = 10\text{V}$		500	
			$V_R = 5\text{V}$		300	
C_T	Junction capacitance	$V_R = 5\text{V}, f = 1\text{MHz}$				pF

⁽²⁾ Measured with a test pulse of 380 μs to minimize self-heating effect

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Junction to case (bottom)	15	$^\circ\text{C/W}$
$R_{\theta JA}$	Junction to ambient ⁽³⁾	240	$^\circ\text{C/W}$

⁽³⁾ Mounted on FR-4 PC board using 1oz copper with recommended minimum foot print




Reverse power dissipation and the possibility of thermal runaway must be considered when operating this device under any reverse voltage conditions. Calculations of T_J therefore must include forward and reverse power effects. The allowable operating T_J may be calculated from the equation:


$T_J = T_{J\max} = r(t)(P_f + P_r)$ where
 $r(t)$ = thermal impedance under given conditions.
 P_f = forward power dissipation, and
 P_r = reverse power dissipation

This graph displays the de-rated allowable T_J due to reverse bias under DC conditions only and is calculated as $T_J = T_{J\max} - r(t) P_r$, Where $r(t) = R_{\theta JA}$. For other power applications further calculations must be performed.

Low Leakage Schottky Barrier Rectifier



Thermal Impedance Junction to Case (bottom)




Thermal Impedance Junction to Ambient

Mechanical Characteristics

Physical dimensions

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.73	0.99	0.029	0.039
B	0.40	0.66	0.016	0.026
C	1.77	2.03	0.070	0.080
D	2.21	2.46	0.087	0.097
E	0.50	0.76	0.020	0.030
F	1.29	1.54	0.051	0.061
G	0.53	0.78	0.021	0.031
H	0.10	0.20	0.004	0.008
I	1.77	2.03	0.070	0.080
J	0.89	1.14	0.035	0.045

Low Leakage Schottky Barrier Rectifier**Footprint dimensions**Powermite 1[®] footprint dimensions in *mm (inches)***Package materials & information****Case** : Epoxy meets UL94V-0**Electrode finish** : Matte Sn
plating - fully RoHS compliant**Marking code** :**20E****Ordering information**

Product order code	Marking	Package	Weight	Base qty	Delivery mode
UPS120Ee3 / TR7	20E	Powermite 1 (DO-216AA)	0.016 g	3000	Tape and reel (7 inch)
UPS120Ee3 / TR13	20E	Powermite 1 (DO-216AA)	0.016 g	12000	Tape and reel (13 inch)

*Commercial Business Unit
Microsemi Corporation*Microsemi Commercial Offshore de Macau Limitada
Avenida Doutor Mario Soares
Bank of China Building, 18/F, Unit D
Macau SARPlease refer to www.microsemi.com for the terms and conditions of purchase