Alle Rechte vorbehalten/ *All rights reserved*




Cross section at flat






| | |
|---|---|
| Wire | Tinned copper |
| Gauge | AWG 28/7 0,089 mm² |
| Voltage rating | 300 Vr.m.s |
| Current rating | 1,3 A at 10°C rise above ambient |
| Capacity unbalanced | 78,7 pF/m nominal at 1MHz |
| Impedance unbalanced | 75 Ω nominal |
| Conductor resistance | 225 mΩ/m |
| Propagation delay | 5,25 ns/m nominal |
| Insulation material | PVC |
| Temperature rating | -20°C(operating) / -30°C(static) to +105°C |
| Insulation resistance | 10 000 MΩ/km |
| Approvals | UL Listed PLCC2-CL2 / CSA Certified AWM FT-1 |

(1) : Flat cable, AWG 28/7

(2) : Clear polyester

(3) : Outer jacket: black PVC

| Part number | Length per reel |
|---|---|
| 09 18 025 7011 | 100 m (328 feet) |
| 09 18 025 7008 | 30,48 m (100 feet) |

| Mod. | Dat. | Name |
|---|---|---|
| EC01911 | 25/05/10 | SC |
| 34612 | 20/09/07 | PK |
| 33247 | 25/10/05 | JMDR |

| | Dat. | Name |
|---|---|---|
| Detail. | 25/10/05 | JMDR |
| Insp. | | |
| Stand. | | |

All Dim. in mm
Orig. Size DIN A 4

HARTING EURL
F-95972 Paris

SEK 18 round flat cable, not shielded, 25 poles

Maßstab/ *Scale*

TB 09 18 025 70XX

Sub.

Blatt/ *Page* 2/2