


Three Phase Rectifier Bridge

PSD 28

$$\begin{aligned} I_{dAV} &= 28 \text{ A} \\ V_{RRM} &= 600\text{-}1200\text{V} \end{aligned}$$

Preliminary Data Sheet

V_{RSM} V_{DSM} (V)	V_{RRM} V_{DRM} (V)	Type
700	600	PSD 28/06
900	800	PSD 28/08
1300	1200	PSD 28/12



Symbol	Test Conditions	Maximum Ratings
I_{dAV}^*	$T_C = 100\text{ }^\circ\text{C}$, (per module)	28 A
I_{FSM}	$T_{VJ} = 45\text{ }^\circ\text{C}$ t = 10 ms (50 Hz), sine	100 A
	$V_R = 0$ t = 8.3 ms (60 Hz), sine	106 A
	$T_{VJ} = T_{VJM}$ t = 10 ms (50 Hz), sine	85 A
	$V_R = 0$ t = 8.3 ms (60 Hz), sine	90 A
$\int i^2 dt$	$T_{VJ} = 45\text{ }^\circ\text{C}$ t = 10 ms (50 Hz), sine	50 A ² s
	$V_R = 0$ t = 8.3 ms (60 Hz), sine	47 A ² s
	$T_{VJ} = T_{VJM}$ t = 10 ms (50 Hz), sine	36 A ² s
	$V_R = 0$ t = 8.3 ms (60 Hz), sine	33 A ² s
T_{VJ}		-40... + 150 °C
T_{VJM}		150 °C
T_{stg}		-40... + 125 °C
V_{ISOL}	50/60 Hz, RMS t = 1 min	2500 V~
	$I_{ISOL} \leq 1\text{ mA}$ t = 1 s	3000 V~
M_d	Mounting torque (M4)	1.5 - 1.8 Nm
		14 - 16 lb.in.
Weight	typ.	16 g

Symbol	Test Conditions	Characteristic Value	
I_R	$V_R = V_{RRM}, T_{VJ} = T_{VJM}$	$\leq$	0.3 mA
	$V_R = V_{RRM}, T_{VJ} = 25^\circ\text{C}$	$\leq$	5 mA
V_F	$I_F = 7\text{ A}, T_{VJ} = 25^\circ\text{C}$	$\leq$	1.12 V
V_{TO}	For power-loss calculations only		0.8 V
r_T			40 m Ω
R_{thJC}	per diode; DC		2.3 K/W
	per module		0.39 K/W
R_{thJH}	per diode; DC		2.8 K/W
	per module		0.47 K/W
d_s	Creeping distance on surface		11.2 mm
d_A	Creeping distance in air		9.7 mm
a	Max. allowable acceleration		50 m/s ²

Data according to IEC 60747 refer to a single diode unless otherwise stated
* - for resistive load at bridge output

Features

-
- Package with DCB ceramic base plate
- Isolation voltage 3000 V~
- Planar glass passivated chips
- Low forward voltage drop
- Leads suitable for PC board soldering
- UL registered. E 148688

Applications

- Supplies for DC power equipment
- Input rectifier for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling capability
- High power density
- Small and light weight

Package style and outline

Dimensions in mm (1mm = 0.0394")

