

REV. G

DIMENSIONS ARE IN INCHES

UNLESS OTHERWISE NOTED


TOLERANCES ARE:

ONE PLACE DECIMALS $\pm .1$ [2.5] THREE PLACE DECIMALS $\pm .005$ [127]
 TWO PLACE DECIMALS $\pm .01$ [.25] FOUR PLACE DECIMALS $\pm .0020$ [.051]

ANGLES
 $\pm 2^\circ$



TITLE: ELEVATED
 SQT ASSM
 SHROUD

DWG NO: ATS-30-Q
 SHEET 1 OF 1




DETAIL 'A'
 SCALE: 3x
 (4 PLCS)



DO NOT SCALE
 FROM THIS PRINT




DETAIL 'B'
 SCALE: 3x




SEE DETAIL 'C'



SECT. "A-A"



DETAIL 'C'
 SCALE: 3x
 (4 PLCS)



MATERIAL:

LCP VECTRA E-130i
 COLOR: BLACK

MAX BOW ALLOWED: .005 [.13]

MAX FLASH ALLOWED: .005 [.13]

25% MAX REGRIND

PLOT SCALE: 1=.25

samtec

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
 PHONE (812) 944-6733 P.O. BOX 1147
 CODE 55322

MADE BY:

BRATCHER 9-6-95

ATS-30-Q
 SHEET 1 OF 1

PROPRIETARY NOTE
 THIS DOCUMENT CONTAINS INFORMATION
 CONFIDENTIAL AND PROPRIETARY TO
 SAMTEC INC. AND SHALL NOT BE
 REPRODUCED OR TRANSFERRED TO
 OTHER DOCUMENTS OR DISCLOSED TO
 OTHERS OR USED FOR ANY PURPOSE
 OTHER THAN THAT FOR WHICH IT WAS
 OBTAINED WITHOUT THE EXPRESSED
 WRITTEN CONSENT OF SAMTEC INC.