

**PRO-M
CP M DM40****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26


D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Use our diode and redundancy modules to connect two power supplies and compensate for a device failing. In addition, our capacity module offers power reserves, guaranteeing purposeful and quick triggering of a circuit breaker, for example.

General ordering data

Available until	2019-06-30
Type	CP M DM40
Order No.	1222220000
Version	Diode module
GTIN (EAN)	4050118005455
Qty.	1 pc(s).
Alternative product	2486110000

**PRO-M
CP M DM40**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	60 mm	Width (inches)	2.362 inch
Height	130 mm	Height (inches)	5.118 inch
Depth	150 mm	Depth (inches)	5.905 inch
Net weight	867 g		

Temperatures

Humidity	5...95 %, no condensation	Operating temperature, max.	70 °C
Operating temperature, min.	-25 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C	Operating temperature	-25 °C...70 °C
Storage temperature	-40 °C...85 °C		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Input

DC input voltage range	18...30 V DC	Input current	2 x 20 A or 1 x 40 A
Rated input voltage	24 V DC	Wire connection method	Screw connection

Output

Continuous output current @ U _{Nominal}	48 A @ 45 °C, 45 A @ 55 °C, 30 A @ 70 °C	Nominal output current for U _{nom}	40 A @ 60 °C
Output current, max.	48 A	Output voltage	Voltage input - 0.7 V
Rated output voltage		Switching thresholds	21.6 V DC, relay is on for Power Good, 20.4 V DC, relay is off for Power Fail
	24 V DC ± 1 %	Wire connection method	Screw connection
Voltage monitoring	Yes, In both inputs		

General data

Degree of efficiency	> 97% @ 24 V Input voltage	Humidity	5...95 %, no condensation
MTBF	> 500,000 h in accordance with IEC 61709 (SN29500)	Mounting position, installation notice	Horizontal on TS35 mounting rail. 50 mm of clearance at top & bottom for air circ. Can mount side by side with no space in between.
Operating temperature	-25 °C...70 °C	Protection degree	IP20

EMC / shock / vibration

Noise emission in accordance with EN55032	Class B	Vibration resistance IEC 60068-2-6	1 g according to EN 50178
Interference immunity test acc. to	EN 61000-4-2 (ESD) EN 61000-4-3 and EN 61000-4-8 (fields) EN 61000-4-4 (burst) EN 61000-4-5 (surge) EN 61000-4-6 (conducted)	Shock resistance IEC 60068-2-27	15 g In all directions

**PRO-M
CP M DM40**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Insulation coordination**

Insulation voltage	0.5 kV _{Input / output - Box}
Protection class	III, with no ground connection, for SELV

Pollution severity	2
--------------------	---

Electrical safety (applied standards)

Electrical machine equipment	Acc. to EN60204
Safety extra-low voltage	SELV according to EN 60950, PELV according to EN 60204

For use with electronic equipment	Acc. to EN50178 / VDE0160
-----------------------------------	---------------------------

Connection data (input)

Conductor cross-section, AWG/kcmil , max.	6
Conductor cross-section, flexible , min.	2.5 mm ²
Conductor cross-section, rigid , min.	0.5 mm ²
Wire connection cross section, flexible (input), max.	10 mm ²

Conductor cross-section, AWG/kcmil , min.	22
Conductor cross-section, rigid , max.	16 mm ²
Number of terminals	4 (1+, 2+, 1-, 2-)

Connection data (output)

Conductor cross-section, AWG/kcmil , max.	6
Conductor cross-section, flexible , max.	10 mm ²
Conductor cross-section, rigid , max.	16 mm ²
Number of terminals	4 (3 +, 4 +, 3 -, 4 -)

Conductor cross-section, AWG/kcmil , min.	22
Conductor cross-section, flexible , min.	2.5 mm ²
Conductor cross-section, rigid , min.	0.5 mm ²

Signalling

Floating contact	Yes
------------------	-----

Approvals

Institute (GERMLLOYD)



Certificate No. (GERMLLOYD)

94767-10

Institute (cULus)



Certificate no. (cULus)

E258476

Classifications

ETIM 6.0	EC002540
eClass 9.0	27-04-07-01
eClass 10.0	27-04-07-01

ETIM 7.0	EC002540
eClass 9.1	27-04-07-01

PRO-M CP M DM40

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	DE_PA5200_160512_001.pdf
Brochure/Catalogue	CAT 4.3 ELECTR 15/16 EN
Engineering Data	EPLAN_WSCAD
Engineering Data	STEP
User Documentation	Operating instructions