

# ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

**GU**



Snap-in Terminal Type, 105°C Standard

series



Anti-Solvent  
Feature  
(Through  
100V only)



- Withstanding 3000 hours application of rated ripple current at 105°C.
- Compliant to the RoHS directive (2011/65/EU).



## Specifications


| Item                          | Performance Characteristics                                                                                                                                                                                                 |                 |      |           |      |                    |        |                                                   |      |  |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------|-----------|------|--------------------|--------|---------------------------------------------------|------|--|
| Category Temperature Range    | - 40 to + 105°C (16 to 250V) , - 25 to +105°C (315 to 450V)                                                                                                                                                                 |                 |      |           |      |                    |        |                                                   |      |  |
| Rated Voltage Range           | 16 to 450V                                                                                                                                                                                                                  |                 |      |           |      |                    |        |                                                   |      |  |
| Rated Capacitance Range       | 47 to 47000μF                                                                                                                                                                                                               |                 |      |           |      |                    |        |                                                   |      |  |
| Capacitance Tolerance         | ± 20% at 120Hz, 20°C                                                                                                                                                                                                        |                 |      |           |      |                    |        |                                                   |      |  |
| Leakage Current               | I ≤ 3√C/V (μA) (After 5 minutes' application of rated voltage) [C : Rated Capacitance (μF) V : Voltage (V)]                                                                                                                 |                 |      |           |      |                    |        |                                                   |      |  |
| Tangent of loss angle (tan δ) | Measurement frequency : 120Hz at 20°C                                                                                                                                                                                       |                 |      |           |      |                    |        |                                                   |      |  |
|                               | Rated voltage(V)                                                                                                                                                                                                            | 16              | 25   | 35        | 50   | 63                 | 80・100 | 160 to 420                                        | 450  |  |
|                               | tan δ (MAX.)                                                                                                                                                                                                                | 0.50            | 0.40 | 0.35      | 0.30 | 0.25               | 0.20   | 0.15                                              | 0.20 |  |
| Stability at Low Temperature  | Measurement frequency : 120Hz                                                                                                                                                                                               |                 |      |           |      |                    |        |                                                   |      |  |
|                               | Rated voltage (V)                                                                                                                                                                                                           |                 |      | 16 to 100 |      | 160 to 250         |        | 315 to 450                                        |      |  |
|                               | Impedance ratio                                                                                                                                                                                                             | Z - 25°C/Z+20°C |      |           | 4    |                    | 3      |                                                   | 8    |  |
|                               | ZT/Z20 (MAX.)                                                                                                                                                                                                               | Z - 40°C/Z+20°C |      |           | 20   |                    | 12     |                                                   | —    |  |
| Endurance                     | The specifications listed at right shall be met when the capacitors are restored to 20°C after D.C. bias plus rated ripple current is applied for 3000 hours at 105°C, the peak voltage shall not exceed the rated voltage. |                 |      |           |      | Capacitance change |        | Within ±20% of the initial capacitance value      |      |  |
|                               |                                                                                                                                                                                                                             |                 |      |           |      | tan δ              |        | 200% or less than the initial specified value     |      |  |
|                               |                                                                                                                                                                                                                             |                 |      |           |      | Leakage current    |        | Less than or equal to the initial specified value |      |  |
| Shelf Life                    | After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the characteristic requirements listed at right.         |                 |      |           |      | Capacitance change |        | Within ±15% of the initial capacitance value      |      |  |
|                               |                                                                                                                                                                                                                             |                 |      |           |      | tan δ              |        | 150% or less than the initial specified value     |      |  |
|                               |                                                                                                                                                                                                                             |                 |      |           |      | Leakage current    |        | Less than or equal to the initial specified value |      |  |
|                               |                                                                                                                                                                                                                             |                 |      |           |      |                    |        |                                                   |      |  |
| Marking                       | Printed with white color letter on black sleeve.                                                                                                                                                                            |                 |      |           |      |                    |        |                                                   |      |  |

## Drawing



※ The other terminal is also available upon request.  
Please refer page 326 for schematic of dimensions.

## Type numbering system (Example : 200V 680μF)



## Frequency coefficient of rated ripple current

| Frequency (Hz) | 50          | 60   | 120  | 300  | 1k   | 10k  | 50k or more |
|----------------|-------------|------|------|------|------|------|-------------|
| Coeff.         | 16 to 100V  | 0.88 | 0.90 | 1.00 | 1.07 | 1.15 | 1.15        |
|                | 160 to 250V | 0.81 | 0.85 | 1.00 | 1.17 | 1.32 | 1.45        |
|                | 315 to 450V | 0.77 | 0.82 | 1.00 | 1.16 | 1.30 | 1.41        |

Minimum order quantity : 50pcs.

- Dimension table in next page.

CAT.8100D

## ■ Dimensions

| 16V (1C)           |                        |                      |                            |              |
|--------------------|------------------------|----------------------|----------------------------|--------------|
| Cap.<br>( $\mu$ F) | Size<br>$\phi$ D×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 6800               | 22 × 25                | 1750                 | 0.98                       | LGU1C682MELZ |
| 8200               | 22 × 30                | 2000                 | 1.08                       | LGU1C822MELZ |
| 10000              | 22 × 30                | 2100                 | 1.20                       | LGU1C103MELZ |
|                    | 25 × 25                | 2050                 | 1.20                       | LGU1C103MELA |
| 12000              | 22 × 35                | 2310                 | 1.31                       | LGU1C123MELZ |
|                    | 25 × 30                | 2300                 | 1.31                       | LGU1C123MELA |
|                    | 30 × 25                | 2380                 | 1.31                       | LGU1C123MELB |
| 15000              | 22 × 40                | 2680                 | 1.46                       | LGU1C153MELZ |
|                    | 25 × 35                | 2680                 | 1.46                       | LGU1C153MELA |
|                    | 30 × 30                | 2570                 | 1.46                       | LGU1C153MELB |
| 18000              | 22 × 45                | 2980                 | 1.60                       | LGU1C183MELZ |
|                    | 25 × 40                | 3160                 | 1.60                       | LGU1C183MELA |
|                    | 30 × 30                | 3000                 | 1.60                       | LGU1C183MELB |
| 22000              | 25 × 45                | 3400                 | 1.77                       | LGU1C223MELA |
|                    | 30 × 35                | 3390                 | 1.77                       | LGU1C223MELB |
|                    | 35 × 30                | 3250                 | 1.77                       | LGU1C223MELC |
| 27000              | 25 × 50                | 3850                 | 1.97                       | LGU1C273MELA |
|                    | 30 × 40                | 3830                 | 1.97                       | LGU1C273MELB |
|                    | 35 × 30                | 3740                 | 1.97                       | LGU1C273MELC |
| 33000              | 30 × 45                | 4300                 | 2.17                       | LGU1C333MELB |
|                    | 35 × 35                | 4270                 | 2.17                       | LGU1C333MELC |
| 39000              | 30 × 50                | 4810                 | 2.36                       | LGU1C393MELB |
|                    | 35 × 40                | 4800                 | 2.36                       | LGU1C393MELC |
| 47000              | 35 × 45                | 5530                 | 2.60                       | LGU1C473MELC |

| 25V (1E)           |                        |                      |                            |              |
|--------------------|------------------------|----------------------|----------------------------|--------------|
| Cap.<br>( $\mu$ F) | Size<br>$\phi$ D×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 4700               | 22 × 25                | 1610                 | 1.02                       | LGU1E472MELZ |
| 5600               | 22 × 30                | 1800                 | 1.12                       | LGU1E562MELZ |
| 6800               | 22 × 30                | 1910                 | 1.23                       | LGU1E682MELZ |
|                    | 25 × 25                | 1910                 | 1.23                       | LGU1E682MELA |
| 8200               | 22 × 35                | 2140                 | 1.35                       | LGU1E822MELZ |
|                    | 25 × 30                | 2340                 | 1.35                       | LGU1E822MELA |
|                    | 30 × 25                | 2250                 | 1.35                       | LGU1E822MELB |
| 10000              | 22 × 40                | 2650                 | 1.50                       | LGU1E103MELZ |
|                    | 25 × 35                | 2610                 | 1.50                       | LGU1E103MELA |
|                    | 30 × 30                | 2610                 | 1.50                       | LGU1E103MELB |
| 12000              | 22 × 45                | 2690                 | 1.64                       | LGU1E123MELZ |
|                    | 25 × 40                | 2810                 | 1.64                       | LGU1E123MELA |
|                    | 30 × 30                | 2740                 | 1.64                       | LGU1E123MELB |
| 15000              | 25 × 45                | 3270                 | 1.83                       | LGU1E153MELA |
|                    | 30 × 35                | 3130                 | 1.83                       | LGU1E153MELB |
|                    | 35 × 30                | 3260                 | 1.83                       | LGU1E153MELC |
| 18000              | 25 × 50                | 3540                 | 2.01                       | LGU1E183MELA |
|                    | 30 × 40                | 3560                 | 2.01                       | LGU1E183MELB |
|                    | 35 × 35                | 3840                 | 2.01                       | LGU1E183MELC |
| 22000              | 30 × 45                | 4240                 | 2.22                       | LGU1E223MELB |
|                    | 35 × 35                | 3960                 | 2.22                       | LGU1E223MELC |
| 27000              | 35 × 45                | 4750                 | 2.46                       | LGU1E273MELC |
| 33000              | 35 × 50                | 5500                 | 2.72                       | LGU1E333MELC |

| 35V (1V)           |                        |                      |                            |              |
|--------------------|------------------------|----------------------|----------------------------|--------------|
| Cap.<br>( $\mu$ F) | Size<br>$\phi$ D×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 3300               | 22 × 25                | 1450                 | 1.01                       | LGU1V332MELZ |
| 3900               | 22 × 30                | 1690                 | 1.10                       | LGU1V392MELZ |
| 4700               | 22 × 35                | 2020                 | 1.21                       | LGU1V472MELZ |
|                    | 25 × 25                | 1780                 | 1.21                       | LGU1V472MELA |
| 5600               | 22 × 35                | 2130                 | 1.32                       | LGU1V562MELZ |
|                    | 25 × 30                | 2040                 | 1.32                       | LGU1V562MELA |
|                    | 30 × 25                | 2120                 | 1.32                       | LGU1V562MELB |
| 6800               | 22 × 40                | 2410                 | 1.46                       | LGU1V682MELZ |
|                    | 25 × 35                | 2310                 | 1.46                       | LGU1V682MELA |
|                    | 30 × 25                | 2310                 | 1.46                       | LGU1V682MELB |
| 8200               | 22 × 50                | 2850                 | 1.60                       | LGU1V822MELZ |
|                    | 25 × 40                | 2730                 | 1.60                       | LGU1V822MELA |
|                    | 30 × 30                | 2750                 | 1.60                       | LGU1V822MELB |
| 10000              | 25 × 45                | 3050                 | 1.77                       | LGU1V103MELA |
|                    | 30 × 35                | 3050                 | 1.77                       | LGU1V103MELB |
| 12000              | 25 × 50                | 3370                 | 1.94                       | LGU1V123MELA |
|                    | 30 × 40                | 3280                 | 1.94                       | LGU1V123MELB |
|                    | 35 × 30                | 3200                 | 1.94                       | LGU1V123MELC |
| 15000              | 30 × 45                | 3740                 | 2.17                       | LGU1V153MELB |
|                    | 35 × 35                | 3690                 | 2.17                       | LGU1V153MELC |
| 18000              | 35 × 40                | 4370                 | 2.38                       | LGU1V183MELC |
| 22000              | 35 × 50                | 4920                 | 2.63                       | LGU1V223MELC |

| 50V (1H)           |                        |                      |                            |              |
|--------------------|------------------------|----------------------|----------------------------|--------------|
| Cap.<br>( $\mu$ F) | Size<br>$\phi$ D×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 1800               | 22 × 25                | 1340                 | 0.90                       | LGU1H182MELZ |
| 2700               | 22 × 30                | 1700                 | 1.10                       | LGU1H272MELZ |
|                    | 25 × 25                | 1700                 | 1.10                       | LGU1H272MELA |
| 3300               | 22 × 35                | 1980                 | 1.21                       | LGU1H332MELZ |
|                    | 25 × 30                | 2000                 | 1.21                       | LGU1H332MELA |
| 3900               | 22 × 40                | 2250                 | 1.32                       | LGU1H392MELZ |
|                    | 25 × 30                | 2280                 | 1.32                       | LGU1H392MELA |
|                    | 30 × 25                | 2220                 | 1.32                       | LGU1H392MELB |
| 4700               | 22 × 45                | 2560                 | 1.45                       | LGU1H472MELZ |
|                    | 25 × 35                | 2610                 | 1.45                       | LGU1H472MELA |
|                    | 30 × 30                | 2580                 | 1.45                       | LGU1H472MELB |
| 5600               | 22 × 50                | 2890                 | 1.58                       | LGU1H562MELZ |
|                    | 25 × 40                | 2810                 | 1.58                       | LGU1H562MELA |
|                    | 30 × 30                | 2950                 | 1.58                       | LGU1H562MELB |
| 6800               | 25 × 45                | 3370                 | 1.74                       | LGU1H682MELA |
|                    | 30 × 35                | 3390                 | 1.74                       | LGU1H682MELB |
|                    | 35 × 30                | 3310                 | 1.74                       | LGU1H682MELC |
| 8200               | 30 × 40                | 3710                 | 1.92                       | LGU1H822MELB |
|                    | 35 × 35                | 3660                 | 1.92                       | LGU1H822MELC |
| 10000              | 30 × 50                | 4090                 | 2.12                       | LGU1H103MELB |
|                    | 35 × 40                | 4070                 | 2.12                       | LGU1H103MELC |
| 12000              | 35 × 45                | 4560                 | 2.32                       | LGU1H123MELC |
| 15000              | 35 × 50                | 4770                 | 2.59                       | LGU1H153MELC |

Rated ripple current (mA<sub>rms</sub>) at 105°C 120Hz

## ■ Dimensions

| 63V (1J)     |                  |                      |                            |              |
|--------------|------------------|----------------------|----------------------------|--------------|
| Cap.<br>(μF) | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 1200         | 22 × 25          | 1250                 | 0.82                       | LGU1J122MELZ |
| 1500         | 22 × 30          | 1470                 | 0.92                       | LGU1J152MELZ |
|              | 25 × 25          | 1440                 | 0.92                       | LGU1J152MELA |
| 1800         | 22 × 30          | 1580                 | 1.01                       | LGU1J182MELZ |
|              | 25 × 25          | 1520                 | 1.01                       | LGU1J182MELA |
| 2200         | 22 × 35          | 1820                 | 1.11                       | LGU1J222MELZ |
|              | 25 × 30          | 1750                 | 1.11                       | LGU1J222MELA |
| 2700         | 22 × 40          | 2070                 | 1.23                       | LGU1J272MELZ |
|              | 25 × 35          | 2110                 | 1.23                       | LGU1J272MELA |
|              | 30 × 25          | 1930                 | 1.23                       | LGU1J272MELB |
| 3300         | 22 × 45          | 2330                 | 1.36                       | LGU1J332MELZ |
|              | 25 × 35          | 2270                 | 1.36                       | LGU1J332MELA |
|              | 30 × 30          | 2240                 | 1.36                       | LGU1J332MELB |
| 3900         | 25 × 40          | 2540                 | 1.48                       | LGU1J392MELA |
|              | 30 × 35          | 2550                 | 1.48                       | LGU1J392MELB |
| 4700         | 25 × 50          | 2970                 | 1.63                       | LGU1J472MELA |
|              | 30 × 40          | 2900                 | 1.63                       | LGU1J472MELB |
|              | 35 × 30          | 2830                 | 1.63                       | LGU1J472MELC |
| 5600         | 30 × 40          | 3280                 | 1.78                       | LGU1J562MELB |
|              | 35 × 35          | 3240                 | 1.78                       | LGU1J562MELC |
| 6800         | 30 × 50          | 3730                 | 1.96                       | LGU1J682MELB |
|              | 35 × 40          | 3710                 | 1.96                       | LGU1J682MELC |
| 8200         | 35 × 45          | 4160                 | 2.15                       | LGU1J822MELC |
| 10000        | 35 × 50          | 4690                 | 2.38                       | LGU1J103MELC |

| 80V (1K)     |                  |                      |                            |              |
|--------------|------------------|----------------------|----------------------------|--------------|
| Cap.<br>(μF) | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 820          | 22 × 25          | 1110                 | 0.76                       | LGU1K821MELZ |
| 1000         | 22 × 25          | 1290                 | 0.84                       | LGU1K102MELZ |
| 1200         | 22 × 30          | 1440                 | 0.92                       | LGU1K122MELZ |
|              | 25 × 25          | 1390                 | 0.92                       | LGU1K122MELA |
| 1500         | 22 × 30          | 1610                 | 1.03                       | LGU1K152MELZ |
|              | 25 × 25          | 1620                 | 1.03                       | LGU1K152MELA |
| 1800         | 22 × 35          | 1830                 | 1.13                       | LGU1K182MELZ |
|              | 25 × 30          | 1860                 | 1.13                       | LGU1K182MELA |
|              | 30 × 25          | 1810                 | 1.13                       | LGU1K182MELB |
| 2200         | 22 × 40          | 2090                 | 1.25                       | LGU1K222MELZ |
|              | 25 × 35          | 2010                 | 1.25                       | LGU1K222MELA |
|              | 30 × 25          | 2100                 | 1.25                       | LGU1K222MELB |
| 2700         | 25 × 40          | 2430                 | 1.39                       | LGU1K272MELZ |
|              | 30 × 30          | 2430                 | 1.39                       | LGU1K272MELB |
| 3300         | 25 × 45          | 2760                 | 1.54                       | LGU1K332MELA |
|              | 30 × 35          | 2780                 | 1.54                       | LGU1K332MELB |
|              | 35 × 30          | 2710                 | 1.54                       | LGU1K332MELC |
| 3900         | 25 × 50          | 2920                 | 1.67                       | LGU1K392MELA |
|              | 30 × 40          | 3120                 | 1.67                       | LGU1K392MELB |
|              | 35 × 30          | 3070                 | 1.67                       | LGU1K392MELC |
| 4700         | 30 × 45          | 3520                 | 1.83                       | LGU1K472MELB |
|              | 35 × 35          | 3500                 | 1.83                       | LGU1K472MELC |
| 5600         | 30 × 50          | 3800                 | 2.00                       | LGU1K562MELB |
|              | 35 × 40          | 3870                 | 2.00                       | LGU1K562MELC |
| 6800         | 35 × 45          | 4190                 | 2.21                       | LGU1K682MELC |

| 100V (2A)    |                  |                      |                            |              |
|--------------|------------------|----------------------|----------------------------|--------------|
| Cap.<br>(μF) | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 560          | 22 × 25          | 1070                 | 0.70                       | LGU2A561MELZ |
| 820          | 22 × 30          | 1350                 | 0.85                       | LGU2A821MELZ |
|              | 25 × 25          | 1350                 | 0.85                       | LGU2A821MELA |
| 1000         | 22 × 30          | 1540                 | 0.94                       | LGU2A102MELZ |
|              | 25 × 30          | 1560                 | 0.94                       | LGU2A102MELA |
| 1200         | 22 × 40          | 1740                 | 1.03                       | LGU2A122MELZ |
|              | 25 × 30          | 1760                 | 1.03                       | LGU2A122MELA |
|              | 30 × 25          | 1710                 | 1.03                       | LGU2A122MELB |
| 1500         | 22 × 45          | 1990                 | 1.16                       | LGU2A152MELZ |
|              | 25 × 35          | 2030                 | 1.16                       | LGU2A152MELA |
|              | 30 × 30          | 2000                 | 1.16                       | LGU2A152MELB |
| 1800         | 25 × 40          | 2280                 | 1.27                       | LGU2A182MELA |
|              | 30 × 35          | 2270                 | 1.27                       | LGU2A182MELB |
| 2200         | 25 × 50          | 2570                 | 1.40                       | LGU2A222MELA |
|              | 30 × 35          | 2590                 | 1.40                       | LGU2A222MELB |
|              | 35 × 30          | 2520                 | 1.40                       | LGU2A222MELC |
| 2700         | 30 × 45          | 2940                 | 1.55                       | LGU2A272MELB |
|              | 35 × 35          | 2900                 | 1.55                       | LGU2A272MELC |
| 3300         | 30 × 50          | 3320                 | 1.72                       | LGU2A332MELB |
|              | 35 × 40          | 3310                 | 1.72                       | LGU2A332MELC |
| 3900         | 35 × 45          | 3690                 | 1.87                       | LGU2A392MELC |
| 4700         | 35 × 50          | 4140                 | 2.05                       | LGU2A472MELC |

| 160V (2C) |                  |                      |                            |              |
|-----------|------------------|----------------------|----------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage<br>Current<br>(mA) | Code         |
| 270       | 20 × 25          | 1100                 | 0.62                       | LGU2C271MELY |
| 330       | 20 × 30          | 1200                 | 0.68                       | LGU2C331MELY |
| 390       | 20 × 30          | 1300                 | 0.74                       | LGU2C391MELY |
|           | 22 × 25          | 1300                 | 0.74                       | LGU2C391MELA |
| 470       | 20 × 35          | 1340                 | 0.82                       | LGU2C471MELY |
|           | 22 × 30          | 1550                 | 0.82                       | LGU2C471MELZ |
|           | 25 × 25          | 1550                 | 0.82                       | LGU2C471MELA |
| 560       | 20 × 40          | 1500                 | 0.89                       | LGU2C561MELY |
|           | 22 × 35          | 1670                 | 0.89                       | LGU2C561MELZ |
|           | 25 × 30          | 1670                 | 0.89                       | LGU2C561MELA |
|           | 30 × 25          | 1670                 | 0.89                       | LGU2C561MELB |
| 680       | 20 × 45          | 1700                 | 0.98                       | LGU2C681MELY |
|           | 22 × 40          | 1820                 | 0.98                       | LGU2C681MELZ |
|           | 25 × 30          | 1820                 | 0.98                       | LGU2C681MELA |
|           | 30 × 25          | 1820                 | 0.98                       | LGU2C681MELB |
| 820       | 22 × 45          | 2040                 | 1.08                       | LGU2C821MELZ |
|           | 25 × 35          | 2040                 | 1.08                       | LGU2C821MELA |
|           | 30 × 30          | 2040                 | 1.08                       | LGU2C821MELB |
|           | 35 × 25          | 2040                 | 1.08                       | LGU2C821MELC |
| 1000      | 22 × 50          | 2250                 | 1.20                       | LGU2C102MELZ |
|           | 25 × 40          | 2250                 | 1.20                       | LGU2C102MELA |
|           | 30 × 30          | 2250                 | 1.20                       | LGU2C102MELB |
|           | 35 × 25          | 2250                 | 1.20                       | LGU2C102MELC |
| 1200      | 25 × 45          | 2490                 | 1.31                       | LGU2C122MELA |
|           | 30 × 35          | 2490                 | 1.31                       | LGU2C122MELB |
|           | 35 × 30          | 2490                 | 1.31                       | LGU2C122MELC |
| 1500      | 30 × 40          | 2840                 | 1.46                       | LGU2C152MELB |
|           | 35 × 30          | 2840                 | 1.46                       | LGU2C152MELC |
| 1800      | 30 × 45          | 3320                 | 1.60                       | LGU2C182MELB |
|           | 35 × 35          | 3000                 | 1.60                       | LGU2C182MELC |
| 2200      | 35 × 45          | 3500                 | 1.77                       | LGU2C222MELC |
| 2700      | 35 × 50          | 4000                 | 1.97                       | LGU2C272MELC |

Rated ripple current (mA rms) at 105°C 120Hz

## ■ Dimensions

| 180V (2Z) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 220       | 20 × 25          | 1000                 | 0.59                    | LGU2Z221MELY |
| 270       | 20 × 30          | 1100                 | 0.66                    | LGU2Z271MELY |
| 330       | 20 × 30          | 1200                 | 0.73                    | LGU2Z331MELY |
|           | 22 × 25          | 1200                 | 0.73                    | LGU2Z331MELZ |
| 390       | 20 × 35          | 1300                 | 0.79                    | LGU2Z391MELY |
|           | 22 × 30          | 1350                 | 0.79                    | LGU2Z391MELZ |
|           | 25 × 25          | 1350                 | 0.79                    | LGU2Z391MELA |
| 470       | 20 × 40          | 1400                 | 0.87                    | LGU2Z471MELY |
|           | 22 × 35          | 1500                 | 0.87                    | LGU2Z471MELZ |
|           | 25 × 30          | 1500                 | 0.87                    | LGU2Z471MELA |
|           | 30 × 25          | 1500                 | 0.87                    | LGU2Z471MELB |
| 560       | 20 × 45          | 1550                 | 0.95                    | LGU2Z561MELY |
|           | 22 × 40          | 1670                 | 0.95                    | LGU2Z561MELZ |
|           | 25 × 30          | 1670                 | 0.95                    | LGU2Z561MELA |
|           | 30 × 25          | 1670                 | 0.95                    | LGU2Z561MELB |
| 680       | 22 × 45          | 1780                 | 1.04                    | LGU2Z681MELZ |
|           | 25 × 35          | 1780                 | 1.04                    | LGU2Z681MELA |
|           | 30 × 30          | 1780                 | 1.04                    | LGU2Z681MELB |
|           | 35 × 25          | 1780                 | 1.04                    | LGU2Z681MELC |
| 820       | 22 × 50          | 2040                 | 1.15                    | LGU2Z821MELZ |
|           | 25 × 40          | 2040                 | 1.15                    | LGU2Z821MELA |
|           | 30 × 30          | 2040                 | 1.15                    | LGU2Z821MELB |
|           | 35 × 25          | 2040                 | 1.15                    | LGU2Z821MELC |
| 1000      | 25 × 45          | 2300                 | 1.27                    | LGU2Z102MELA |
|           | 30 × 35          | 2300                 | 1.27                    | LGU2Z102MELB |
|           | 35 × 30          | 2300                 | 1.27                    | LGU2Z102MELC |
| 1200      | 25 × 50          | 2550                 | 1.39                    | LGU2Z122MELA |
|           | 30 × 40          | 2550                 | 1.39                    | LGU2Z122MELB |
|           | 35 × 30          | 2550                 | 1.39                    | LGU2Z122MELC |
| 1500      | 30 × 45          | 2900                 | 1.55                    | LGU2Z152MELB |
|           | 35 × 35          | 2900                 | 1.55                    | LGU2Z152MELC |
| 1800      | 35 × 45          | 3300                 | 1.70                    | LGU2Z182MELC |
| 2200      | 35 × 50          | 3650                 | 1.88                    | LGU2Z222MELC |

| 200V (2D) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 220       | 20 × 25          | 1000                 | 0.62                    | LGU2D221MELY |
| 270       | 20 × 30          | 1100                 | 0.69                    | LGU2D271MELY |
|           | 22 × 25          | 1100                 | 0.69                    | LGU2D271MELZ |
| 330       | 20 × 35          | 1200                 | 0.77                    | LGU2D331MELY |
|           | 22 × 30          | 1250                 | 0.77                    | LGU2D331MELZ |
|           | 25 × 25          | 1250                 | 0.77                    | LGU2D331MELA |
| 390       | 20 × 40          | 1310                 | 0.83                    | LGU2D391MELY |
|           | 22 × 30          | 1350                 | 0.83                    | LGU2D391MELZ |
|           | 25 × 25          | 1350                 | 0.83                    | LGU2D391MELA |
| 470       | 20 × 45          | 1450                 | 0.91                    | LGU2D471MELY |
|           | 22 × 35          | 1500                 | 0.91                    | LGU2D471MELZ |
|           | 25 × 30          | 1500                 | 0.91                    | LGU2D471MELA |
|           | 30 × 25          | 1500                 | 0.91                    | LGU2D471MELB |
| 560       | 20 × 50          | 1580                 | 1.00                    | LGU2D561MELY |
|           | 22 × 40          | 1670                 | 1.00                    | LGU2D561MELZ |
|           | 25 × 30          | 1670                 | 1.00                    | LGU2D561MELA |
|           | 30 × 25          | 1670                 | 1.00                    | LGU2D561MELB |
| 680       | 22 × 45          | 1780                 | 1.10                    | LGU2D681MELZ |
|           | 25 × 35          | 1780                 | 1.10                    | LGU2D681MELA |
|           | 30 × 30          | 1780                 | 1.10                    | LGU2D681MELB |
|           | 35 × 25          | 1780                 | 1.10                    | LGU2D681MELC |
| 820       | 25 × 45          | 2040                 | 1.21                    | LGU2D821MELA |
|           | 30 × 30          | 2040                 | 1.21                    | LGU2D821MELB |
|           | 35 × 25          | 2040                 | 1.21                    | LGU2D821MELC |
| 1000      | 25 × 50          | 2300                 | 1.34                    | LGU2D102MELA |
|           | 30 × 35          | 2300                 | 1.34                    | LGU2D102MELB |
|           | 35 × 30          | 2300                 | 1.34                    | LGU2D102MELC |
| 1200      | 30 × 40          | 2650                 | 1.46                    | LGU2D122MELB |
|           | 35 × 35          | 2650                 | 1.46                    | LGU2D122MELC |
| 1500      | 30 × 50          | 3080                 | 1.64                    | LGU2D152MELB |
|           | 35 × 40          | 3080                 | 1.64                    | LGU2D152MELC |
| 1800      | 35 × 45          | 3480                 | 1.80                    | LGU2D182MELC |
| 2200      | 35 × 50          | 3780                 | 1.98                    | LGU2D222MELC |

| 220V (2P) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 180       | 20 × 25          | 900                  | 0.59                    | LGU2P181MELY |
| 220       | 20 × 30          | 1000                 | 0.66                    | LGU2P221MELY |
|           | 22 × 25          | 1000                 | 0.66                    | LGU2P221MELZ |
| 270       | 20 × 35          | 1150                 | 0.73                    | LGU2P271MELY |
|           | 22 × 30          | 1150                 | 0.73                    | LGU2P271MELZ |
| 330       | 20 × 40          | 1250                 | 0.80                    | LGU2P331MELY |
|           | 22 × 35          | 1250                 | 0.80                    | LGU2P331MELZ |
|           | 25 × 25          | 1250                 | 0.80                    | LGU2P331MELA |
| 390       | 20 × 45          | 1400                 | 0.87                    | LGU2P391MELY |
|           | 22 × 35          | 1400                 | 0.87                    | LGU2P391MELZ |
|           | 25 × 30          | 1400                 | 0.87                    | LGU2P391MELA |
| 470       | 20 × 50          | 1450                 | 0.96                    | LGU2P471MELY |
|           | 22 × 40          | 1450                 | 0.96                    | LGU2P471MELZ |
|           | 25 × 35          | 1450                 | 0.96                    | LGU2P471MELA |
|           | 30 × 25          | 1450                 | 0.96                    | LGU2P471MELB |
| 560       | 22 × 45          | 1700                 | 1.05                    | LGU2P561MELZ |
|           | 25 × 40          | 1700                 | 1.05                    | LGU2P561MELA |
|           | 30 × 30          | 1700                 | 1.05                    | LGU2P561MELB |
| 680       | 25 × 45          | 1780                 | 1.16                    | LGU2P681MELA |
|           | 30 × 35          | 1780                 | 1.16                    | LGU2P681MELB |
|           | 35 × 25          | 1780                 | 1.16                    | LGU2P681MELC |
| 820       | 25 × 50          | 2100                 | 1.27                    | LGU2P821MELA |
|           | 30 × 40          | 2100                 | 1.27                    | LGU2P821MELB |
|           | 35 × 30          | 2100                 | 1.27                    | LGU2P821MELC |
| 1000      | 30 × 45          | 2400                 | 1.40                    | LGU2P102MELB |
|           | 35 × 35          | 2400                 | 1.40                    | LGU2P102MELC |
| 1200      | 30 × 50          | 2600                 | 1.54                    | LGU2P122MELB |
|           | 35 × 40          | 2600                 | 1.54                    | LGU2P122MELC |
| 1500      | 35 × 45          | 3000                 | 1.72                    | LGU2P152MELC |

| 250V (2E) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 150       | 20 × 25          | 790                  | 0.58                    | LGU2E151MELY |
| 180       | 20 × 30          | 900                  | 0.63                    | LGU2E181MELY |
| 220       | 20 × 30          | 1000                 | 0.70                    | LGU2E221MELY |
|           | 22 × 25          | 1000                 | 0.70                    | LGU2E221MELZ |
| 270       | 20 × 35          | 1100                 | 0.77                    | LGU2E271MELY |
|           | 22 × 35          | 1180                 | 0.77                    | LGU2E271MELZ |
|           | 25 × 25          | 1180                 | 0.77                    | LGU2E271MELA |
| 330       | 20 × 40          | 1200                 | 0.86                    | LGU2E331MELY |
|           | 22 × 40          | 1300                 | 0.86                    | LGU2E331MELZ |
|           | 25 × 30          | 1300                 | 0.86                    | LGU2E331MELA |
|           | 30 × 25          | 1300                 | 0.86                    | LGU2E331MELB |
| 390       | 20 × 50          | 1450                 | 0.93                    | LGU2E391MELY |
|           | 22 × 45          | 1490                 | 0.93                    | LGU2E391MELZ |
|           | 25 × 35          | 1490                 | 0.93                    | LGU2E391MELA |
|           | 30 × 25          | 1490                 | 0.93                    | LGU2E391MELB |
| 470       | 22 × 50          | 1650                 | 1.02                    | LGU2E471MELZ |
|           | 25 × 40          | 1650                 | 1.02                    | LGU2E471MELA |
|           | 30 × 30          | 1650                 | 1.02                    | LGU2E471MELB |
|           | 35 × 25          | 1650                 | 1.02                    | LGU2E471MELC |
| 560       | 25 × 45          | 1800                 | 1.12                    | LGU2E561MELA |
|           | 30 × 35          | 1800                 | 1.12                    | LGU2E561MELB |
|           | 35 × 25          | 1800                 | 1.12                    | LGU2E561MELC |
| 680       | 25 × 50          | 2000                 | 1.23                    | LGU2E681MELA |
|           | 30 × 40          | 2000                 | 1.23                    | LGU2E681MELB |
|           | 35 × 30          | 2000                 | 1.23                    | LGU2E681MELC |
| 820       | 30 × 45          | 2300                 | 1.35                    | LGU2E821MELB |
|           | 35 × 35          | 2300                 | 1.35                    | LGU2E821MELC |
| 1000      | 30 × 50          | 2470                 | 1.50                    | LGU2E102MELB |
|           | 35 × 40          | 2470                 | 1.50                    | LGU2E102MELC |
| 1200      | 35 × 45          | 2600                 | 1.64                    | LGU2E122MELC |
| 1500      | 35 × 50          | 3000                 | 1.83                    | LGU2E152MELC |

Rated ripple current (mA) at 105°C 120Hz

CAT.8100D

## ■ Dimensions

| 315V (2F) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 82        | 20 × 25          | 640                  | 0.48                    | LGU2F820MELY |
| 100       | 20 × 30          | 690                  | 0.53                    | LGU2F101MELY |
| 120       | 20 × 30          | 750                  | 0.58                    | LGU2F121MELY |
|           | 22 × 25          | 750                  | 0.58                    | LGU2F121MELZ |
| 150       | 20 × 35          | 820                  | 0.65                    | LGU2F151MELY |
|           | 22 × 30          | 820                  | 0.65                    | LGU2F151MELZ |
|           | 25 × 25          | 820                  | 0.65                    | LGU2F151MELA |
| 180       | 20 × 40          | 900                  | 0.71                    | LGU2F181MELY |
|           | 22 × 35          | 920                  | 0.71                    | LGU2F181MELZ |
|           | 25 × 25          | 920                  | 0.71                    | LGU2F181MELA |
| 220       | 20 × 50          | 1000                 | 0.78                    | LGU2F221MELY |
|           | 22 × 40          | 1040                 | 0.78                    | LGU2F221MELZ |
|           | 25 × 30          | 1040                 | 0.78                    | LGU2F221MELA |
|           | 30 × 25          | 1040                 | 0.78                    | LGU2F221MELB |
| 270       | 22 × 45          | 1160                 | 0.87                    | LGU2F271MELY |
|           | 25 × 35          | 1160                 | 0.87                    | LGU2F271MELA |
|           | 30 × 25          | 1160                 | 0.87                    | LGU2F271MELB |
| 330       | 22 × 50          | 1330                 | 0.96                    | LGU2F331MELZ |
|           | 25 × 40          | 1330                 | 0.96                    | LGU2F331MELA |
|           | 30 × 30          | 1330                 | 0.96                    | LGU2F331MELB |
|           | 35 × 25          | 1330                 | 0.96                    | LGU2F331MELC |
| 390       | 25 × 45          | 1470                 | 1.05                    | LGU2F391MELA |
|           | 30 × 35          | 1470                 | 1.05                    | LGU2F391MELB |
|           | 35 × 30          | 1470                 | 1.05                    | LGU2F391MELC |
| 470       | 25 × 50          | 1700                 | 1.15                    | LGU2F471MELA |
|           | 30 × 40          | 1700                 | 1.15                    | LGU2F471MELB |
|           | 35 × 30          | 1700                 | 1.15                    | LGU2F471MELC |
| 560       | 30 × 45          | 2050                 | 1.26                    | LGU2F561MELB |
|           | 35 × 35          | 2050                 | 1.26                    | LGU2F561MELC |
| 680       | 30 × 50          | 2170                 | 1.38                    | LGU2F681MELB |
|           | 35 × 40          | 2170                 | 1.38                    | LGU2F681MELC |
| 820       | 35 × 45          | 2200                 | 1.52                    | LGU2F821MELC |

| 400V (2G) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 56        | 20 × 25          | 510                  | 0.44                    | LGU2G560MELY |
| 68        | 20 × 30          | 560                  | 0.49                    | LGU2G680MELY |
| 82        | 20 × 30          | 640                  | 0.54                    | LGU2G820MELY |
|           | 22 × 25          | 640                  | 0.54                    | LGU2G820MELZ |
| 100       | 20 × 35          | 700                  | 0.60                    | LGU2G101MELY |
|           | 22 × 30          | 700                  | 0.60                    | LGU2G101MELZ |
|           | 25 × 25          | 700                  | 0.60                    | LGU2G101MELA |
| 120       | 20 × 40          | 750                  | 0.65                    | LGU2G121MELY |
|           | 22 × 35          | 750                  | 0.65                    | LGU2G121MELZ |
|           | 25 × 25          | 750                  | 0.65                    | LGU2G121MELA |
| 150       | 20 × 45          | 830                  | 0.73                    | LGU2G151MELY |
|           | 22 × 40          | 880                  | 0.73                    | LGU2G151MELZ |
|           | 25 × 30          | 880                  | 0.73                    | LGU2G151MELA |
|           | 30 × 25          | 880                  | 0.73                    | LGU2G151MELB |
| 180       | 22 × 45          | 980                  | 0.80                    | LGU2G181MELY |
|           | 25 × 35          | 980                  | 0.80                    | LGU2G181MELA |
|           | 30 × 30          | 980                  | 0.80                    | LGU2G181MELB |
|           | 35 × 25          | 980                  | 0.80                    | LGU2G181MELC |
| 220       | 22 × 50          | 1100                 | 0.88                    | LGU2G221MELY |
|           | 25 × 40          | 1100                 | 0.88                    | LGU2G221MELA |
|           | 30 × 30          | 1100                 | 0.88                    | LGU2G221MELB |
|           | 35 × 25          | 1100                 | 0.88                    | LGU2G221MELC |
| 270       | 25 × 45          | 1220                 | 0.98                    | LGU2G271MELA |
|           | 30 × 35          | 1220                 | 0.98                    | LGU2G271MELB |
|           | 35 × 30          | 1220                 | 0.98                    | LGU2G271MELC |
| 330       | 25 × 50          | 1440                 | 1.08                    | LGU2G331MELA |
|           | 30 × 40          | 1440                 | 1.08                    | LGU2G331MELB |
|           | 35 × 30          | 1440                 | 1.08                    | LGU2G331MELC |
| 390       | 30 × 45          | 1600                 | 1.18                    | LGU2G391MELB |
|           | 35 × 35          | 1600                 | 1.18                    | LGU2G391MELC |
| 470       | 30 × 50          | 1900                 | 1.30                    | LGU2G471MELB |
|           | 35 × 40          | 1900                 | 1.30                    | LGU2G471MELC |
| 560       | 35 × 45          | 2120                 | 1.41                    | LGU2G561MELC |

| 420V (W6) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 56        | 20 × 25          | 510                  | 0.46                    | LGUW6560MELY |
| 68        | 20 × 30          | 560                  | 0.50                    | LGUW6680MELY |
| 82        | 20 × 35          | 640                  | 0.55                    | LGUW6820MELY |
|           | 22 × 25          | 640                  | 0.55                    | LGUW6820MELZ |
| 100       | 20 × 35          | 700                  | 0.61                    | LGUW6101MELY |
|           | 22 × 30          | 700                  | 0.61                    | LGUW6101MELZ |
|           | 25 × 25          | 700                  | 0.61                    | LGUW6101MELA |
| 120       | 20 × 40          | 750                  | 0.67                    | LGUW6121MELY |
|           | 22 × 35          | 750                  | 0.67                    | LGUW6121MELZ |
|           | 25 × 30          | 750                  | 0.67                    | LGUW6121MELA |
| 150       | 20 × 50          | 880                  | 0.75                    | LGUW6151MELY |
|           | 22 × 40          | 880                  | 0.75                    | LGUW6151MELZ |
|           | 25 × 35          | 880                  | 0.75                    | LGUW6151MELA |
|           | 30 × 25          | 880                  | 0.75                    | LGUW6151MELB |
| 180       | 22 × 45          | 950                  | 0.82                    | LGUW6181MELZ |
|           | 25 × 35          | 950                  | 0.82                    | LGUW6181MELA |
|           | 30 × 30          | 950                  | 0.82                    | LGUW6181MELB |
| 220       | 22 × 50          | 1100                 | 0.91                    | LGUW6221MELZ |
|           | 25 × 45          | 1100                 | 0.91                    | LGUW6221MELA |
|           | 30 × 35          | 1100                 | 0.91                    | LGUW6221MELB |
|           | 35 × 25          | 1100                 | 0.91                    | LGUW6221MELC |
| 270       | 25 × 50          | 1220                 | 1.01                    | LGUW6271MELA |
|           | 30 × 40          | 1220                 | 1.01                    | LGUW6271MELB |
|           | 35 × 30          | 1220                 | 1.01                    | LGUW6271MELC |
| 330       | 30 × 45          | 1450                 | 1.11                    | LGUW6331MELB |
|           | 35 × 35          | 1450                 | 1.11                    | LGUW6331MELC |
| 390       | 30 × 50          | 1550                 | 1.21                    | LGUW6391MELB |
|           | 35 × 40          | 1550                 | 1.21                    | LGUW6391MELC |
| 470       | 35 × 45          | 1900                 | 1.33                    | LGUW6471MELC |
| 560       | 35 × 50          | 2150                 | 1.45                    | LGUW6561MELC |

| 450V (2W) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 47        | 20 × 25          | 390                  | 0.43                    | LGU2W470MELY |
| 56        | 20 × 30          | 510                  | 0.47                    | LGU2W560MELY |
| 68        | 20 × 35          | 560                  | 0.52                    | LGU2W680MELY |
|           | 20 × 35          | 640                  | 0.57                    | LGU2W820MELY |
| 82        | 22 × 30          | 640                  | 0.57                    | LGU2W820MELZ |
|           | 25 × 25          | 640                  | 0.57                    | LGU2W820MELA |
| 100       | 20 × 45          | 690                  | 0.63                    | LGU2W101MELY |
|           | 22 × 35          | 690                  | 0.63                    | LGU2W101MELZ |
|           | 25 × 30          | 690                  | 0.63                    | LGU2W101MELA |
| 120       | 20 × 50          | 750                  | 0.69                    | LGU2W121MELY |
|           | 22 × 40          | 800                  | 0.69                    | LGU2W121MELZ |
|           | 25 × 30          | 800                  | 0.69                    | LGU2W121MELA |
|           | 30 × 25          | 800                  | 0.69                    | LGU2W121MELB |
| 150       | 22 × 45          | 880                  | 0.77                    | LGU2W151MELZ |
|           | 25 × 35          | 880                  | 0.77                    | LGU2W151MELA |
|           | 30 × 30          | 880                  | 0.77                    | LGU2W151MELB |
| 180       | 22 × 50          | 1000                 | 0.85                    | LGU2W181MELZ |
|           | 25 × 40          | 1000                 | 0.85                    | LGU2W181MELA |
|           | 30 × 30          | 1000                 | 0.85                    | LGU2W181MELB |
| 220       | 25 × 45          | 1120                 | 0.94                    | LGU2W221MELA |
|           | 30 × 35          | 1120                 | 0.94                    | LGU2W221MELB |
|           | 35 × 30          | 1120                 | 0.94                    | LGU2W221MELC |
| 270       | 30 × 40          | 1280                 | 1.04                    | LGU2W271MELB |
|           | 35 × 35          | 1280                 | 1.04                    | LGU2W271MELC |
| 330       | 30 × 50          | 1450                 | 1.15                    | LGU2W331MELB |
|           | 35 × 40          | 1450                 | 1.15                    | LGU2W331MELC |
| 390       | 35 × 40          | 1500                 | 1.25                    | LGU2W391MELC |
| 470       | 35 × 50          | 1850                 | 1.37                    | LGU2W471MELC |

Rated ripple current (mA) at 105°C 120Hz

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Nichicon:

[LGU1J222MELZ](#) [LGU2D152MELC](#) [LGU2W221MHLC](#) [LGU2W820MESA](#) [LGUW6221MELC](#) [LGU2D821MELB](#)  
[LGU2G471MELB](#) [LGU1H103MELC](#) [LGU1H272MELZ](#) [LGU1H472MELZ](#) [LGU1H822MELB](#) [LGU2D102MELB](#)  
[LGU2D681MELB](#) [LGU2E181MELENA](#) [LGU2G221MELB](#) [LGU2G221MELC](#) [LGU2G271MELA](#) [LGU2G560MELY](#)  
[LGU2G820MELZ](#) [LGU2W101MELZ](#) [LGU2W181MELA](#) [LGU2W271MELB](#) [LGU2W271MELENA](#) [LGUW6151MELZ](#)  
[LGU1H103MELB](#) [LGU1H272MELA](#) [LGU2W101MELA](#) [LGU1K392MHLC](#) [LGU2G121MELZ](#) [LGU2G391MELB](#)  
[LGU2W151MELB](#) [LGU2W221MELB](#) [LGU2W221MELC](#) [LGU2W331MELC](#) [LGU2W391MELC](#) [LGU1K562MELC](#)  
[LGU2G221MELZ](#) [LGU1K102MELZ](#) [LGU2W121MELZ](#) [LGU2W121MELB](#) [LGU2G331MHLA](#) [LGU2G331MHLB](#)  
[LGUW6221MHLC](#) [LGU2F331MELB](#) [LGU2W470MHLY](#) [LGU2W271MHLB](#) [LGU2C561MHLB](#) [LGU2W820MELA](#)  
[LGU2C182MHLC](#) [LGU2W181MHLA](#) [LGU2D681MHLA](#) [LGU2E821MHLC](#) [LGU1C103MELA](#) [LGU1C103MHLA](#)  
[LGU1C223MELA](#) [LGU1C223MHLA](#) [LGU1H103MHLC](#) [LGU1H472MELB](#) [LGU1H472MHLZ](#) [LGU1H682MELC](#)  
[LGU1H822MHLB](#) [LGU1J332MELA](#) [LGU1V103MELA](#) [LGU1V103MHLA](#) [LGU1V682MHLA](#) [LGU2D102MELC](#)  
[LGU2D102MHLB](#) [LGU2D102MHLC](#) [LGU2D122MHLC](#) [LGU2D152MHLC](#) [LGU2D221MHLY](#) [LGU2D561MELA](#)  
[LGU2D681MELA](#) [LGU2D681MHLB](#) [LGU2D821MHLB](#) [LGU2E181MHLENA](#) [LGU2E221MELY](#) [LGU2E221MELZ](#)  
[LGU2E471MELB](#) [LGU2E681MELB](#) [LGU2G101MELA](#) [LGU2G101MELZ](#) [LGU2G101MHLA](#) [LGU2G121MDLA](#)  
[LGU2G121MELA](#) [LGU2G121MHLA](#) [LGU2G151MELA](#) [LGU2G181MELB](#) [LGU2G221MHLB](#) [LGU2G221MHLC](#)  
[LGU2G271MHLA](#) [LGU2G331MELB](#) [LGU2G331MELC](#) [LGU2G391MHLC](#) [LGU2G471MELC](#) [LGU2G560MHLY](#)  
[LGU2G561MHLC](#) [LGU2W101MHLZ](#) [LGU2W471MELC](#) [LGU2W820MHSA](#)