

1671A Coax - 50 Ohm Microwave Cable

For more Information
please call

1-800-Belden1

**General Description:**

RG-405/U type, 24 AWG solid .020" silver-plated copper-covered steel conductor, TFE Teflon® insulation, copper-tin composite shield (100% coverage), unjacketed.

Physical Characteristics (Overall)**Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	24	Solid	SPCCS - Silver Plated Copper Covered Steel	0.508

Total Number of Conductors: 1

Insulation**Insulation Material:**

Insulation Trade Name	Insulation Material	Dia. (mm)
Teflon®	TFE - Tetrafluoroethylene	1.5748

Outer Shield**Outer Shield Material:**

Layer #	Type	Outer Shield Material	Coverage (%)
1	Tape	Copper Foil	100
2	Braid	Tin-Filled Composite	100

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
Unjacketed

Overall Cable

Overall Nominal Diameter: 2.159 mm

Mechanical Characteristics (Overall)

Operating Temperature Range:	-70°C To +200°C
UL Temperature Rating:	105°C (UL AWM Style 10245)
Non-UL Temperature Rating:	200°C
Bulk Cable Weight:	17.858 Kg/Km
Max. Recommended Pulling Tension:	115.653 N
Min. Bend Radius/Minor Axis:	3.048 mm
Min. Bend Radius (Continuous Flexing):	9.398 mm
Min. Bend Radius (Overall):	25.400 mm

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

AWM Specification:	UL Style 10245 (30 V 105°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes

1671A Coax - 50 Ohm Microwave Cable

EU Directive 2002/95/EC (RoHS):	Yes
---------------------------------	-----

EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005
---------------------------------------	------------

EU Directive 2002/96/EC (WEEE):	Yes
---------------------------------	-----

EU Directive 2003/11/EC (BFR):	Yes
--------------------------------	-----

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

RG Type:	405/U
----------	-------

Flame Test

Other Flame Test:	Horizontal Wire
-------------------	-----------------

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Suitability - Outdoor:	Yes
------------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)**Nom. Characteristic Impedance:**

Impedance (Ohm)

50

Nom. Inductance:

Inductance (μH/m)

0.22967

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

96.7895

Nominal Velocity of Propagation:

VP (%)

69.5

Nominal Delay:

Delay (ns/m)

4.79026

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

210.64

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

33.4662

Maximum VSWR:

Freq. (MHz)	Max. VSWR
-------------	-----------

500	1.1:1
-----	-------

20000	1.3:1
-------	-------

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
-------------	-----------------------

500	49.215
-----	--------

1000	72.8382
------	---------

2000	107.617
------	---------

3000	135.177
------	---------

5000	180.127
------	---------

7000	217.858
------	---------

10000	266.417
-------	---------

15000	334.662
-------	---------

1671A Coax - 50 Ohm Microwave Cable

18000	370.753
20000	393.72

Max. Power Rating:

Freq. (MHz)	Rating (W)
500	180
1000	119
2000	79
3000	62
5000	46
7000	37
10000	30
15000	24
18000	21
20000	20

Max. Operating Voltage - UL:

Voltage
30 V RMS (UL AWM Style 10245)

Max. Operating Voltage - Non-UL:

Voltage
1500 V RMS

Other Electrical Characteristic 1:

Shield effectiveness values are typical/nominal values.

Shield Effectiveness:

Freq. (MHz)	Effectiveness (dB)
9000.000	120.000

Misc. Information (Overall)**Notes (Overall)**

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1671A TIN100	30 MT	0.862 KG	TIN - COLOR		#24 TFE BRD TINNED COAX
1671A TIN1000	305 MT	5.443 KG	TIN - COLOR	V	#24 TFE BRD TINNED COAX
1671A TIN50	15 MT	0.499 KG	TIN - COLOR		#24 TFE BRD TINNED COAX
1671A TIN500	152 MT	2.948 KG	TIN - COLOR	V	#24 TFE BRD TINNED COAX

Notes:

V = 250' PUT-UP EXACT LENGTH MAXIMUM OF 3 PIECES MINIMUM LENGTH 50' 500' PUT-UP EXACT LENGTH MAXIMUM OF 5 PIECES MINIMUM LENGTH 50'

Test Reports**a) UL**

- i) UL Test Reports are available on-line through the UL Client Document Access web portal.
- ii) UL Inspection Reports are also available through the UL Client Document Access web portal.

b) CSA

- i) CSA "Descriptive Report and Test Results" documents are available on the CSA Gateway Portal.
- ii) CSA Inspection Reports are maintained on the CSA issued 'flash drive' at each manufacturing location.

* other test data may be available if requested at time of order.

Revision Number: 4 Revision Date: 11-13-2012

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

1671A Coax - 50 Ohm Microwave Cable

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.