

Modern Digital Multimeter



Specifications:

Basic Functions	Range	Best Accuracy
DC Voltage	600mV/6V/60V/600V/1,000V	± (0.5% +3)
AC Voltage	600mV/6V/60V/600V/1,000V	± (1% +2)
DC Current	60mA/600mA/10A	± (1.2% +3)
AC Current	60mA/600mA/10A	± (2% +5)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	± (1% +2)
Capacitance	6nF/60nF/600nF/6μF/60μF/600μF/6mF	± (4% +3)
Temperature (°C)	-40°C to 1,000°C	± (1% +3)
Frequency	6kHz/60kHz/600kHz/6MHz/60MHz	± (0.05% +3)

Special Functions

Fused 10A Range		✓
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
RS232C		✓
Display Backlight		✓
Full Icon Display		✓
Sleep Mode		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max Display	5,999	

General Characteristics:

Power	9V Battery (6F22)
LCD Size	63mm × 31mm
Product Net Weight	Around 312g
Product Size	177mm × 73.5mm × 35mm
Standard Accessories	Test Lead, Battery, English Manual , Test Clip, Software, Point Contact Temperature Probe, RS232C Interface Cable
Certifications	UL, cUL Pending

Part Number Table

Description	Part Number
Modern Digital Multimeter	72-7750

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.

