

Distributor list

DELPHI	Languages ▼ Search: by P/N or text	Registered users Login Password Forgot password?
	▶ DELPHI GROUP ▶ PRO	DDUCTS PAPPLICATIONS CONTACT US
↑ Home		
Quick Links Start > Search=54001864* >	54001864	
ROHS/LF P/N Search 54001864 54001864 - ADEV 4	I.2 mm Female Terminal	Add to Favorites
Documentation	ACTIVE	
Customer drawing search Free search		FCI Brings You More Contact our sales/technical support Sample request
Services 🖻		La / pampie request

Download document

Specifications

General Dimensional Electrical Mechanical Ph	nysical Environmental Other Features	
General		
Product Type	Terminal system	
Terminal size (in mm)	1.2	
Family	APEX 1.2	
Features	Suitable for secondary lock High current carrying capacity 180° terminal orientation Design compatible with a large range of connector sealing technologies	
Dimensional		
Wire size range Min - Max	AVVG 16 - 18	
Pitch	3.5 mm	
Electrical	Type Co	
Current Carrying Capacity at 23°C	25A	
Current Carrying Capacity at 85°C	25A	
Current Carrying Capacity at 100°C	18A	
Current Carrying Capacity at 125℃	10A	
Maximum Insulation (in mm)	3	
Resistance (Contact)	< 0.5 mohms	
Mechanical		
Contact mating force	< 5N	
Single Wire Seal Compatible	Compatible	
Contact unmating force	< 1N	
Physical	all transfer	
Plating	Sn	
Material	CuFeP/CuBe	
Environmental	17 × 5	
IMDS	Yes	
Other Features		
Market	Passenger Vehicles	
Туре	Female	
Tradename	Apex	
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.	