

PRODUCT DATASHEET Lenina series

last update 18/3/2013



15 degrees

Available

88 %



Ordering number CN12600_LENINA-S

Family Lenina
Type RefPack

LED BXRA ES Rectangle cd/lm (simulated) 0.000
Color Metal Gerber File Available

FWHM

Efficiency

Gerber File

Color Metal Diameter 74 mm Height 46.25 mm Style Round PC Optic Material PC Holder Material Fastening Screw Status On production

Ordering number CN12603_LENINA-S-DL

Family Lenina FWHM 20 degrees
Type RefPack Efficiency 80 %

LED BXRA ES Rectangle cd/lm (simulated) 0.000

Color Metal
Diameter 74 mm
Height 48.35 mm
Style Round
Optic Material PC
Holder Material PC
Fastening Screw

Status On production

Ordering number CN12601_LENINA-M

Family Lenina FWHM 29 degrees Type RefPack Efficiency 86 %

LED BXRA ES Rectangle cd/lm (simulated) 0.000
Color Metal Gerber File Available

Color Metal Diameter 74 mm Height 46.25 mm Round Style PC Optic Material Holder Material PC Fastening Screw Status On production

Ordering number CN12604_LENINA-M-DL

Family Lenina FWHM 36 degrees Type RefPack Efficiency 78 %

LED BXRA ES Rectangle cd/lm (simulated) 0.000
Color Metal Gerber File Available

Diameter 74 mm
Height 48.35 mm
Style Round
Optic Material PC
Holder Material PC
Fastening -

Status On production

June 18th 2014 13:05 Copyright Ledil Oy - Subject to change without prior notice - Page 1/4



PRODUCT DATASHEET Lenina series

last update 18/3/2013





Ordering number CN12602_LENINA-W

Family Lenina Type RefPack

LED **BXRA ES Rectangle**

Color Metal Diameter 74 mm Height 46.25 mm Style Round PC Optic Material PC Holder Material Screw Fastening Status On production **FWHM** 54 degrees Efficiency 86 %

Gerber File Available

(simulated) 0.000

54 degrees

Available

72.5 degrees

84 %

0.567

Available

Reflector twist-and-locks into included base part that

holds COB in place. Base part is attached into heat

(simulated) 0.000

78 %

cd/lm

FWHM

cd/lm

FWHM

cd/lm

Efficiency

Gerber File

sink with screws.

Efficiency

Gerber File

Ordering number CN12605_LENINA-W-DL

Family Lenina Type RefPack

LED BXRA ES Rectangle

Metal Color Diameter 74 mm 48.35 mm Height Round Style Optic Material PC Holder Material PC

Status On production

Fastening

Ordering number CN12974_LENINA-XW-DL

Lenina Family RefPack Type **BXRA ES Rectangle** LED Color White Diameter 74 mm 48.35 mm Height Round Style Optic Material PC Holder Material PC

Fastening Socket Status On production

Ordering number CN12960_LENINA-XW

Family Lenina RefPack Type LED **BXRA ES Rectangle**

Color White Diameter 74 mm Height 46.25 mm Style Round Optic Material PC Holder Material PC

Fastening Socket Status On production **FWHM** 74 degrees Efficiency 89 % cd/lm 0.611 Gerber File Available

Reflector twist-and-locks into included base part that holds COB in place. Base part is attached into heat

sink with screws.

June 18th 2014 13:05 Copyright Ledil Oy - Subject to change without prior notice - Page 2/4



PRODUCT DATASHEET Lenina series



last update 18/3/2013

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



PRODUCT DATASHEET Lenina series

BRIDGELUX

last update 18/3/2013

GENERAL INFORMATION


- Product series especially designed & optimized for BXRA ES Rectangle series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PC with high UV and temperature resistance (120 degrees of Celcius / 248 degrees of Fahrenheit). Allows use of high current and temperature conditions.

Please find more information about used materials from below:


http://ledil.fi/sites/default/files/Documents/Technical/Material/PC%20Makrolon%202400_2407_2456_2458-UL.pdf


- Reflector is made of aluminium coated PC (120 degrees of Celcius / 248 degrees of Fahrenheit) with protective lacquer (short term 100 degrees of Celcius / 212 degrees of Fahrenheit).
- Optic holder molded by high quality PC material (120 dergees of Celcius / 248 dégrees of Fahrenheit).

Absolute intensity of CN12974_LENINA-XW-DL




Absolute intensity of CN12960_LENINA-XW







Luminaire: LEDIL OY CN12974_LENINA-XW-DL Eff.84.2% Lamps: 1 x BXRA ES Rectangle (790.36Im@250mA)



Luminaire: LEDIL OY CN12960_LENINA-XW Eff.88,8% Lamps: 1 x BXRA ES Rectangle (790.36Im@250mA)



Luminaire: LEDIL OY CN12974_LENINA-XW-DL Eff.84.2% Lamps: 1 x BXRA ES Rectangle (790.36lm@250mA)



Luminaire: LEDIL OY CN12960_LENINA-XW Eff.88,8% Lamps: 1 x BXRA ES Rectangle (790.36Im@250mA)

