

NTE950/NTE951/NTE977 Integrated Circuit Positive 3 Terminal Voltage Regulator, 100mA

Description:

The NTE950, NTE951, and NTE977 are positive 3-terminal voltage regulators in available in a TO92 type package. With adequate heat sinking these regulators can deliver 100mA output current. Current limiting is included to limit peak output current to safe value. Safe area protection for the output transistors is provided to limit internal power dissipation. If internal power dissipation becomes too high for the heat sinking provided, the thermal shutdown circuit takes over preventing the IC from overheating.

When used as a zener diode/resistor combination replacement, these devices usually result in an effective output impedance improvement of two orders of magnitude, and lower quiescent current. These regulators can provide local on card regulation, eliminating the distribution problems associated with single point regulation. Typical applications include use in logic systems, instrumentation, HiFi, and other solid state electronic equipment. Although designed primarily as fixed voltage regulators these devices can be used with external components to obtain adjustment voltages and currents.

Features:

- Output Voltage Tolerances of $\pm 5\%$ over the Temperature Range
- Output Current of 100mA
- Internal Thermal Overload Protection
- Output Transistor Safe Area Protection
- Internal Short Circuit Current Limit

Absolute Maximum Ratings:

Output Voltage, V_{OUT}	
NTE977	5V
NTE950	12V
NTE951	15V
Input Voltage, V_{IN}	
NTE977	30V
NTE950, NTE951	35V
Internal Power Dissipation (Note 1), P_D	Internally Limited
Operating Temperature Range, T_{opr}	0°C to +70°C
Maximum Junction Temperature, T_J	+125°C
Storage Temperature Range, T_{stg}	-55°C to +150°C
Lead Temperature (Soldering, 10 sec), T_L	+260°C

Note 1. Thermal resistance is typically +60°C/W junction to case, +232°C/W junction to ambient, and +88°C/W junction to ambient at 400ft min of air. The maximum junction temperature shall not exceed +125°C on Electrical parameters.

Electrical Characteristics: ($T_J = 0^\circ$ to $+125^\circ\text{C}$, $I_O = 40\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_O = 0.1\mu\text{F}$, Note 2 unless otherwise specified)

NTE Type Number			NTE977			NTE950			NTE951			Unit
Input Voltage (unless otherwise specified)			V _{IN} = 10V			V _{IN} = 19V			V _{IN} = 23V			
Parameter	Symbol	Test Conditions	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
Output Voltage (Note 4)	V _O	T _J = +25°C	4.8	5.0	5.2	11.5	12.0	12.5	14.4	15.0	15.6	V
		1mA ≤ I _O ≤ 70mA	4.75	–	5.25	11.4	–	12.6	14.25	–	15.75	V
		1mA ≤ I _O ≤ 70mA	4.75	–	5.25	11.4	–	12.6	14.25	–	15.75	V
		V _{MIN} ≤ V _{IN} ≤ V _{MAX}	(7 ≤ V _{IN} ≤ 20)			(14.5 ≤ V _{IN} ≤ 27)			(17.5 ≤ V _{IN} ≤ 30)			
Line Regulation	ΔV _O	T _J = +25°C	–	10	54	–	20	110	–	25	140	mV
			(8 ≤ V _{IN} ≤ 20)			(16 ≤ V _{IN} ≤ 27)			(20 ≤ V _{IN} ≤ 30)			V
			–	18	75	–	30	180	–	37	250	mV
			(7 ≤ V _{IN} ≤ 20)			(14.5 ≤ V _{IN} ≤ 27)			(17.5 ≤ V _{IN} ≤ 30)			V
Load Regulation	ΔV _O	T _J = +25°C, 1mA ≤ I _O ≤ 40mA	–	5	30	–	10	50	–	12	75	mV
		T _J = +25°C, 1mA ≤ I _O ≤ 100mA	–	20	60	–	30	100	–	35	150	mV
Long Term Stability	ΔV _O		–	12	–	–	24	–	–	30	–	$\frac{\text{mV}}{1000\text{Hrs}}$
Quiescent Current	I _Q	T _J = +25°C	–	3	5	–	3	5	–	3.1	5	mA
		T _J = +125°C	–	–	4.7	–	–	4.7	–	–	4.7	mA
Quiescent Current Change	ΔI _Q	1mA ≤ I _O ≤ 40mA	–	–	0.1	–	–	0.1	–	–	0.1	mA
		V _{MIN} ≤ V _{IN} ≤ V _{MAX}	–	–	1.0	–	–	1.0	–	–	1.0	mA
		(8 ≤ V _{IN} ≤ 20)			(16 ≤ V _{IN} ≤ 27)			(20 ≤ V _{IN} ≤ 30)			V	
Output Noise Voltage	V _n	T _J = +25°C, Note 3, f = 10Hz to 10kHz	–	40	–	–	80	–	–	90	–	μV
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	f = 120Hz	47	62	–	40	54	–	37	51	–	dB
	(8 ≤ V _{IN} ≤ 16)			(15 ≤ V _{IN} ≤ 25)			(18.5 ≤ V _{IN} ≤ 28.5)			V		
Input Voltage Required to Maintain Line Regulation		T _J = +25°C	7	–	–	14.5	–	–	17.5	–	–	V

Note 2. The maximum steady state usable output current and input voltage are very dependent on the heat sinking and/or lead length of the package. The data above represent pulse test conditions with junction temperatures as indicated at the initiation of test.

Note 3. Recommended minimum load capacitance of $0.01\mu\text{F}$ to limit high frequency noise bandwidth.

Note 4. The temperature coefficient of V_{OUT} is typically within $\pm 0.01\% V_O/^\circ\text{C}$.

