




(DESIGNATION) S M 3 A

KEY POSITION
TYPE: A, B, E, M

SERIES PREFIX



TABLE 1

TABLE 2

NOTE1. THE COPLANARITY OF CONTACT AND HOLD DOWN SHALL BE 0.1 MAXIMUM ON THE SURFACE TABLE.
NOTE2. THIS NUMBER IS PIN-OUT NUMBER DEFINED BY NGFF SPECIFICATION.
NOTE3. THIS CONNECTOR IS HALOGEN FREE CORRESPONDENCE PRODUCT.
NOTE4. THIS AREA SHALL NOT SHOW ANY BURRS AND UNEVEN SURFACE BY EJECTOR PIN MARK,
TOOL PARTING LINE, AND ANY OTHER FACTORS.

NO.	DESCRIPTION	QTY.	MATERIAL	FINISH	REMARKS			
仕様書 (SPECIFICATION)		第1版 (ORIGINAL DATE) 08/JAN/2013		尺度 (SCALE) 5:1	シリーズ (SERIES) SM3	日本航空電子工業株式会社		
一般公差 (GENERAL TOLERANCE)		製図 DR.		名称 (TITLE) SM3ZS06U7310※※ (NGFF Double-Sided modules)		 JAPAN AVIATION ELECTRONICS INDUSTRY, LTD.		
寸法 (DIMENSION)	角度 (ANGLES)	担当 CHK.	S. YAMAGUCHI				 図面番号 (DRAWING NO.)	
± 0.8	×° ±	査閲 APPD.	R. KATOU					SJ113505
× ± 0.4	××° ±	承認 APPD.	T. SHINDOU					
×× ± 0.1				質量 (MASS)		1		
××× ±	単位 (UNIT) : mm							