



NOTES:

- MATERIAL:
 - HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0.
 - CONTACT: COPPER ALLOY
 - FITTING NAIL: COPPER ALLOY
 - ACTUATOR: THERMOPLASTIC, HIGH TEMP., UL94V-0.
- FINISH:
 - UNDER PLATING: 50u" MIN. NICKEL OVERALL
 - CONTACT AREA AND SOLDER TAIL: GOLD FLASH OVERALL
 - FITTING NAIL: UNDER PLATING: 50u" MIN. NICKEL OVERALL
 - GOLD FLASH OVERALL
- REFLOW SOLDER CAPABLE TO 260°C PEAK TEMP. FOR 10 SECONDS MAX.
- SPEC. PLS. REFER TO GS-12-580.
- PACKAGE PLS. REFER TO GS-14-1332.
- PART NUMBER DESCRIPTION:

10089710-XXX 0 1 0 LF
NO. OF ONTACTS(CKT) LEAD FREE
PACKING 0: TAPE & REEL
COLOR X: HOUSING ACTUATOR
O: NATURAL BLACK
PLATING 1: GOLD FLASH OVERALL

CKT	DIM.A	DIM.B	DIM.C	DIM. D
012	5.5	10.80	12.5	6.65
020	9.5	14.80	16.5	10.65
030	14.5	19.80	21.5	15.65

mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY	FCI		
ltr	ecn no	dr	date	linear	.X ± 0.25				
A	T08-1182	WL	11/06/08	linear	.XX ± 0.15	projection	title		
B	T08-1196	WL	12/10/08		.XXX ± 0.10				
C	T09-1005	WL	01/20/09	angles	0° ± 2°	MM	product family FPC		
D	T10-0113	WL	07/17/10	dr	LEIF SHEN 08-06-18				
				engr	DENNIS GOH 08-08-08	scale	size dwg no		code SNG
				chr	DENNIS GOH 08-08-08				
				appd	JOEY NG 08-08-08		A4		sheet 1 of 1
sheet index	revision sheet	D	1						