RF-13 (Rev 04FEB14)

samtec

ISRATE® Isolated Edge Rate Contact

(4,00 mm) .1575"

IJ5C SERIES

50Ω HIGH ISOLATION RF CABLE ASSEMBLY

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?IJ5C

Insulator Material: Black LCP
Contact Material: Copper Alloy
Pin Material: Copper Alloy
Dielectric Material: Black LCP
Plating: Au over 50µ" (1,27 µm) Ni
Operating Temp Range: -40°C to +90°C
RoHS Compliant: Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality

FILE NO. E111594

Cable (-1):

Conductor Size: 26 AWG, (0,48 mm) .019" dia.
Conductor Material: Silver Plated Copper
Insulator Diameter: (1,27 mm) .050"
Insulator Material: Foamed FEP
Shield Material: Silver Plated Copper
Jacket Material: FEP
Jacket Diameter: (1,80 mm) .071"
Impedance: 50Ω
Current Rating: 2.5A
RoHS Compliant: Yes

Cable (-2):

Conductor Size: 26 AWG, (0,51 mm) .020" dia.
Conductor Material: Silver and Copper Plated Steel Wire
Insulator Diameter: (1,52 mm) .060"
Insulator Material: PTFE
Shield Material: Silver Plated Copper Wire
Jacket Material: FEP
Jacket Diameter: (2,54 mm) .100"
Impedance: 50Ω
Current Rating: 5A DC
RoHS Compliant: Yes

Note: This Series is non-standard, non-returnable.

Mates with: IP5

EDGE RATE™ CONTACT

RUGGEDIZED by SAMTEC

- Edge Rate™ Contacts
- Positive Latching



1 Meter Cable Assembly	Frequency
Insertion Loss = 3 dB	9.5 GHz / 19.0 Gbps
Return Loss = 15 dB	2.2 GHz / 4.4 Gbps
VSWR = 1.4	2.1 GHz / 4.2 Gbps
Isolation = 60 dB	3.1 GHz / 6.2 Gbps
Performance and complete test data available at www.samtec.com?IJ5C or contact sig@samtec.com	

IJ5C – NO. OF POSITIONS – ASSEMBLED LENGTH – PLATING OPTION – END OPTION – END 2 OPTION – CABLE TYPE

–01, –02, –04, –06, –08

NO. OF POSITIONS	A
–01	(20,87) .822
–02	(24,87) .979
–04	(32,87) 1.294
–06	(40,87) 1.609
–08	(48,87) 1.924

–"XXXX" = Assembled Length in millimeters –0100 to –1000 (100 mm) 3.94" minimum

–S = 30µ" (0,76 µm) Gold on contact

–S = Single Ended
–D = Double Ended

–NUS = Notch up, straight P1 to P1
–NDS = Notch down, straight P1 to PN

–1 = CTB-2650F-01 cable
–2 = RG 316 cable



Due to technical progress, all designs, specifications and components are subject to change without notice.