


[Home](#) > [Search Tools](#) > [Part Number](#)

Part Number Search

You Searched For:

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS.
 ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

[Sales Support](#)
[Product Overview](#)
[Stock Check](#)

Our Catalog Part Number: ZEDBL25PBA

Our Global Manufacturing Part Number: 111979-0212

☐	YES	RoHS compliant =	material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2002/95/EC
	YES	RoHS compatible =	Compatible with lead free soldering process

Export Compliance		
☐	Country of Compliance	United States
	Export Compliance Notes	Commercial Shipments "C"
		Controlled by the US Department of Commerce.

Product Datasheet	
Thumbnail Image	
Where Sold	Americas, Asia Pacific, Europe
Product Group	D-Subminiature
Product Sub-Family	D-Sub Standard
Component Type	Connector
Application Type	Commercial
Cable or PC Board	PC Board
Gender	Plug
Number of Signal Pins	25
Number of Size 8 contacts	0
Straight or Right Angle	Right Angle
Contact Plating	Gold over Nickel
Shell Plating	Tin (with Grounding Dimples)
Hardware	Plastic Brackets, Ground Straps, 4-40 Threads, Boardlocks
Other Features	Stamped Contacts
Contact Termination	US Footprint 8,08 (.318)
Shell Size	DB
Temperature Rating	-55°C to +105°C
Current Capacity	5 A
Contact Resistance	15 milli ohms max.
Dielectric Withstanding Voltage	1000 V AC at Sea Level
Insulator Material	Thermoplastic, UL 94V-0
Contact Material	Copper Alloy
Shell Material	Steel
Hardware Material and Plating	Thermoplastc, Steel Copper Alloy with Tin or Nickel Plating