




REV.	DATE	ECR NO.	DESCRIPTION
A	10/15/04	XXXXXX	MODFY HOUSING FINISH TO NEXCOTE
B	06/09/09	XXXXXX	CABLE STRIPPING DIM'S WAS CHANGED



RECOMMENDED
CABLE STRIPPING DIM'S



8	NUT	BRASS	NEXCOTE	1
8	BARREL	BRASS	GOLD	1
8	HOUSING	BRASS	NEXCOTE	1
7	CONTACT PIN	BRASS	GOLD	1
6	RETAINER RING	SUS 304	NATURAL	1
5	GASKET	SILICONE	RED	1
4	CONTACT BODY	BRASS	NEXCOTE	1
3	INSULATOR	PTFE	NATURAL	1
2	BODY	BRASS	NEXCOTE	1
1	SHELL	BRASS	NEXCOTE	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 - 8mm $\pm$ 0.20mm
8 - 30mm $\pm$ 0.40mm
30 - 120mm $\pm$ 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 - .315 $\pm$ 0.007"
.315 - 1.180 $\pm$ 0.015"
1.180 - 4.724 $\pm$ 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN M.ZHANG	06/09/09
CHECKED	
ISSUED	
SHEET 1 OF 1	
CAD FILE	C:/CONNEX/172236.DWG

Amphenol Connex			
PART DESCRIPTION N R/A DIRECT SOLDER PLUG (FOR .141 SEMI RIGID CABLE)			
PART NO. 172236			
DWG. NO.	172236.DWG	REV. B	SIZE A
		SCALE	NA