



A complete variety of UL Recognized modular plugs are available. All plugs have 15 micro inches* of gold plating on the contacts for standard applications for voice and data. Flat satin stranded, round stranded, and round solid cables are accommodated. Keyed, shielded and category 5 versions are available. Flat modular cable types accept 28 AWG, 24 stranded. Round cable types accept 24 AWG, stranded or solid.

Four RJ45 network ports are shown in a row, each with a different colored plastic housing: blue, green, yellow, and red. They are set against a dark background.

The new patent **EZRJ45™** connector simplifies installation by allowing the pairs to be inserted through the connector. There is no handle liner or wire bar to deal with. Inspection of the correct conductor order is done before crimping so no connector is wasted wiring. The conductors are able to be pulled forward so the pairs are very close to the contacts. This method allows the integrity maintain Category Five, and even enhanced Category 5 and Category 6 capabilities. (50 u in. gold)

The **EZRJ12™** and both **EZRJ45™** can be crimped with most any standard tool, then trimmed with a cutter or small utility knife. The new BD45000 crimp tool crimps and trims the exposed conductors in one operation. The vertical action of the tool makes a uniform crimp.

Video Demo



BD45000 Crimp & Trim Tool

EZ-RJ45 Cat 6
Shielded with
SNAGLESS Boot

CXB500/600 Snagless Boot

[Back to Index](#)

FOR TECHNICAL SUPPORT: PHONE 973-47-4040 / FAX 973-47-2111



Category 5 Liner Plugs are supplied with an insertable liner for the conductors. This is also known as a "Wired Bar" style. The separated conductors inserted into the liner, cut off squarely at bottom, inserted into the RJ45 plug, then perfectly crimped. (Use CBX300 series boots for Category 5 assembly.)



Wall Jacks

Plastic wall jacks are furnished with mounting hardware for easy installation. Type N are very economical and are to be used where not required. 15 micro inches of gold plate on the contacts is standard on all jacks. Rounded configuration, rear wiring terminals all to fit all standard receptacle boxes.



FOR TECHNICAL SUPPORT: PHONE 973-47-4040 / FAX 973-47-2111

[Back to Index](#)