

LOADED CONNECTOR ASSEMBLY
(FOR EXAMPLE)

EXAMPLE)

note 5

2.00±0.05 (21X)

42.00

12.0

2.00±0.05 (6X)

44.0 MAX.

15 40±0.50

11.70±0.10

note 3

note 6


13.45±0.15

40.10

3.00±0.1

SHEET NR. : 906

LAY-OUT P.C.B.-HOLE



HM2P70PME 129  LEAD FREE INDICATOR : LF = LEAD FREE
(DIGIT 15 & 16)

PLATING CODE (DIGIT 13 AND 14)
(REF DWG No. BS.C .201844.003)

NOTES:

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASSFILLED
POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN
MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER
DEPENDING ON PRODUCTION LOCATION.
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS.A .201572.001

1DEC ±0,2 2DEC ±0,1 ANGLES ±1°	APPR.	DATE	SIGN.	LOADING PATTERN OVERVIEW	
	DRAFT	1999-09-28	G. Nys	CAT. No.	HM2P70PME129----
	CHECKED				www.fciconnect.com
PROD. MGR.					
PR. ENG. MGR.					
WE RESERVE THE RIGHT TO CHANGE DIMENSIONS OR REQUIREMENTS WITHOUT PRIOR NOTICE	PR. MGT. MGR.			SCALE	
ALL DIMENSIONS IN MM	REFERENCES			BS, C , 201843, 818	
				DRAWING No. CUSTOMER DRAWING D	
				REVISION	