




NOTES:

1. SEE SHEET 2 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS.
2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITIES.
3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON.
4. TESTED TO EIA/TIA 568-B.3.
5. PATCH CORD ROUTING CONFIGURATION A TO B.
6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

												FIBER OPTIC PATCH CORD DUPLEX SC TO SC CONFIGURATION CUSTOMER DRAWING		
													 <b>PANDUIT</b> <sup>TM</sup> CORP. TINLEY PARK, ILL 60477	
												 THIRD ANGLE PROJECTION	ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED.  DIMENSIONAL TOLERANCES ARE: (.X) (.XXX) ± .010 (.0.3) (.XX) ± .03 (.0.8) ANGLES	DRAWING FILENAME M02779BA_DC_00A.prt
											SCALE NONE			
											DRAWN BY MC		REVIEW DRAWING NUMBERS	PART NO. SEE TABLE, SHT. 2
											DATE 04-27-07			DRAWING NO. 02779-09 (SHT. 1 of 2)
REV	DATE	BY	CHK	DESCRIPTION		ECN	-	R	CUST	SUP	OTH	CHK'D		
R	06-05-07	MC		RELEASED TO PRODUCTION		02779-09								

