




RTD ELEMENT RESISTANCE @ 0°C = $100\ \Omega \pm 0.12\%$
 RTD ELEMENT ACCURACY @ 0°C = $\pm 0.30^{\circ}\text{C}$
 RTD ELEMENT DIN 43760 ACCURACY CLASS = "B"
 TCR = $3,850\ \text{ppm}/^{\circ}\text{C}$
 TEMPERATURE RATING = $-50\ \text{TO } +500^{\circ}\text{C}$
 THERMAL TIME CONSTANT = 10 SECONDS MAXIMUM (1m/SEC MOVING AIR)
 DISSIPATION CONSTANT = $2.5\ \text{mW}/^{\circ}\text{C}$ NOMINAL (1m/SEC MOVING AIR)
 MAXIMUM APPLIED CURRENT = 1 mA

SEE MANUFACTURING SPECIFICATION (LAYER 1)

"D"	DIMENSION "L" FOR $100\ \Omega$ RTDS WAS $0.095'' \pm 0.008''$	10/11/08	DD
"C"	LEAD WIRE WAS 32 AWG PLATINUM PLATED NICKEL	08/25/05	DD
---	ISO RELEASE	04/11/03	DD
"B"	UPDATED LEAD WIRE AWG & LENGTH, ADDED NOTE	08/14/02	RD
"A"	UPDATED LEAD WIRE AWG & TYPE	07/15/02	RD
REV	REVISION RECORD	DATE	APP

SCALE	NONE	U.S. SENSOR CORP. © COPYRIGHT 714-639-1000 www.ussensor.com PLATINUM RTD SENSOR P/N PPG101B1
DRAWN BY	DAN DANKERT	
DATE	07/15/02	
REV.	"D"	
LAYER	0 OF 2	