

Optical Components

Rev. 3 [10. 2008]

OF3507B

156Mbps APD-preamplifier coaxial module with a single mode fiber

1. DESCRIPTION

OF3507B is an optical receiver module for digital transmission systems up to 156Mbps. It uses an InGaAs avalanche photodiode with a low noise preamplifier. Package style is a hermetically sealed coaxial package with a single mode fiber pigtail.

2. FEATURES

Data rate up to 156Mbps
High responsivity InGaAs-APD : 8.5A/W
Wide dynamic range
Typical sensitivity : -47.5dBm
Low noise
Small coaxial package

3. APPLICATION

SONET OC-3/SDH STM-1 applications
Long-haul transmission systems up to 156Mbps



4. OPTICAL AND ELECTRICAL CHARACTERISTICS

(Wavelength=1550nm , Tc =25°C , Vcc=3.3V, unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Wavelength	λ	--	1250	--	1620	nm
APD Breakdown Voltage	VBR	ID=10 μ A	40	50	70	V
Temperature Coefficient of VBR	γ	--	0.05	0.09	0.12	V/°C
APD Responsivity	RAPD	λ =1.55 μ m, M=1	0.80	0.85	--	A/W
		λ =1.31 μ m, M=1	0.75	0.85	--	
Responsivity	R	RL>500 Ω , M=10, Pin=-43dBm, Differential	160	--	--	kV/W
Bandwidth	BW	f3dB, RL>500 Ω , M=10	120	--	--	MHz
Sensitivity	Prmin	155Mbps, NRZ, BER=10 ⁻¹⁰ , PRBS2 ²³ -1, Rext=12.0dB*, M=Mopt.	--	-47.5	-46.5	dBm
Overload	Prmax	155Mbps, NRZ, BER=10 ⁻¹⁰ , PRBS2 ²³ -1, M=3	-7	-5	--	dBm
Supply Current	ICC	Pin = 0mW	--	21	26	mA
Recommended TIA Supply Voltage	VCC	--	3.1	3.3	3.5	V
Optical Return Loss	ORL	--	--	--	-27	dB

*) Extinction ratio of LD source.

OF3507B

5. ABSOLUTE MAXIMUM RATING

(Tc = 25 °C, unless otherwise specified)

Parameter	Symbol	Rating	Unit
APD Bias Voltage	VB	0 to VBR	V
TIA Supply Voltage	Vcc	4.5	V
APD Forward Current	IF	2	mA
APD Reverse Current	IR	2(cw)	mA
Operating Temperature	Tc	-40 to +85	°C
Storage Temperature	Tstg	-40 to +85	°C

6. CONNECTOR AND FIBER SPECIFICATIONS

Parameter	Specifications	Unit
Type	SM	--
Flame Rating	UL94 V-0	--
	UL1581 VW-1	--
Mode Field Diameter	10	μm
Cladding Diameter	125	μm
Jacket Diameter	900	μm
Length	1 (Min.)	m
Standard Connector	FC/PC or SC/PC	--

7. ORDERING INFORMATION

OF3507B - _ _ _ _

ex.) OF3507B-WFFC

OF3507B with a flange and FC connector.


<u>Flange</u>	<u>Connector</u>
WF	FC
NF	SC
	LC
	MU

OF3507B


8. OUTLINE DRAWING

All dimensions in millimeters


Package No. OF3507B-WF__



Package No. OF3507B-NF__



Pin Connection	
1	VAPD
2	VCC
3	VOUT-
4	VOUT+
5	GND(case)



NOTE

Under the condition “ V_{APD} set, but with V_{cc} absent”, optical inputs may result in damage to the TIA. It is necessary to set V_{cc} before optical inputs to prevent such trouble.

SAFETY INFORMATION ON THIS PRODUCT

Caution GaAs Product	The product contains gallium arsenide, GaAs. GaAs vapor and powder are hazardous to human health if inhaled, ingested or swallowed. Do not destroy or burn the product. Do not crush or chemically dissolve the product. Do not put the product in the mouth. Observe related laws and company regulations when discarding this product. The product should be excluded from general industrial waste or household garbage.
Caution Optical Fiber	A glass-fiber is attached on the product. Handle with care. When the fiber is broken or damaged, handle carefully to avoid injury from the damaged part or fragments.

Notice

No copying or reproduction of this document, in part or in whole, is permitted without the consent of LAPIS Semiconductor Co., Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing LAPIS Semiconductor's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from LAPIS Semiconductor upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, LAPIS Semiconductor shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. LAPIS Semiconductor does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by LAPIS Semiconductor and other parties. LAPIS Semiconductor shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While LAPIS Semiconductor always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. LAPIS Semiconductor shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). LAPIS Semiconductor shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.

Copyright 2008 - 2011 LAPIS Semiconductor Co., Ltd.