

► UNIVERSAL POUCH

- 2 hooks for loose connectors
- Maximum tool weight 3 kg per hook
- 2 rings for lanyards, capacity 100 daN per ring



4750-UP-2 7314150187768

► HAMMER HOLDER

- 1 ring for lanyards, capacity 100 daN



4750-HHO-3 7314150187751

► POWER DRILL HOLDER

- 1 ring for lanyards, capacity 100 daN



4750-DHO-2 7314150187775

► 3 POCKET BELT

- 4 hooks for loose connectors
- Maximum tool weight 3 kg per hook
- 3 rings for lanyards, capacity 100 daN per ring



4750-3PB-2 7314150187782



Quality tests

The elastic and retractable lanyards are certified against Bahco standards and developed against the highest quality principles in the industry. The lanyards are quality tested in both static and dynamic tests. In order to make sure the quality is up to Bahco's high placed demands, the lanyards are tested under far more stringent and demanding circumstances than they are intended to be used in. For our dynamic test it technically means that a security coefficient 2, factor 2 test is performed.



During the test, the lanyard is elevated from a solid central point, extended to maximum outstretched length and dropped for a distance of twice the outstretched length of the lanyard with twice the maximum weight attached. The product quality is approved as the lanyard is unaffected by the treatment.

