

## TENTATIVE RESTRICTIVE DATA

## TOSHIBA AC SWITCH



OPTICALLY ISOLATED AC SWITCH WITH ZERO VOLTAGE TURN-ON FUNCTION

## TSA2000G, TSA2000J


- R.M.S. On-State Current :  $I_T$  (RMS) = 0.1~2A
- Repetitive Peak Off-State Voltage :  $V_{DRM}$  = 400, 600V
- Isolation Voltage between Input to Output : 3000VAC (t=1min.)
- Thickness of Inner Insulation Material : 0.8mm (Min.)
- Creepage Distances, Clearances for Insulation between Input and Output Side : 6mm (Min.)
- TTL drive is Available

MAXIMUM RATINGS ( $T_a = 25^\circ\text{C}$ )

CHARACTERISTIC		SYMBOL	RATING	UNIT
INPUT	Control Input Current	$I_F$ (IN)	50	mA
	Forward Current Derating ( $T_a \geq 53^\circ\text{C}$ )	$\Delta I_F$ / $^\circ\text{C}$	-0.7	mA / $^\circ\text{C}$
	Peak Forward Current (100 $\mu\text{s}$ pulse, 100pps)	$I_{FP}$	1	A
	Reverse Voltage	$V_R$	5	V
OUTPUT	Repetitive Peak Off-State Voltage	$V_{DRM}$	400	V
	TSA2000G		600	
	Nominal AC Line Voltage (Note 1)	VAC	80~125	V
	TSA2000J		80~250	
	R.M.S On-State Current (Sine Waveform, R.M.S.)	$I_T$ (RMS)	0.1~2	A
	Peak One Cycle Surge On-State Current (Non-Repetitive)	$I_{TSM}$	20 (50Hz) 22 (60Hz)	A
I <sup>2</sup> t Limit Value		$I^2t$	2	$\text{A}^2\text{s}$
Operating Frequency Range		f	45~65	Hz
Operating Temperature Range		$T_{opr}$	-40~100	$^\circ\text{C}$
Storage Temperature Range		$T_{stg}$	-40~100	$^\circ\text{C}$
Isolation Voltage (Input to Output) Note 2		$BV_s$	3000	V

Weight : 2g  
Marking

## EQUIVALENT CIRCUIT



1 : AC OUTPUT (MT2) 4 : DC INPUT (+)  
2 : AC OUTPUT (MT1) 5 : DC INPUT (-)  
3 : GATE ZC : ZEROCROSS CIRCUIT

NUMBER	SYMBOL	MARK	
※1	TYPE	TSA2000G	TYPE
		TSA2000J	TSA2000J
※2	Lot Number Month Year	(Staring from Alphabet A)	Example 3A : January 1993 3B : February 1993 3L : December 1993
		Year (Last Number of the Christian era)	

(The cutted pins near by Pin No.1 &amp; No.3 is connecting in electrically with output terminal)

Note 1 : When the voltage larger than applied AC voltage is applied to the device such as 2 phase motor and others, please derating for this maximum rating value.

Note 2 : TEST CONDITION : AC, t=60s, RH  $\leq 60\%$ 

Note 3 : Soldering of printed wiring board should be used under 260°C and 10 seconds.

ELECTRICAL CHARACTERISTICS ( $T_a = 25^\circ\text{C}$ )

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
INPUT	Forward Voltage	$V_F$	$I_F = 10\text{mA}$	1.0	1.15	1.3	V
	Reverse Current	$I_R$	$V_R = 5\text{V}$	—	—	10	$\mu\text{A}$
	Capacitance	$C_T$	$V_T = 0\text{V}, f = 1\text{MHz}$	—	20	—	pF
OUTPUT	Peak Off-State Current	$I_{DRM}$	$V_{DRM} = \text{Rated}$	—	—	10	$\mu\text{A}$
	Peak On-State Voltage	$V_{TM}$	$I_{TM} = 3\text{A}$	—	—	1.5	V
	Holding Current	$I_H$	$V_D = 6\text{V}, \text{Beginning Current} = 1\text{A}$	—	—	25	mA
	Critical Rate of Rise of Off-State Voltage	$dv/dt$	$V_{DRM} = \text{Rated}$	—	2000	—	$\text{V}/\mu\text{s}$
	Critical Rate of Rise of Commutating Voltage	$(dv/dt)_c$	$V_D = 400\text{V}, -di/dt = 20\text{A}/\text{ms}$	—	20	—	$\text{V}/\mu\text{s}$
	Thermal Resistance	$R_{th(j-\ell)}$	AC	—	—	22	$^\circ\text{C}/\text{W}$
	Junction to Lead	$R_{th(j-a)}$	AC	—	—	90	$^\circ\text{C}/\text{W}$

COUPLED ELECTRICAL CHARACTERISTICS ( $T_a = 25^\circ\text{C}$ )

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	$I_{FT}$	$V_D = 6\text{V}, R_L = 20\Omega$	—	—	10	mA
Inhibit Voltage	$V_{IH}$	$I_F = 10\text{mA}, R_L = 20\Omega$	—	38	50	V
Capacitance (Input to output)	$C_S$	$V_S = 0\text{V}, f = 1\text{MHz}$	—	0.5	—	pF
Isolation Resistance	$R_S$	$V = 500\text{V}, RH \leq 60\%$	$10^9$	—	—	$\Omega$
Turn-off Time	$t_{off}$	OUTPUT : Sine Waveform	—	—	3/4	cycle















Fig.1 ZERO VOLTAGE SWITCHING WAVEFORM





**RESTRICTIONS ON PRODUCT USE**

000707EBA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.