

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
30 mm - Embeddable, eurofast[®] Connection 	Bi10-M30-AD4X-H1141	T4417500		10	2-Wire DC
	Bi12-M30-AD4X-H1141	T4417041	Extended Range	12	
	Bi10U-M30-AD4X-H1144	M4405072	Uprox+	10	
	Bi10-M30-AN6X-H1141	T4617600		10	3-Wire DC NPN
	Bi10U-EM30-AN6X-H1141	M1636350	Uprox	10	
	Bi10U-EM30H-AN6X2-H1141	M1636407	Uprox, Stoneface	10	
	Bi10U-EM30H-AN6X2-H1141/S1589	M1636490	weldguard[®], Uprox	10	
	Bi10U-M30-AN6X-H1141	M1636150	Uprox	10	
	Bi15-M30-AN6X-H1141	T4618600	Extended Range	15	
	Bi15-EM30H-AN6X-H1141	T4618692	Stoneface, Ext. Range	15	
	Bi15U-M30-AN6X-H1141	M1636736	Uprox+	15	
	Bi10-M30-AP6X-H1141	T4617500		10	3-Wire DC PNP
	Bi10U-EM30-AP6X-H1141	M1636340	Uprox	10	
	Bi10U-EM30H-AP6X2-H1141/S1589	M1636491	weldguard[®], Uprox	10	
	Bi10U-M30-AP6X-H1141	M1636140	Uprox	10	
	Bi10U-M30-AP6X2-H1141	M1636145	Uprox	10	
	Bi15-M30-AP6X-H1141	T4618500	Extended Range	15	
	Bi15-EM30H-AP6X-H1141	T4618592	Stoneface, Ext. Range	15	
	Bi15-EM30H-AP6X-H1141/S1589	T4618593	weldguard[®]	15	
	Bi15U-EM30-AP6X-H1141	M1636733	Uprox+	15	
	Bi15U-M30-AP6X-H1141	M1636732	Stainless steel Uprox+	15	
30 mm - Embeddable, eurofast[®] Connection 	Bi15-EM30H-AP6X-H1141/S1610	T4618589	Weld/armorguard	15	3-Wire DC PNP
30 mm - Embeddable, eurofast[®] Connection 	Bi10-M30-VN4X-H1141	T1571600	Comp. Outputs	10	4-Wire DC NPN
	Bi10U-M30-VN4X-H1141	M1582352	Uprox, Comp. Outputs	10	
	Bi15-M30-VN4X-H1141	T4570711	Comp. Outputs	15	
	Bi10-M30-VP4X-H1141	T1561600	Comp. Outputs	10	4-Wire DC PNP
	Bi10U-M30-VP4X-H1141	M1582253	Uprox, Comp. Outputs	10	
	Bi15-M30-VP4X-H1141	T4570710	Comp. Outputs	15	
	Bi10-M30-Y1X-H1141	M4020200		10	2-Wire DC

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #	Wiring Diagrams
10-65 VDC	500	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1	Diagram 1
	500	≤100	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.2T-*	1	
	1000	≤100	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	2	
10-30 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	Diagram 2
	2000	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	3	
	2000	≤200	-30 to +85	IP 68	SS	SF	GN	YE	RKV 4T-*	3	
	2000	≤200	-30 to +85	IP 68	SS	WG	GN	YE	RKC 4T-*/S1587	3	
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
	300	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
	300	≤200	-25 to +70	IP 67	SS	SF	N/A	YE	RKC 4T-*/S1587	3	
10-30 VDC	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	3	Diagram 3
	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	
	2000	≤200	-30 to +85	IP 68	SS	PA 12	N/A	YE	RKV 4T-*	4	
	2000	≤200	-30 to +85	IP 68	SS	WG	GN	YE	RKC 4T-*/S1587	4	
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	GN	YE	RK 4T-*	4	
	300	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	
	300	≤200	-25 to +70	IP 67	SS	SF	N/A	YE	RKV 4T-*	4	
	300	≤200	-25 to +70	IP 67	SS	WG	N/A	YE	RKC 4T-*/S1587	4	
10-30 VDC	750	≤200	-30 to +85	IP 68	SS	LCP	N/A	YE	RK 4T-*	4	Diagram 4
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
	750	≤200	-30 to +85	IP 68	CPB	LCP	N/A	YE	RK 4T-*	4	
10-30 VDC	300	≤200	-25 to +70	IP 67	AG	WG	N/A	YE	RKC 4T-*/S1587	4	Diagram 5
	300	≤200	-25 to +70	IP 67	AG	WG	N/A	YE	RKC 4T-*/S1587	4	
10-65 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5	Diagram 6
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5	
	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	5	
10-65 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	6	Diagram 7
	2000	≤200	-30 to +85	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	6	
	300	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.4T-*	6	
5-30 VDC	2000	Remote	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4.21T-*	7	

* Length in meters.

For material descriptions see page M36.