SPC-F005.DWG ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. <u>ი</u> ĊΊ 4. φ 3. Rustproof and scratch resistant 2. Non-conductive **SPECIFICATIONS:** Positive action latches Brass hinge and latch pins Resistant to oil and most common chemicals Material: lightweight co-polymer polypropylene resin, Gray Tongue and groove construction Tough recessed handle 4 S % 3 DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED, INSCLAIMER
ALL STATELENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED LIPON INFORMATION
AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIBELE. SINCE CONDITIONS OF USE ARE
BEYOND OHR CONTROL, THE USER SHALL DETERMINE THE SINCE CONTROL. THE PRODUCT FOR THE
INTENED USE AND ASSUME ALL RESK AND LUBILITY WHATSOEPER IN CONNECTION THEREWITH. ====== J.C. DRAWN BY: CHECKED BY: APPROVED ВY: DCP # 1090 REV 2/6/92 œ ⋗ DATE: DATE: DATE: Try Size: 12 ½ X 4 ¾ X 1 ½ SIZE SCALE: DRAWING TITLE: \triangleright REVISIONS REDRAWN & UPDATED DWG. NO. DESCRIPTION RELEASED SIN UTILITY BOX WITH LIFT-OUT TRAY SPC TECHNOLOGY C - 304 - 2U.O.M.: INCHES J.C. DRAWN OYH DOC. NO. SPC-F005 * Effective: 12/21/98 * ۹ 10/11/01 2/6/92 DATE CHECKD ELECTRONIC FILE J.C. 84N1449.DWG 10/16/01 SHEET: DATE J.C. **APPRVD** DCP No: 680 유 1 10/16/0 DATE

യ 🤻