

## SlimFix

### SF 3/21 MC SDR V2

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergsstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



Similar to illustration

SlimFix are conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. They consist of halogen-free material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm<sup>2</sup>
- Markers in proven MultiCard format

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.



#### General ordering data

Type	SF 3/21 MC SDR V2
Order No.	<a href="#">1918880000</a>
Version	SlimFix, Conductor and cable markers, 3 - 3.7 mm, 21 x 4.6 mm, To customer specification
GTIN (EAN)	4032248554263
Qty.	64 pc(s).
compatible printer	<a href="#">1324380000 2438520000 2438510000</a>

**SlimFix**  
**SF 3/21 MC SDR V2**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergsstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**
**Dimensions and weights**

Width	4.6 mm	Width (inches)	0.181 inch
Height	21 mm	Height (inches)	0.827 inch
Depth	4.8 mm	Depth (inches)	0.189 inch
Net weight	0.31 g		

**General data**

Advice label	Colour based on customer requirements (Please send M-Print PRO file)	Colour	
Colour of printing	black		To customer specification
Material	Polyamide 66		
Orientation of print			
	horizontal		
Printing method	MC Laser		
Type of printing	To customer specification		
Width	4.6 mm		

**Conductor and cable markers**

Conductor O.D.	3 - 3.7 mm	Conductor O.D., max.	3.7 mm
Conductor O.D., min.	3 mm	Conductor cross-section, max.	2.5 mm <sup>2</sup>
Conductor cross-section, min.	1.5 mm <sup>2</sup>	Halogen	No

**Classifications**

ETIM 6.0	EC001530	ETIM 7.0	EC001530
eClass 9.0	27-40-04-01	eClass 9.1	27-40-04-01
eClass 10.0	27-40-04-01	UNSPSC	44-12-17-08

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">EPLAN</a> , <a href="#">WSCAD</a>
------------------	---