

f	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6		
e	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
d	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
c	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6		
b	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
a	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
z	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6		
P	0					0					1					1					2					2
S	1					5					0					5					0					5

The drawing consists of two parts: a cross-section (left) and a plan view (right).

Cross-section (Left): Shows a bridge deck with a total width of 15.40 ± 0.50 m. The deck is supported by a central pier with a width of 11.70 ± 0.10 m. The deck thickness is $3.00 - 0.10$ m. The total height of the structure is $13.45 + 0.15 - 0.10$ m. The drawing includes a callout for "NOTE 3" pointing to the deck surface and "NOTE 6" pointing to the pier structure.

Plan View (Right): Shows the bridge deck layout. The total length is 50.0 m. The deck is divided into sections with a width of $2.00 \pm 0.05 (6x)$ m. The drawing includes a callout for "NOTE 5" pointing to a dashed rectangular area. The total width of the bridge is 48.00 m. The drawing also includes a callout for "NOTE 6" pointing to the pier structure.

Technical drawing showing two connector types, labeled 5 and 6, with dimensions relative to a seating plane.

Connector 5 dimensions:

- Distance from the left end to the seating plane: 9.70
- Distance from the seating plane to the right end: 3.70

Connector 6 dimensions:

- Distance from the left end to the seating plane: 11.20
- Distance from the seating plane to the right end: 3.70

The seating plane is indicated by a vertical line and labeled "SEATING PLANE FOR CONNECTOR".

A diagram of a rectangular field with a width of 48.00 and a height of 12.00. The field is filled with a grid of small circles, representing points. The grid consists of 12 rows and 40 columns of points, totaling 480 points. The points are arranged in a regular pattern, with the first row of points starting at a height of 1.00 from the bottom edge and the last row ending at a height of 11.00. The horizontal spacing between points is 1.20, and the vertical spacing between rows is 1.00.

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

[illegible]