




Wiha. Premium Tools  
for Professionals.

## Wiha ESD Safe Conductive Screwdrivers. For Anti-Static Applications.





Wiha ESD precision screwdrivers with the successful handle geometry. Due to the surface resistance of  $10^6 - 10^9$  ohms, defined electrostatic discharge is guaranteed.

Electrostatic discharges are a major problem, since even low voltages can damage sensitive components.

Various factors have to be considered in order to understand the problem. In ESD protection areas, the electrostatic charge is safely conducted to earth. Users have to wear the appropriate ESD footwear or grounded wrist strap. The tools used also have to be electrostatically protected.

The ESD screwdrivers from Wiha conform to the international ESD Standards DIN EN 61340-5-1/ 61340-5-2. Due to the electrical surface resistance,  $10^6 - 10^9$  ohms, defined electrostatic discharge is guaranteed. Thanks to the rotating cap, incremental adjusting is easy. The large handle enables powerful tightening and loosening of screws.



### The Product Advantages:

- Safety as a result of electrostatic discharge
- Conforms to new ESD Standards DIN EN 61340-5-1/ 61340-5-2
- Rotating cap with large surface for extra fast working
- Large handle end for powerful tightening and loosening screws
- Wiha ChromTop-finish on tip for a perfect fit every time.

### Please note:

These tools are not suited for working on live electrical components.





Wiha. Premium Tools  
for Professionals.

## Wiha ESD Safe Conductive Screwdrivers. For Anti-Static Applications.

### For Slotted, Phillips & Pozidriv Screws.



#### 272 ESD Slotted Screwdriver.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Handle: Wiha Precision Handle.

Standards: DIN EN 61340-5-1/ 61340-5-2.

Application: For maximum protection in sensitive electronic applications.

Order-No.	Ø	Length	Tip Length	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia
07634 4	1.5	40	0.25	120	2.0	12.5	10	443-1157	
07635 1	2.0	40	0.40	120	2.0	12.5	10	443-1169	
07636 8	2.5	50	0.40	145	2.5	13.0	10	443-1170	
07637 5	3.0	50	0.50	145	3.0	13.0	10	443-1182	
07638 2	3.5	60	0.60	170	3.5	14.0	10	443-1194	
07639 9	4.0	60	0.80	170	4.0	14.0	10	443-1200	



#### 273 ESD Phillips Screwdriver.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Handle: Wiha Precision Handle.

Standards: DIN EN 61340-5-1/ 61340-5-2.

Application: For maximum protection in sensitive electronic applications.

Order-No.	Ø	Length	Tip Length	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia
07640 5	00	40	120	2.0	12.5	10	443-1212		
07641 2	0	50	145	3.0	13.0	10	443-1224		
07642 9	1	60	170	4.0	14.0	10	443-1236		



#### 274 ESD Pozidriv Screwdriver.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Handle: Wiha Precision Handle.

Standards: DIN EN 61340-5-1/ 61340-5-2.

Application: For maximum protection in sensitive electronic applications.

Order-No.	Ø	Length	Tip Length	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia
07643 6	1	60	170	4.0	14	10	443-1248		

### For Hexagon Socket Screws and Hex Nuts.



#### 275 ESD Hex Screwdriver.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Handle: Wiha Precision Handle.

Standards: DIN EN 61340-5-1/ 61340-5-2.

Application: For maximum protection in sensitive electronic applications.

Order-No.	Ø	Length	Tip Length	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia
07644 3	1.3	40	120	12.5	10				
07645 0	1.5	50	145	13.0	10				
07646 7	2	50	145	13.0	10				
07647 4	2.5	60	170	14.0	10				
07648 1	3	60	170	14.0	10				



#### 276 ESD Ballpoint Hex Screwdriver.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Handle: Wiha Precision Handle.

Standards: DIN EN 61340-5-1/ 61340-5-2.

Application: For maximum protection in sensitive electronic applications.

Extra: Ballpoint allows up to 25 degree entry angle to fastener.

Order-No.	Ø	Length	Tip Length	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia
07649 8	1.5	50	145	13.0	10	443-1250			
07650 4	2	50	145	13.0	10	443-1261			
07651 1	2.5	60	170	14.0	10	443-1273			
07652 8	3	60	170	14.0	10	443-1285			



#### 277 ESD Nut Driver.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.

Handle: Wiha Precision Handle.

Standards: DIN EN 61340-5-1/ 61340-5-2.

Application: For maximum protection in sensitive electronic applications.

Order-No.	Ø	Length	Tip Length	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia	Tip Dia
07653 5	2.5	60	155	4.0	4.0	13.0	10	443-1297	
07654 2	3	60	155	5.0	5.0	13.0	10	443-1303	
07655 9	3.5	60	155	5.3	6.0	13.0	10	443-1315	
07656 6	4	60	155	5.5	6.0	13.0	10	443-1327	
07657 3	5	60	155	6.8	7.0	13.0	10	443-1339	
07658 0	5.5	60	170	7.6	8.0	14.0	10	443-1340	

Please note:  
These tools are not suited for working  
on live electrical components.