



Standard Size Sealed Rockette Switches



*Other terminations available



Stock No.	Mfr.'s Type	Circuit	Action (Momentary)	EACH		
				1-24	25-49	50-99
757-5539	NGR20011BNOON	DPST	On-None-Off	8.14	6.44	6.21
757-5540	NGR20041BNOON	DPDT	On-None-Off	11.10	8.79	8.47
757-5541	NGR20041BNOON	DPDT	On-Off-On	9.41	7.45	7.18
757-5542	NGR20051BNOON	DPDT	(On)-Off-(On)	11.30	8.95	8.62

757-5543	NGR25011BNAON	DPST	On-None-Off	12.09	9.76	9.40
757-5544	NGR25481BNAAN	DPDT	On-None-On	13.92	11.24	10.83
757-5545	NGR25681BNAAN	DPDT	On-Off-On	13.92	11.24	10.83
757-5546	NGR25881BNAAN	DPDT	(On)-Off-(On)	14.08	11.36	10.95

Stock No.	Mr.'s Type	Fig.	Description	EACH		
				1-24	25-49	50-99
757-5567	1B	A	Black Rocker, No Lens	1.60	1.26	1.20
757-5568	2C00050000500	B	Lens Hole Top/Bottom	2.27	1.85	1.79
757-5569	2A000500	C	Lens Hole Top	1.63	1.28	1.23
757-5570	2B000500	D	Lens Hole Bottom	1.63	1.28	1.23

Stock No.	Mfr.'s Type	Color	EACH		
			1-24	25-49	50-99
757-5551	28-5863	Green	.30	.23	.22
757-5552	28-5863-3	Amber	.30	.23	.22
757-5553	28-5863-2	Red	.30	.23	.22

Matte Finish/Rounded Bezel/Contoured Rocker — 1500/2500 Series

These switches come in lighted and non-lighted versions in a variety of standard or custom colors. They are UL, CSA and VDE approved. Ideal applications include appliances, electronic instrumentation, data processing, communications, medical and office equipment. Options available are legend stamping, solder lugs, independent lamp circuits, special and matched colors, high inrush capability. Aesthetically pleasing yet ruggedly functional with traditional Eaton quality, these switches are ideal for up-front applications where both appearance and reliability are required.

Panel Mount

Panel Mount

Panel Mount

Panel Mount

A 1.248" Max. 31.7
.594" 15.1

B 1.248" Max. 31.7
1.027" 26.1

C 1.248" Max. 31.7
.594" 15.1

D 1.248" Max. 31.7
1.027" 26.1

These switches come in lighted and non-lighted versions in a variety of standard or custom colors. They are UL, CSA and VDE approved. Ideal applications include appliances, electronic instrumentation, data processing, communications, medical and office equipment. Options available are legend stamping, solder lugs, independent lamp circuits, special and matched colors, high inrush capabilities. Aesthetically pleasing yet ruggedly functional with traditional Eaton quality, these switches are ideal for up-front applications where both appearance and reliability are required.

Illuminated Type (Rated: 15 A, 125 V; 10 A, 250 V)								
Stock No.	Mfr.'s Type*	Fig.	Circuit	Action	Lens Color	EACH		
						1-24	25-49	50-99
757-5007	1500R11E	C	SPST	On-None-Off	Red	2.40	2.15	1.78
757-5008	1500A11E	C	SPST	On-None-Off	Amber	2.50	2.24	1.89
757-5009	1500G11E	C	SPST	On-None-Off	Green	2.50	2.24	1.89
757-5010	2500R11E	D	DPST	On-None-Off	Red	2.82	2.36	1.94
757-5011	2500A11E	D	DPST	On-None-Off	Amber	3.50	3.15	2.63
757-5012	2500G11E	D	DPST	On-None-Off	Green	2.85	2.56	2.14

*Other lamp voltages are available.

Stock No.	Mfr.'s Type	Fig.	Circuit	Action	EACH		
					1-24	25-49	50-99
757-5020	1500-11E671	A	SPST	On-None-Off	1.33	1.17	.98
757-5021	2500-11E735	B	DPST	On-None-Off	2.05	1.71	1.43

E 183
Max.
30.3
555"
Max.
14.1

F 1,250"
31.7
1,027"
26.1

G 1,195"
Max.
30.3
555"
Max.
14.1

H 1,250"
31.7
1,027"
26.1

Stock No.	Mfr.'s Type	Fig.	Circuit	Action (Momentary)	EACH		
					1-24	25-49	50-99
757-3012	1600-11E	E	SPST	On-None-Off	1.35	1.17	.97
757-3013	1601-11E	E	SPST	(On)-None-Off	1.25	1.10	.93
757-3014	1602-11E	E	SPDT	On-None-On	1.52	1.33	1.12
757-3015	1604-11E	E	SPDT	On-Off-On	1.64	1.44	1.20
757-3016	1607-11E	F	DPST	On-None-Off	1.77	1.56	1.29
757-3017	2601-11E	F	DPST	(On)-None-Off	2.14	1.89	1.56
757-3018	2602-11E	F	DPDT	On-None-On	2.35	2.11	1.74
757-3019	2604-11E	F	DPDT	On-Off-On	2.66	2.39	1.98

Stock No.	Mfr.'s Type	Fig.	Circuit	Action	Lens Color	EACH		
						1-24	25-49	50-99
757-3020	1600R11E	G	SPST	On-None-Off	Red	2.51	2.24	1.89
757-3021	1600A11E	G	SPST	On-None-Off	Amber	2.51	2.24	1.89
757-3024	1600G11E	G	SPST	On-None-Off	Green	2.65	2.37	2.00
757-3025	2600R11E	H	DPST	On-None-Off	Red	3.14	2.81	2.32
757-3026	2600A11E	H	DPST	On-None-Off	Amber	3.14	2.81	2.32
757-3027	2600G11E	H	DPST	On-None-Off	Green	3.14	2.81	2.32

Stock No.	Mfr.'s Type	Fig.	Circuit	Action	Description	EACH		
						1-24	25-49	50-99
757-3028	1600H11E	E	SPST	On-None-Off	Black Gloss	1.54	1.35	1.12
757-3029	1600HR11E	F	SPST	On-None-Off	Red Lens,125 V Neon	2.70	2.42	2.03
757-3030	2600H11E	G	DPST	On-None-Off	Black Gloss	2.02	1.78	1.47
757-3031	2600HR11E	H	DPST	On-None-Off	Red Lens,125 V Neon	3.07	2.75	2.27