



TOLERANCES SEE TABLE FOR SPECIFIED, UNLESS OTHERWISE		
OVER	TO	TOLERANCE
	6	± 0.3
6	18	± 0.5
18	50	± 0.7
50	125	± 1
125	250	± 1.3
ANGULAR		$\pm 1^\circ$

- ① 4 PINS HEADER HAVE ONE PROJECTION AT CENTER. OTHER PINS HAVE 2PROJECTION AS PER DRAWING.
- ② CONTACT NOS. (1, 2, 9, 10... 40) AND NUMBER OF CONTACTS AND ONE SMALLER NUMBER OF CONTACTS SHALL BE MARKED.
- ③ 3 FORMAT CHANGING.
- ④ UNLESS OTHERWISE SPECIFIED, THE TOLERANCE SHALL CONFORM TO THE TABLE 1.

				1	POLYAMIDE	NATURAL(WHITE), UL94V-0		
NO.	MATERIAL	FINISH , REMARKS			NO.	MATERIAL	FINISH , REMARKS	
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED HT. SATO	CHECKED HK. UMEHARA	DATE 11. 03. 04	
 HIROSE ELECTRIC CO., LTD.		APPROVED : KJ. KATAYOSE		05. 01. 05	DRAWING NO. EDC3-160092-02			
		CHECKED : TY. OMA		05. 01. 05	PART NO. DF1B-*DS-2.5RC			
		DESIGNED : TS. KUMAZAWA		05. 01. 05	CODE NO. CL541			
		DRAWN : TS. KUMAZAWA		05. 01. 05	 			