



Technical Data


- through-hole or SMD
- 50mA/24VDC
- single pole/momentary
- 10.000.000 operations life time
- IP67 sealing
- temperature range:
 - low temp: -40/+115°C
 - high temp: -40/+160°C




Dimensions (through-hole)




**Dimensions w/LED in switch
(1C/1H)**



Dimensions w/LED PCB mounted (2B)



Dimensions (SMD)



How to order

3 A			+		+		
Switch	Mounting T through-hole S surface mount	L 6 low temp. H 9 high temp.		Cap 		Bezel 	
				00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black		00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black	
							For 1B and 2A only:
							30 ultra blue 40 dusty blue 42 aqua blue 32 mint green 33 tele grey 34 melon 38 noble red
							50 metal dark blue 53 metal light grey 57 metal dark grey 58 metal bordeaux

3 A	T		L 6 low temp. H 9 high temp.		LED 00 blue 20 green 40 yellow 80 red	+	1 C		 00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black	+		+		2 A	 00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black	
Switch	Mounting T through-hole															
3 A			L 6 low temp. H 9 high temp.	+	1 B		 00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black	+	2 B			 00 blue 02 green 03 grey 04 yellow 06 white 08 red 09 black	2 B			Lens 1 transparent 2 green 4 yellow 6 frosted white 8 red
Switch	Mounting T through-hole S surface mount															

Keycaps and bezels shown on this page can also be used on **illume™ switch 4A** - see page 9. Part nos. for bezels for 4A are 2C and 2D.

Keycaps and bezels shown on this page can also be used on
illumec™ switch 4A - see page 9. Part nos. for bezels for 4A are 2C and 2D.

Ordering example: 3ATL640 + 1C094 + 2A04

For updates of products and/or changes of specifications please see www.mec.dk