





P	LTR	DESCRIPTION	DATE	DWN	APVD
	D2	REVISED PER ECO-11-005140	01APR11	RK	HMR



注記;

1. 使用端子型番は170359,170360,170361,170362
2. 嵌合相手ハウジング型番は172161

NOTE;

1. APPLICABLE CONT P/N:170359,170360,170361,170362
2. MATING HSG P/N:172161

△3 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△3 OBSOLETE

黒 (BLACK)	1-172169-9
青 (BLUE)	1-172169-8
緑 (GREEN)	1-172169-5
赤 (RED)	1-172169-2
自然色 (NATURAL)	172169-1
色 (COLOR)	型番 (P/N)
WIRE RANGE 包含電線断面積	INSULATION DIA 被覆外径

DIMENSIONS: 単位: ㎜		TOLERANCES UNLESS OTHERWISE SPECIFIED 一般公差 (GENERAL TOLERANCE) ±0.3		DWN M. Yamazaki 2 Jun '98 CHK M. Shida 15 Jun '98 APVD M. Shida 15 Jun '98 PRODUCT SPEC 製品規格 108-5138 INSTRUCTION SHEET 取り扱い説明書 IS-105J WEIGHT —		NAME 名称 9極ミニユニバーサルメイトンロックプラグハウジング (UL94V-0) 9Pos MINI UNIVERSAL MATE-N-LOCK CONN.PLUG HOUSING (UL94V-0)							
MATERIAL 材料 66ナイロン UL94V-0 (66NYLON UL94V-0)		FINISH 仕上 —		SIZE A3		CAGE CODE 00779		DRAWING NO 番号 C-172169		RESTRICTED TO			
CUSTOMER DRAWING						SCALE 尺度 2-1		SHEET 1		OF 1		REV D2	

参考図面