


MATERIALS

CONNECTORS	PASSIVATED STAINLESS STEEL
CONTACT	GOLD PLATED
INSULATOR	PTFE
HEAT SINK	ANODIZED ALUMINUM



SPECIFICATIONS

FREQUENCY RANGE: DC TO 18 GHz

ATTENUATION: 20dB

IMPEDANCE: 50 OHMS

ACCURACY: ± 0.5 dB

VSWR:

DC — 4 GHz 1.15:1 MAX

4 GHz — 8 GHz 1.20:1 MAX

8 GHz — 12.4 GHz 1.25:1 MAX

12.4 GHz — 18 GHz 1.35:1 MAX

AVG. POWER HANDLING CAPABILITY: 5 WATTS



PASTERNAK ENTERPRISES, INC.

P.O BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE7052-20

DES.

TNC ATTENUATOR, 5 WATT FREQUENCY
RANGE: DC TO 18 GHz

SIZE A

FSCM NO. 53919

CAD FILE 080502

SCALE N/A

127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.