

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS



P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	16MAR2015	DL	CW
	B	ECR-15-013292	24SEP2015	DL	CW
	B1	ECR-16-015492	15NOV2016	QY	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250 V
RATED CURRENT: 10 A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 2.5 KV
POLLUTION DEGREE: 2
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.14-2.5 mm² (26-14 AWG)
CONTACT TYPE: CRIMP CONTACT
2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20200X10XX000)



注释:

1. 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 2.5 KV
污染等级: 2
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: 0.14-2.5 mm² (26-14 AWG)
接线类型: 冷压接
2. 端子需要单独订购.
(订货号参考图面: T20200X10XX000)






TYPE-1, T2030242101-000, TE LOGO
类型-1, T2030242101-000, TE LOGO

M4 SCREW RECOMMENDED
TIGHTENING TORQUE 1.2Nm
M4 螺丝, 推荐锁紧力矩 1.2Nm



4X M3 SCREW RECOMMENDED
TIGHTENING TORQUE 0.5Nm
4X M3螺丝, 推荐锁紧力矩 0.5Nm




PANEL CUT OUT FOR INSERTS FOR USING
WITHOUT HODDS/HOUSINGS
不用防护外壳时芯件的安装开孔图

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DAVIE LI 16MAR2015	 TE Connectivity		
		CHK CHRIS WANG 16MAR2015			
		APVD XU XIANG 16MAR2015	NAME HDD-024-M		
DIMENSIONS: mm		PRODUCT SPEC 108-137043			
		APPLICATION SPEC 114-137043			
MATERIAL -		WEIGHT -	SIZE A3	CAGE CODE -	DRAWING NO T2030242101000
		CUSTOMER DRAWING	SCALE 1:1	SHEET 1 OF 2	REV B1

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1	-	-	-

D







D

NOTE :
SEE SHEET 1


注释 :
见页 1

C



C

B




B

TYPE-2,T2030242101-002,STAINLESS STEEL SCREW,NO LOGO
类型-2,T2030242101-002,不锈钢螺丝,无LOGO

T2030242101-002	HDD-024-M	HDD-024 MALE INSERT, STAINLESS STEEL SCREW,NO LOGO HDD-024 公插,不锈钢螺丝,无LOGO	TYPE-2 类 型-2
T2030242101-000	HDD-024-M	HDD-024 MALE INSERT HDD-024 公插	TYPE-1 类 型-1
PART NUMBER 料 号	PART DESCRIPTION 描 述		TYPE 类 型

ALL DIMENSIONS ARE SAME AS TYPE 1,
EXCEPT THOSE DEFINED IN THIS TYPE.
除了在本类型中定义的尺寸外,其它尺寸同类型1

A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DAVIE LI 16MAR2015	 TE Connectivity					
		CHK CHRIS WANG 16MAR2015						
DIMENSIONS: mm		APVD XU XIANG 16MAR2015	NAME HDD-024-M					
		PRODUCT SPEC 108-137043	SIZE A3					
		APPLICATION SPEC 114-137043					CAGE CODE -	
		DRAWING NO C-T2030242101000						
MATERIAL -		WEIGHT -	RESTRICTED TO -					
FINISH -		CUSTOMER DRAWING		SCALE 1:1	SHEET 2 OF 2	REV B1		

A