

Technical drawing of a three-roller assembly. The drawing shows a cross-section of three rollers arranged horizontally. The total length of the assembly is labeled L . The distance between the centers of the rollers is labeled D . The diameter of the rollers is labeled $\varnothing C$ min. The diameter of the central roller is labeled $\varnothing B$ min. The distance from the center of the central roller to the right edge of the assembly is labeled 150 min (5.9 min). The rollers are numbered 1, 2, and 3 from left to right. The rollers are shown with different hatching patterns to indicate different materials or sections.

MATERIAL

- ## APPLICATION

- Colors available:
20AWG-black, green, white
22AWG-black, green, white
24AWG-black, blue, white
26AWG-black, white
All gauges: White with a single black stripe.

 TE Connectivity		Raychem Devices		TITLE: SOLDERSLLEEVE* DEVICE TERMINATION WITH LEADS			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.				DOCUMENT NO.: ST63-X-55-GA-CL			
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	Raychem reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		ECO NUMBER: ECO-19-005864		ISSUE DATE: 15-APRIL-2019	
DRAWN BY: R. MAPALO	DRAWN DATE: 08/12/1998	CAD FILE: ST63-X-55-GA-CL	CAGE CODE: 06090	DOC ISSUE: E1	SCALE: NONE	SIZE: A	SHEET: 1 of 1