

Cord Connectors

Straight Male

Form Size 5-8



Cast Aluminum

Cast Aluminum
Malleable Iron

UL Listed to Type 4, 4X, 12 and Type 13

**IP66***
SUITABILITY

N.P.T. Hub Size	Cord Dia. Inches	(mm)	Form Size	Cast Aluminum	Malleable Iron†
1"	.88"-1.00"	(22.2-25.4)	F5	SHC1046	•
	1.00"-1.13"	(25.4-28.6)		SHC1047**	•
	1.13"-1.25"	(28.6-31.7)		SHC1048**	•
	1.25"-1.38"	(31.7-34.9)		SHC1049**	•
1 1/4"	.75"-.88"	(19.0-22.2)	F5	SHC1050	•
	.88"-1.00"	(22.2-25.4)		SHC1051	•
	1.00"-1.13"	(25.4-28.6)		SHC1052	SHC1052ZP
	1.13"-1.25"	(28.6-31.7)		SHC1053	SHC1053ZP
1 1/2"	1.25"-1.38"	(31.7-34.9)	F5	SHC1054**	SHC1054ZP
	.75"-.88"	(19.0-22.2)		SHC1055	•
	.88"-1.00"	(22.2-25.4)		SHC1056	•
	1.00"-1.13"	(25.4-28.6)		SHC1057	SHC1057ZP
1 1/2"	1.13"-1.25"	(28.6-31.7)	F6	SHC1058	SHC1058ZP
	1.25"-1.38"	(31.7-34.9)		SHC1059	SHC1059ZP
	1.38"-1.50"	(34.9-38.1)		SHC1061	•
	1.50"-1.63"	(38.1-41.3)		SHC1062**	•
2"	1.63"-1.75"	(41.3-44.4)	F6	SHC1063**	•
	1.75"-1.88"	(44.4-47.6)		SHC1064**	•
	1.25"-1.38"	(31.7-34.9)		SHC1065	•
	1.38"-1.50"	(34.9-38.1)		SHC1066	•
2"	1.50"-1.63"	(38.1-41.3)	F7	SHC1067	•
	1.63"-1.75"	(41.3-44.4)		SHC1068	•
	1.75"-1.88"	(44.4-47.6)		SHC1069	•
	1.69"-1.81"	(42.9-46.0)		SHC1070	•
2"	1.81"-1.94"	(46.0-49.2)	F7	SHC1071	•
	1.94"-2.06"	(49.2-52.4)		SHC1072**	•
	2.06"-2.19"	(52.4-55.6)		SHC1073**	•
	2.19"-2.31"	(55.6-58.7)		SHC1074**	•
2 1/2"	2.19"-2.31"	(55.6-58.7)	F7	SHC1076	•
	2.31"-2.44"	(58.7-61.9)		SHC1077	•
	1.69"-1.81"	(42.9-46.0)		SHC1078	•
	1.81"-1.94"	(46.0-49.2)		SHC1079	•
3"	1.94"-2.06"	(49.2-52.4)	F7	SHC1080	•
	2.06"-2.19"	(52.4-55.6)		SHC1081**	•
	2.19"-2.31"	(55.6-58.7)		SHC1086	•
	2.31"-2.44"	(58.7-61.9)		SHC1087	•
3"	2.44"-2.63"	(61.9-66.7)	F8	SHC1088	•
	2.63"-2.81"	(66.7-71.4)		SHC1089	•
	2.81"-3.00"	(71.4-76.2)		SHC1090	•
	3.00"-3.25"	(76.2-82.5)		SHC1091	•
3"	2.44"-2.63"	(61.9-66.7)	F8	SHC1092	•
	2.63"-2.81"	(66.7-71.4)		SHC1093	•
	2.81"-3.00"	(71.4-76.2)		SHC1094	•
	3.00"-3.25"	(76.2-82.5)		SHC1095**	•

Note: See pages T-87 to T-98 for additional technical data and dimensional drawings.

*IP66 Suitability when used with optional metal clad O-ring shown on page T-83.

**Cable jacket may have to be stripped to pass through connector body.

F5 and larger will not be color coded.