

# Soldering Station

**TENMA**™



## Features:

- Light-weight handle design, suitable for use for a long time
- Imported heating element made in high quality materials using advanced technology, extending using life and saves cost
- Split design of heating element, easy to replace
- Soldering tip is compatible to any international brand, according to your working condition, you can choose suitable iron tip
- Soldering station is made of conductive materials makes it anti static
- 150 to 450°C setting temperature, LCD display, using three programmable knobs, you can choose every temperature you want to set

## Apply

Manufacturing production line

On field soldering jobs

Lead-free solder

## Specifications:

Input voltage	: 220 V ±10% 50 Hz
Output voltage	: 26 V ac
Temperature range	: 150 to 450°C
Temperature stability	: ±1°C (static working model)
Leak resistance of soldering tip	: < 2 Ω
Leak voltage of soldering tip	: < 5 mV

## Part Number Table

Description	Part Number
Soldering Station, Digital, EU	21-10120 EU
Soldering Station, Digital, UK	21-10120 UK

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2011.