

Formerly MIL-C-5015 Types A and B

See page 429 for dimension table. MS receptacles mate with MS mating plugs that are on the same line in the table below. *Standard shells have cadmium plating with drab olive chrome finish. In shell sizes 12S, 14S, 16, 16S, 18, 20, 22, 24, and 28, clear chromate over cadmium plating (639), black zinc over zinc plating (621), or electroless nickel plating (689) are also available. Add the shell finish identification to the end of part number to specify a shell finish other than drab olive. *notes the shell styles that are available with all four of these finish choices. Pricing shown is for standard drab olive and for (639) clear chromate and (621) black zinc finishes. Prices for finish (689) are higher. See page 436 for cable clamps and other accessories.

MS Receptacles

No. of Contacts	Shell Size and Insert	97-3100A*		97-3101A*		97-3102A*	
		EACH		EACH		EACH	
		1-9	10-49	1-9	10-49	1-9	10-49
6	20-8S*	45.26	30.59	41.03	31.84	33.03	25.62
13	20-11P	30.89	25.28	34.76	25.09	20.53	
13	20-11S	61.78	46.18	57.29	44.45	46.81	38.30
5	20-14P	38.41	30.72	36.08	27.99	28.07	21.78
5	20-14S	51.02	36.63	50.19	38.95	42.18	32.72
7	20-15P	18.74	14.99	21.08	14.74	12.21	9.77
7	20-15S	24.89	19.91	26.11	20.89	18.33	14.67
9	20-16P	20.37	14.45	18.87	15.43	11.76	9.63
9	20-16S	21.32	15.37	19.65	16.08	15.22	10.76
6	20-17P	21.80	18.34	21.84	16.95	23.64	19.34
6	20-17S	26.33	22.55	26.58	20.62	17.11	14.00
9	20-18P	23.34	16.25	20.07	17.16	16.28	11.48
9	20-18S	25.80	18.51	26.57	18.44	16.34	13.37
3	20-19P	24.45	20.55	24.33	18.88	15.86	12.30
3	20-19S	29.46	25.43	27.22	22.27	21.55	16.73
9	20-21P	36.84	24.89	30.78	23.87	22.99	17.85
9	20-21S	38.71	26.18	33.30	25.83	25.53	19.81
2	20-23P	18.04	14.76	19.14	15.66	12.16	9.95
2	20-23S	23.36	16.27	24.76	17.19	16.67	11.73
4	20-24P	37.59	25.43	31.59	24.51	23.83	18.49
4	20-24S	46.60	31.51	37.40	29.02	27.63	22.61
14	20-27P	19.97	14.06	21.82	15.21	12.70	10.16
14	20-27S	20.45	16.36	23.61	16.43	16.30	11.49
17	20-29P	21.04	15.10	21.75	17.40	13.97	11.18
17	20-29S	22.92	18.34	24.15	19.32	16.37	13.10
11	20-33P	24.35	17.28	22.09	18.08	17.75	12.47
11	20-33S	21.33	17.45	26.44	18.34	15.50	12.69
2	22-1P	17.81	14.84	19.61	16.04	11.79	9.64
2	22-1S	26.07	20.36	25.91	20.10	15.44	12.63
3	22-2P	24.05	16.97	25.23	17.56	15.92	11.25
3	22-2S	23.83	19.86	26.27	21.49	21.16	14.78
4	22-4P	42.58	28.76	36.77	29.41	27.57	21.40
4	22-4S	48.37	32.71	42.91	34.34	34.13	26.47
6	22-5P	39.62	26.77	41.50	28.53	25.38	17.61
6	22-5S	25.38	21.15	41.59	28.56	20.40	15.83
2	22-8P	33.99	22.97	26.51	21.20	16.48	12.78
2	22-8S	42.52	28.72	35.83	28.66	26.53	20.59
3	22-9P	35.86	24.25	26.53	21.22	16.51	12.80
3	22-9S	44.89	30.36	35.13	28.11	24.21	19.81
4	22-10P	35.57	24.53	23.01	18.82	21.08	14.69
4	22-10S	21.81	18.17	24.03	19.66	16.23	13.28
2	22-11P	33.07	22.34	25.74	20.58	15.69	12.18
2	22-11S	35.50	24.01	28.39	22.71	15.36	12.56
5	22-12P	42.58	31.84	40.32	32.99	34.51	26.77
5	22-12S	49.62	33.56	44.17	35.33	35.46	27.51
5	22-13P	39.46	26.68	33.07	26.45	23.83	18.49
5	22-13S	41.50	30.05	37.84	30.27	28.72	22.28
19	22-14P	23.20	18.56	24.20	19.36	8.74	6.35
19	22-14S	26.32	21.05	27.31	21.85	20.73	14.52
6	22-15P	42.20	28.53	35.61	28.48	22.22	18.51
6	22-15S	51.22	34.63	46.33	37.05	37.74	29.29
9	22-16P	25.69	19.90	26.29	21.04	16.27	12.64
9	22-16S	26.07	20.44	26.84	21.45	16.85	13.08
8	22-18P	22.12	16.10	24.35	18.05	15.06	10.66
8	22-18S	23.36	16.27	20.83	17.04	12.97	10.61
14	22-19P	20.05	16.71	22.10	18.08	14.28	11.68
14	22-19S	24.89	17.89	22.60	18.49	14.78	12.09
9	22-20P	19.24	16.03	21.17	17.32	13.37	10.94
9	22-20S	19.77	16.47	26.00	18.05	13.96	11.42
4	22-22P	27.55	19.10	28.62	20.96	16.98	13.89
4	22-22S	34.20	23.58	31.44	25.72	23.64	19.34
8	22-23P	26.52	18.39	23.82	19.49	18.29	12.87
8	22-23S	33.31	22.97	30.99	25.35	17.73	
7	22-26P	43.64	29.50	37.75	30.19	28.59	22.18
7	22-26S	49.62	33.56	44.17	35.33	35.46	27.51
9	22-27P	25.81	17.43	26.92	20.51	15.63	12.80
9	22-27S	27.95	19.34	21.83	17.48	14.30	
7	22-28P	43.18	29.18	37.25	29.80	28.07	21.78
7	22-28S	59.56	41.62	55.49	44.38	47.50	36.87
5	22-34P	39.46	26.68	34.56	28.80	19.37	15.85
5	22-34S	41.39	27.99	34.87	27.90	25.81	20.02
7	24-2P	25.02	17.38	25.16	18.70	16.45	11.60
7	24-2S	29.61	20.49	29.77	21.73	18.61	15.23
16	24-5P	30.55	21.13	26.47	21.66	19.77	15.83
16	24-5S	34.18	23.58	34.22	26.73	23.46	18.77
8	24-6P	48.92	33.53	49.00	33.57	32.00	22.11
8	24-6S	63.05	43.05	42.80	35.67	46.85	32.14
16	24-7P	28.56	19.77	28.62	19.81	17.45	14.28
16	24-7S	25.56	21.30	25.60	21.34	22.42	15.63
2	24-9P	38.42	28.38	38.50	30.80	29.30	22.72
2	24-9S	44.47	32.84	44.80	35.85	29.13	23.83
7	24-10P	41.26	27.50	32.99	27.49	29.87	20.66

UL Approved
File # E 115497CSA Certified
File # LR 69183