

# Micro BetaCHIP Probes (MCD)

2 to 100K Ohms Resistance @25°C  
±0.2°C Tolerance from 0°C to +70°C  
Fast Time Response  
Small Tip Diameter



## MCD PROBE

NTC thermistor soldered to 38 AWG Solid Nickel Bifilar with Polyester Type Insulation. Unit is potted in a polyimide tube with thermally conductive epoxy.


## FEATURES

- 2 to 100K Ohms Resistance @25°C
- Supplied with ±0.2°C tolerance @ +25°C
- Custom tolerances available
- Smaller than mini BetaCURVE device
- Rapid time response (200 milliseconds in liquids)
- Temperature range -40°C to +125°C
- RoHS Compliant

## APPLICATIONS

- Low volume flow sensors (liquids or gases)
- Laboratory animal research
- Peltiere temperature tracking sensors
- Temperature control for bath showers
- DNA research sensors
- Medical catheters

## Dimensions



# Micro BetaCHIP Probes (MCD)

## Product Definition

Part Number	Resistance [Ω] @+25°C	Beta Value 25/85	Time response in liquids [milliseconds]	Dissipation Constant in still air [mW/°C]	Temperature Range
<a href="#">2K7MCD1</a>	2,000	3499	200	0.3	-40°C to +125°C
<a href="#">10K3MCD1</a>	10,000	3976	200	0.3	-40°C to +125°C
<a href="#">100K6MCD1</a>	100,000	4261	200	0.3	-40°C to +125°C

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

## Ordering Information

### NORTH AMERICA

Measurement Specialties, Inc.  
910 Turnpike Road  
Shrewsbury, MA 01545  
Tel: 1-508-842-0516  
Fax: 1-508-842-0342

Sales email:  
[temperature.sales.amer@meas-spec.com](mailto:temperature.sales.amer@meas-spec.com)

### EUROPE

Measurement Specialties, Inc  
Ballybrit Business Park  
Galway Ireland  
Tel: +353-91-753238  
Fax: +353-91-770789

Sales email:  
[temperature.sales.emea@meas-spec.com](mailto:temperature.sales.emea@meas-spec.com)

### ASIA

Measurement Specialties (China) Ltd.  
No. 26 Langshan Road  
Shenzhen High-Tech Park (North)  
Nanshan District, Shenzhen 51807  
China  
Tel: +86 (0) 755 33305088  
Fax: +86 (0) 755 33305099

Sales email:  
[temperature.sales.asia@meas-spec.com](mailto:temperature.sales.asia@meas-spec.com)