

## Highly Accurate, Ultra Small, Low Power Consumption Voltage Detector

### ■ GENERAL DESCRIPTION

The XC6120 series are highly precise, low power consumption voltage detectors, manufactured using CMOS and laser trimming technologies. With low power consumption and high accuracy, the series is suitable for precision mobile equipment. The XC6120 in ultra small packages are ideally suited for high-density mounting. The XC6120 is available in both CMOS and N-channel open drain output configurations.


### ■ APPLICATIONS

- Microprocessor reset circuitry
- Memory battery back-up circuits
- Power-on reset circuits
- Power failure detection
- System battery life and charge voltage monitors

### ■ FEATURES


- Highly Accurate** :  $\pm 2\%$  ( $V_{DF} \geq 1.5V$ )  
:  $\pm 30mV$  ( $V_{DF} < 1.5V$ )
- Low Power Consumption** :  $0.6 \mu A$  [ $V_{DF}=2.7V$ ,  $V_{IN}=2.97V$ ]
- Detect Voltage Range** :  $1.0V \sim 5.0V$  (0.1V increments)
- Operating Voltage Range** :  $0.7V \sim 6.0V$
- Detect Voltage Temperature Characteristics**  
:  $\pm 100ppm/^{\circ}C$  (TYP.)
- Output Configuration** : CMOS (XC6120C)  
: N-channel open drain (XC6120N)
- Operating Temperature Range** :  $-40^{\circ}C \sim 85^{\circ}C$
- Packages** : USP-3, SSOT-24
- Environmentally Friendly** : EU RoHS Compliant, Pb Free

### ■ TYPICAL APPLICATION CIRCUIT




### ■ TYPICAL PERFORMANCE CHARACTERISTICS

#### ● Supply Current vs. Input Voltage



## PIN CONFIGURATION



## PIN ASSIGNMENT

| PIN NUMBER |         | PIN NAME  | FUNCTION               |
|------------|---------|-----------|------------------------|
| USP-3      | SSOT-24 |           |                        |
| 1          | 4       | $V_{IN}$  | Power Input            |
| 3          | 2       | $V_{SS}$  | Ground                 |
| 2          | 3       | $V_{OUT}$ | Output (Detect "Low" ) |
| -          | 1       | NC        | No Connection          |

## PRODUCT CLASSIFICATION

### Ordering Information


XC6120①②③④⑤⑥-⑦<sup>(\*)</sup>

| DESIGNATOR          | ITEM                        | SYMBOL | DESCRIPTION               |
|---------------------|-----------------------------|--------|---------------------------|
| ①                   | Output Configuration        | C      | CMOS output               |
|                     |                             | N      | N-ch open drain output    |
| ②③                  | Detect Voltage ( $V_{DF}$ ) | 10~50  | For example 1.0V → ②1, ③0 |
| ④                   | Detect Accuracy             | 2      | $\pm 2\%$                 |
| ⑤⑥-⑦ <sup>(*)</sup> | Packages<br>(Order Unit)    | HR     | USP-3 (3,000/Reel)        |
|                     |                             | HR-G   | USP-3 (3,000/Reel)        |
|                     |                             | NR     | SSOT-24 (3,000/Reel)      |
|                     |                             | NR-G   | SSOT-24 (3,000/Reel)      |


<sup>(\*)</sup> The "-G" suffix indicates that the products are Halogen and Antimony free as well as being fully RoHS compliant.

## BLOCK DIAGRAMS

(1) XC6120C



(2) XC6120N



## ■ ABSOLUTE MAXIMUM RATINGS

Ta=25°C

| PARAMETER                   |                        | SYMBOL    | RATING                      | UNITS |
|-----------------------------|------------------------|-----------|-----------------------------|-------|
| Input Voltage               |                        | $V_{IN}$  | $V_{SS}-0.3\sim 7.0$        | V     |
| Output Current              |                        | $I_{OUT}$ | 10                          | mA    |
| Output Voltage              | CMOS Output            | $V_{OUT}$ | $V_{SS}-0.3\sim V_{IN}+0.3$ | V     |
|                             | N-ch Open Drain Output |           | $V_{SS}-0.3\sim 7.0$        |       |
| Power Dissipation           | USP-3                  | $P_d$     | 120                         | mW    |
|                             | SSOT-24                |           | 150                         |       |
| Operating Temperature Range |                        | $T_{opr}$ | $-40\sim +85$               | °C    |
| Storage Temperature Range   |                        | $T_{stg}$ | $-55\sim +125$              | °C    |

## ■ ELECTRICAL CHARACTERISTICS

XC6120 Series

Ta=25°C

| PARAMETER                   |                  | SYMBOL                                          | CONDITION                                                                  | MIN.                  | TYP.                  | MAX.               | UNITS  | CIRCUIT |
|-----------------------------|------------------|-------------------------------------------------|----------------------------------------------------------------------------|-----------------------|-----------------------|--------------------|--------|---------|
| Operating Voltage           |                  | $V_{IN}$                                        | $V_{DF(T)}=1.0\sim 5.0V$ (*1)                                              | 0.7                   | -                     | 6.0                | V      | -       |
| Detect Voltage              |                  | $V_{DF}$                                        | $V_{DF(T)}=1.0V\sim 5.0V$                                                  | E-1                   |                       |                    | V      | ①       |
| Hysteresis Width            |                  | $V_{HYS}$                                       | $V_{DF(T)}=1.0V\sim 5.0V$                                                  | $V_{DF}$<br>×<br>0.03 | $V_{DF}$<br>×<br>0.05 | $V_{DF}$<br>× 0.07 | V      | ①       |
| Supply Current 1            |                  | $I_{SS1}$                                       | $V_{IN}=V_{DF(T)} \times 1.1$                                              | E-2                   |                       |                    | μA     | ②       |
| Supply Current 2            |                  | $I_{SS2}$                                       | $V_{IN}=V_{DF(T)} \times 0.9V$                                             | E-3                   |                       |                    | μA     | ②       |
| Output Current              | $I_{OUTN}$       | $V_{IN}=0.7V$                                   | $V_{OUT}=0.5V$                                                             | 0.09                  | 0.57                  | -                  | mA     | ③       |
|                             |                  |                                                 | $V_{OUT}=0.3V$                                                             | 0.08                  | 0.56                  | -                  |        |         |
|                             |                  |                                                 | $V_{OUT}=0.1V$                                                             | 0.05                  | 0.30                  | -                  |        |         |
|                             |                  | $V_{IN}=1.0V$                                   | $V_{OUT}=0.1V, V_{DF(T)} > 1.0V$                                           | 0.46                  | 0.71                  | -                  |        |         |
|                             |                  | $V_{IN}=2.0V$                                   | $V_{OUT}=0.1V, V_{DF(T)} > 2.0V$                                           | 1.15                  | 1.41                  | -                  |        |         |
|                             |                  | $V_{IN}=3.0V$                                   | $V_{OUT}=0.1V, V_{DF(T)} > 3.0V$                                           | 1.44                  | 1.77                  | -                  |        |         |
|                             |                  | $V_{IN}=4.0V$                                   | $V_{OUT}=0.1V, V_{DF(T)} > 4.0V$                                           | 1.61                  | 1.96                  | -                  |        |         |
|                             | $I_{OUTP}$ (*2)  | $V_{IN}=6.0V$                                   | $V_{OUT}=5.5V$                                                             | -                     | -0.95                 | -0.60              | mA     | ③       |
| Leakage Current             | CMOS Output(Pch) | $I_{LEAK}$                                      | $V_{IN}=V_{DF} \times 0.9V, V_{OUT}=0V$                                    | -                     | -0.001                | -                  | μA     | ③       |
|                             | N-ch Open Drain  |                                                 | $V_{IN}=6.0V, V_{OUT}=6.0V$                                                | -                     | 0.001                 | 0.10               |        |         |
| Temperature Characteristics |                  | $\Delta V_{DF} / (\Delta T_{opr} \cdot V_{DF})$ | $-40^\circ C \leq T_{opr} \leq 85^\circ C$                                 | -                     | ±100                  | -                  | ppm/°C | ①       |
| Detect Delay Time (*3)      |                  | $t_{DF}$                                        | $V_{IN}=6.0V \rightarrow 0.7V$<br>$V_{IN}=V_{DF}$ to $V_{OUT}=0.5V$        | -                     | 30                    | 100                | μs     | ④       |
| Release Delay Time (*5)     |                  | $t_{DR}$                                        | $V_{IN}=0.7V \rightarrow 6.0V$<br>$V_{IN}=V_{DR}$ to $V_{OUT}=V_{DR}$ (*4) | -                     | 20                    | 100                | μs     | ④       |

\*1:  $V_{DF(T)}$ : Nominal detect voltage

\*2: For XC6120C only.

\*3: A time taking from the time at  $V_{IN} = V_{DF}$  to the time at  $V_{OUT}=0.5V$  when  $V_{IN}$  falls from 6.0V to 0.7V.\*4:  $V_{DR}$ : Release voltage ( $V_{DR} = V_{DF} + V_{HYS}$ )\*5: A time taking from the time at  $V_{IN} = V_{DR}$  to the time at  $V_{OUT} = V_{DR}$  when  $V_{IN}$  rise from 0.7V to 6.0V.

●XC6120N recommended pull-up resistance

| Input Voltage Range | Pull-up Resistance |
|---------------------|--------------------|
| 0.7V~6.0V           | ≥ 220kΩ            |
| 0.8V~6.0V           | ≥ 100kΩ            |
| 1.0V~6.0V           | ≥ 33kΩ             |

## ELECTRICAL CHARACTERISTICS (Continued)


### ● DETECT VOLTAGE ACCURACY AND SUPPLY CURRENT SPECIFICATIONS

| SYMBOL                 | E-1                                      |       | E-2                   |      | E-3                   |      |
|------------------------|------------------------------------------|-------|-----------------------|------|-----------------------|------|
| PARAMETER              | DETECT VOLTAGE                           |       | SUPPLY CURRENT 1      |      | SUPPLY CURRENT 2      |      |
| NOMINAL DETECT VOLTAGE | V <sub>DF</sub> (V)<br>XC6120xxx2 Series |       | I <sub>SS1</sub> (μA) |      | I <sub>SS2</sub> (μA) |      |
| V <sub>DF(T)</sub>     | MIN.                                     | MAX.  | TYP.                  | MAX. | TYP.                  | MAX. |
| 1.0                    | 0.970                                    | 1.030 | 0.5                   | 1.4  | 0.4                   | 1.35 |
| 1.1                    | 1.070                                    | 1.130 |                       |      |                       |      |
| 1.2                    | 1.170                                    | 1.230 |                       |      |                       |      |
| 1.3                    | 1.270                                    | 1.330 |                       |      |                       |      |
| 1.4                    | 1.370                                    | 1.430 |                       |      |                       |      |
| 1.5                    | 1.470                                    | 1.530 |                       |      |                       |      |
| 1.6                    | 1.568                                    | 1.632 |                       |      |                       |      |
| 1.7                    | 1.666                                    | 1.734 |                       |      |                       |      |
| 1.8                    | 1.764                                    | 1.836 |                       |      |                       |      |
| 1.9                    | 1.862                                    | 1.938 |                       |      |                       |      |
| 2.0                    | 1.960                                    | 2.040 | 0.6                   | 1.7  | 0.5                   | 1.60 |
| 2.1                    | 2.058                                    | 2.142 |                       |      |                       |      |
| 2.2                    | 2.156                                    | 2.244 |                       |      |                       |      |
| 2.3                    | 2.254                                    | 2.346 |                       |      |                       |      |
| 2.4                    | 2.352                                    | 2.448 |                       |      |                       |      |
| 2.5                    | 2.450                                    | 2.550 |                       |      |                       |      |
| 2.6                    | 2.548                                    | 2.652 |                       |      |                       |      |
| 2.7                    | 2.646                                    | 2.754 |                       |      |                       |      |
| 2.8                    | 2.744                                    | 2.856 | 0.7                   | 1.9  | 0.6                   | 1.80 |
| 2.9                    | 2.842                                    | 2.958 |                       |      |                       |      |
| 3.0                    | 2.940                                    | 3.060 |                       |      |                       |      |
| 3.1                    | 3.038                                    | 3.162 |                       |      |                       |      |
| 3.2                    | 3.136                                    | 3.264 |                       |      |                       |      |
| 3.3                    | 3.234                                    | 3.366 |                       |      |                       |      |
| 3.4                    | 3.332                                    | 3.468 |                       |      |                       |      |
| 3.5                    | 3.430                                    | 3.570 |                       |      |                       |      |
| 3.6                    | 3.528                                    | 3.672 |                       |      |                       |      |
| 3.7                    | 3.626                                    | 3.774 |                       |      |                       |      |
| 3.8                    | 3.724                                    | 3.876 |                       |      |                       |      |
| 3.9                    | 3.822                                    | 3.978 |                       |      |                       |      |
| 4.0                    | 3.920                                    | 4.080 |                       |      |                       |      |
| 4.1                    | 4.018                                    | 4.182 |                       |      |                       |      |
| 4.2                    | 4.116                                    | 4.284 |                       |      |                       |      |
| 4.3                    | 4.214                                    | 4.386 |                       |      |                       |      |
| 4.4                    | 4.312                                    | 4.488 |                       |      |                       |      |
| 4.5                    | 4.410                                    | 4.590 |                       |      |                       |      |
| 4.6                    | 4.508                                    | 4.692 |                       |      |                       |      |
| 4.7                    | 4.606                                    | 4.794 |                       |      |                       |      |
| 4.8                    | 4.704                                    | 4.896 |                       |      |                       |      |
| 4.9                    | 4.802                                    | 4.998 |                       |      |                       |      |
| 5.0                    | 4.900                                    | 5.100 |                       |      |                       |      |


(※6) When detect voltage is  $1.0\text{V} \leq V_{DF(T)} < 1.5\text{V}$ , detect accuracy is  $\pm 30\text{mV}$ .  
When detect voltage is  $1.5\text{V} \leq V_{DF(T)} \leq 5.0\text{V}$ , detect accuracy is  $\pm 2\%$ .

## ■ TEST CIRCUITS


Circuit 1




Circuit 2



Circuit 3




Circuit 4




## OPERATIONAL EXPLANATION

### ● Typical Application Circuit



### ● Timing Charge




Note: For explaining in a simplified case, an operation time of the circuit is not counted.

The following explains the operation of the typical application circuit along number symbols shown in the timing chart.

- ① When input voltage ( $V_{IN}$ ) is higher than detect voltage ( $V_{DF}$ ), output voltage ( $V_{OUT}$ ) will be equal to input voltage ( $V_{IN}$ ). (A condition of high impedance exists with N-ch open drain output configurations.)
- ② When input voltage ( $V_{IN}$ ) falls below detect voltage ( $V_{DF}$ ), output voltage ( $V_{OUT}$ ) will be equal to the ground voltage ( $V_{SS}$ ) level.
- ③ When input voltage ( $V_{IN}$ ) falls to a level below that of the minimum operating voltage ( $V_{MIN}$ ), output will become unstable. If in this condition,  $V_{IN}$  will equal the pulled-up output (should output be pulled-up.) (Input voltage,  $V_{IN}$ , in the typical application circuit.)
- ④ When input voltage ( $V_{IN}$ ) rises above the minimum operating voltage ( $V_{MIN}$ ) level until it achieves a release voltage ( $V_{DR}$ ), output keeps the ground voltage level ( $V_{SS}$ ).
- ⑤ When the input voltage ( $V_{IN}$ ) rises above the release voltage ( $V_{DR}$ ), output voltage ( $V_{OUT}$ ) will be equal to input voltage ( $V_{IN}$ ). (A condition of high impedance exists with N-ch open drain output configurations.)
- ⑥ The difference between  $V_{DR}$  and  $V_{DF}$  represents the hysteresis width.

## ■ NOTE ON USE

1. Please use this IC within the stated maximum ratings. For temporary, transitional voltage drop or voltage rising phenomenon, the IC is liable to malfunction should the ratings be exceeded.
2. In order to stabilize the IC's operations, please ensure that  $V_{IN}$  pin's input frequency's rise and fall times are more than several  $\mu s / V$ .
3. With a resistor connected between the  $V_{IN}$  pin and the power supply  $V_{DD}$  some errors may be observed from the input voltage at the detect and release voltage. Those errors are not constant because of the fluctuation of the supply current.
4. When a resistor is connected between the  $V_{IN}$  pin and the power supply  $V_{DD}$ , oscillation may occur as a result of through current and voltage drop at the  $R_{IN}$  at the time of voltage release. (refer to the Oscillation Description (1) below ) Especially in the CMOS output configurations, oscillation may occur regardless of detect/release operation if load current ( $I_{OUT}$ ) exists. (refer to the Oscillation Description (2) below)
5. Please use N-ch open drains configuration, when a resistor  $R_{IN}$  is connected between the  $V_{IN}$  pin and the power supply  $V_{DD}$  power source. In such cases, please ensure that  $R_{IN}$  is less than  $10k\Omega$  and that  $C$  is more than  $0.1 \mu F$ .
6. Torex places an importance on improving our products and its reliability.  
However, by any possibility, we would request user fail-safe design and post-aging treatment on system or equipment.



[Figure 1: Circuit connected with the input resistor]


### ● Oscillation Description

#### (1) Oscillation as a result of through current

Since the XC6120 series are CMOS ICs, transient through current will flow when the IC's internal circuit switching operates regardless of output configuration. Consequently, oscillation is liable to occur as a result of the similar operations as in (1) above. This oscillation does not occur during the detect operation.

#### (2) Output current oscillation with the CMOS output configuration



As shown in figure 2, when the voltage applied at the power supply ( $V_{DD}$ ) rises from below detect voltage to above release voltage, the IC commence release operations and the internal P-ch driver transistor will be on. The output current ( $I_{OUT}$ ) flows the input resistor ( $R_{IN}$ ) via the P-ch driver transistor. Because of the input resistor ( $R_{IN}$ ) and the output current ( $I_{OUT}$ ), an input pin voltage drops  $R_{IN} \times I_{OUT}$ . If the voltage drop level is larger than the IC's hysteresis width ( $V_{HYS}$ ), the input pin voltage will falls below the  $V_{DF}$  and detect operations will commence so that the internal P-ch driver transistor will be off. The voltage drop will stop because the output current ( $I_{OUT}$ ) which was flowing the P-ch driver transistor will run down. The input pin voltage will become the same voltage level as the input voltage ( $V_{IN}$ ). For this, the input pin voltage will rise above the release voltage ( $V_{DR}$ ), therefore, the release operations will begin over again. Oscillation may occur with this repetition. Further, this condition will also appear via means of a similar mechanism during detect operations.





[Figure 2: Oscillation caused by the input resistor of the CMOS output product and the output current]

## TYPICAL PERFORMANCE CHARACTERISTICS



### (1) Supply Current vs. Input Voltage



### (2) Output Voltage vs. Input Voltage





### (3) Detect Voltage, Release Voltage vs. Ambient Temperature







## ■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

### (4) Output Current (Nch Driver) vs. Input Voltage




### (5) Output Current (Pch Driver) vs. Input Voltage




## ■ PACKAGING INFORMATION

## ● USP-3

(unit : mm)




### ●USP-3 Reference Pattern Layout




## ●SSOT-24

(unit : mm)




### ●USP-3 Reference Metal Mask Design



## ■ MARKING RULE

### ●SSOT-24



**SSOT-24**  
(TOP VIEW)

① represents output configuration and detect voltage Range

| MARK | OUTPUT CONFIGURATION | OUTPUT VOLTAGE | PRODUCT SERIES |
|------|----------------------|----------------|----------------|
| K    | CMOS                 | 1.0V~2.9V      | XC6120C        |
| L    |                      | 3.0V~5.0V      |                |
| M    | Nch open drain       | 1.0V~2.9V      | XC6120N        |
| N    |                      | 3.0V~5.0V      |                |

② represents detect voltage

| MARK | DETECT VOLTAGE (V) |     | MARK | DETECT VOLTAGE (V) |     |
|------|--------------------|-----|------|--------------------|-----|
| 0    | -                  | 3.0 | F    | 1.5                | 4.5 |
| 1    | -                  | 3.1 | H    | 1.6                | 4.6 |
| 2    | -                  | 3.2 | K    | 1.7                | 4.7 |
| 3    | -                  | 3.3 | L    | 1.8                | 4.8 |
| 4    | -                  | 3.4 | M    | 1.9                | 4.9 |
| 5    | -                  | 3.5 | N    | 2.0                | 5.0 |
| 6    | -                  | 3.6 | P    | 2.1                | -   |
| 7    | -                  | 3.7 | R    | 2.2                | -   |
| 8    | -                  | 3.8 | S    | 2.3                | -   |
| 9    | -                  | 3.9 | T    | 2.4                | -   |
| A    | 1.0                | 4.0 | U    | 2.5                | -   |
| B    | 1.1                | 4.1 | V    | 2.6                | -   |
| C    | 1.2                | 4.2 | X    | 2.7                | -   |
| D    | 1.3                | 4.3 | Y    | 2.8                | -   |
| E    | 1.4                | 4.4 | Z    | 2.9                | -   |


③, ④ represents production lot number

01 to 09, 10, 11, ..., 99, 0A, ..., 0Z, 1A, ...repeated.

(G, I, J, O, Q, W excluded. Reversed character is not used.)

## ■ MARKING RULE (Continued)

### ● USP-3



① represents product series

| MARK | PRODUCT SERIES |
|------|----------------|
| 0    | XC6120*****    |

② standard : represents output configuration and integer number of detect voltage

#### ● CMOS Output (XC6120C Series)

| MARK | DETECT VOLTAGE (V) |
|------|--------------------|
| A    | 1.X                |
| B    | 2.X                |
| C    | 3.X                |
| D    | 4.X                |
| E    | 5.X                |

#### ● Nch open drain (XC6120N Series)

| MARK | DETECT VOLTAGE (V) |
|------|--------------------|
| F    | 1.X                |
| H    | 2.X                |
| K    | 3.X                |
| L    | 4.X                |
| M    | 5.X                |

③ standard : represents decimal point of detect voltage

| MARK | DETECT VOLTAGE (V) | PRODUCT SERIES |
|------|--------------------|----------------|
| 3    | X.3                | XC6120**3***   |
| 0    | X.0                | XC6120**0***   |

④, ⑤ represents production lot number

01 to 09, 10, 11, ..., 99, 0A, ..., 0Z, 1A, ...repeated.  
(G, I, J, O, Q, W excluded.)

1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this datasheet.
4. The products in this datasheet are not developed, designed, or approved for use with such equipment whose failure or malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.  
(e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this datasheet within the specified ranges.  
Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this datasheet may be copied or reproduced without the prior permission of TOREX SEMICONDUCTOR LTD.

**TOREX SEMICONDUCTOR LTD.**