

ANTENNA PRODUCTS

DATA SHEET

1.575 GHz Circular Polarized Pin Feed Ceramic GPS Antenna (25*25*4 mm)

2006 August. 28 Rev.1

25*25*4 mm Pin Feed Ceramic Antenna for GPS Application				CAN4313425031581B				— ▶	1	Aug.. 28, 06	
								— ▶	2	Nov, 06	
								— ▶	3		
BY / 製定者	Sunwiun.hu	SUPER / 原圖編號	C.T. Lee	TLL.SH / 共頁	8	PAGE/ 頁	1	SH nr.	— ▶	4	
CHECK				DATE / 日期		August. 28, 2006			— ▶	5	

**CERAMIC ANTENNA (CIRCULAR POLARIZATION PIN FEED TYPE)
FOR GLOBAL POSITIONING SYSTEMS (GPS) (1.575G Hz)**

Product Specification¹

QUICK REFERENCE DATA

Central Frequency	1.575 GHz*
Bandwidth	20 MHz min.**
Gain	3 dBic Max***
VSWR	2.0 max
Polarization	Right Hand Circular Polarization
Axial Ratio	3dB
Impedance	50Ω
Operating Temperature	-55~125 °C




* Central frequency will shift 5 MHz down when a non-metal cover is placed

** Return loss ≤ -10dB.

*** Based on 70 * 70 mm ground plane


MECHANICAL DATA (25 * 25 * 4 mm)




¹ All the technical data and information contained herein are subject to change without prior notice

25*25*4 mm Pin Feed Ceramic Antenna for GPS Application				CAN4313425031581B				1	Aug.. 28, 06
								2	Nov, 06
								3	
BY / 製 定 者	Sunwiun.hu	SUPER / 原圖編號	C.T. Lee	TLL.SH / 共 頁	8	PAGE/ 頁	2	SH nr.	4
CHECK				DATE / 日期	August. 28, 2006			5	

Directivity Chart (with 30*30 mm square Ground Plane)



f = 1575 MHz




25*25*4 mm Pin Feed
Ceramic Antenna
for GPS Application

CAN4313425031581B

—	1	Aug.. 28, 06
►	2	Nov, 06
—	3	
►	4	
—	5	
►		


BY / 製定者	Sunwiun.hu	SUPER / 原圖編號	C.T. Lee	TLL.SH / 共頁	8	PAGE/ 頁	3	SH nr.	
CHECK				DATE / 日期	August. 28, 2006				

Return Loss and Smith Chart (with 70 * 70 mm square Ground Plane)




No tape

25*25*4 mm Pin Feed Ceramic Antenna for GPS Application				CAN4313425031581B				— ▶	1	Aug.. 28, 06	
								— ▶	2	Nov, 06	
								— ▶	3		
BY / 製定者	Sunwiun.hu	SUPER / 原圖編號	C.T. Lee	TLL.SH / 共頁	8	PAGE/ 頁	4	SH nr.	— ▶	4	
CHECK				DATE / 日期		August. 28, 2006			— ▶	5	



With tape and Liner



With tape but without Liner

25*25*4 mm Pin Feed
Ceramic Antenna
for GPS Application

CAN4313425031581B

—	1	Aug.. 28, 06
▶	2	Nov, 06
—	3	
▶	4	
—	5	

BY / 製定者	Sunwiun.hu	SUPER / 原圖編號	C.T. Lee	TLL.SH / 共頁	8	PAGE / 頁	5	SH nr.	—	4	
CHECK				DATE / 日期	August. 28, 2006				—	5	

ORDERING INFORMATION: 12NC Ordering Code

The antennas may be ordered by using the Yageo ordering code. These code numbers can be determined by the following rules:

CAN 43 13 4 25 03 158 1B
F C M S T A P

F. Family Code

CAN 43 = Antenna

C. Packing Type Code

13 = bulk packing

M. Materials Code

4 = High Frequency Material

S. Size Code

25 = 25 * 25 mm

T. Type

03 = Pin Feed Type 3

A. Working Frequency


158 = 1.575GHz

Packing Type Code


1B = bulk packing

25*25*4 mm Pin Feed Ceramic Antenna for GPS Application				CAN4313425031581B				— ▶	1	Aug.. 28, 06	
								— ▶	2	Nov, 06	
								— ▶	3		
BY / 製 定 者	Sunwiun.hu	SUPER / 原 圖 編 號	C.T. Lee	TLL.SH / 共 頁	8	PAGE/ 頁	6	SH nr.	— ▶	4	
CHECK				DATE / 日 期		August. 28, 2006			— ▶	5	

Packing Information



Cover Tray



Bottom Tray

25*25*4 mm Pin Feed Ceramic Antenna for GPS Application				CAN4313425031581B				— ▶	1	Aug.. 28, 06	
								— ▶	2	Nov, 06	
								— ▶	3		
BY / 製定者	Sunwiun.hu	SUPER / 原圖編號	C.T. Lee	TLL.SH / 共頁	8	PAGE/ 頁	7	SH nr.	— ▶	4	
CHECK				DATE / 日期		August. 28, 2006			— ▶	5	

Revision Control:

Revision	Date	Content	Remark
	Aug. 28, 2006	New Issued	
	Nov, 2006	Modify the packing tray	

25*25*4 mm Pin Feed Ceramic Antenna for GPS Application				CAN4313425031581B				— ▶	1	Aug.. 28, 06	
								— ▶	2	Nov, 06	
								— ▶	3		
BY / 製定者	Sunwiun.hu	SUPER / 原圖編號	C.T. Lee	TLL.SH / 共頁	8	PAGE/ 頁	8	SH nr.	— ▶	4	
CHECK				DATE / 日期		August. 28, 2006			— ▶	5	