

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

creo

CreoParametri2.0

DO NOT REVISE
EXCEPT BY CAD

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	M	REVISED DESIGN ECO-14-005638	16APR2014	NCL	GOJ
	M1	REVISED DRAWING ECO-14-012763	16OCT2014	NCL	DAO
	M2	REV. BY ECO 14-019128	09JAN2015	HC	WLS

5,6

X

R0,50
TYP.

2

3

0,8

6,8

X

10,7

Y

4,60±0,15

8,6

10,2

3,45

Y

11,9

6,7

3,3

6,5

6,0

1

2

3

4

5

SECTION X-X

25,4

1,30

SECTION Y-Y

PERSPECTIVE VIEW
SCALE 3:1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN NCLAPRESA 18FEB2011
CHK JRGOLDSCHIMDT 18FEB2011
APVD MBGODOY 18FEB2011

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±0,2
1 PLC ±0,3
2 PLC ±
3 PLC ±
4 PLC ±
ANGLES ±30'
FINISH

MATERIAL
SEE TABLE
-

DWN NCLAPRESA 18FEB2011
CHK JRGOLDSCHIMDT 18FEB2011
APVD MBGODOY 18FEB2011

PRODUCT SPEC
-

APPLICATION SPEC
-

WEIGHT
-

Customer Drawing

TE Connectivity

NAME
-

HOUSING 2 POSN.,FASTIN-ON
.110 TAB

SIZE A200779
CAGE CODE C-626065
DRAWING NO
RESTRICTED TO
-

SCALE 5:1
SHEET 1 OF 1
REV M2

1471-9 (3/13)

- 1- MATERIA PRIMA CONFORME ESPECIF. IEC 60335-1
GWT 750° C, SEM CHAMAS.
- RAW MATERIAL ACC. TO SPEC 60335-1
GWT 750° C,WITHOUT FRAME.
- 2- CIRCUITO 1-SOMENTE PARA REFERENCIA.
- CIRCUIT 1- FOR REFERENCE ONLY.
- 3- CIRCUITO 2- SOMENTE PARA REFERENCIA.
- CIRCUIT 2- FOR REFERENCE ONLY.
- 4- NÚMERO DA CAVIDADE DO MOLDE.
- MOLD CAVITY NUMBER.
- 5- OBSOLETE PARTS: OBSELETE CIS STREAMLINING
PER D.RENAUD/D.SINISI

6-WORK BETTER WHEN USED WITH
TAB PN-881719 OR PN-880638.

NATURAL	PA6.6 V-0	1-626065 -2
NATURAL	PA6.6-ZYTEL 103 HSL	1-626065 -1
NATURAL	PBT V-0	1-626065 -0
ORANGE	POLIAMIDA 6.6	626065 -9
VIOLET	POLIAMIDA 6.6	626065 -8
GRAY	POLIAMIDA 6.6	626065 -7
BROWN	POLIAMIDA 6.6	626065 -6
BLACK	POLIAMIDA 6.6	626065 -5
YELLOW	POLIAMIDA 6.6	626065 -4
BLUE	POLIAMIDA 6.6	626065 -3
GREEN	POLIAMIDA 6.6	626065 -2
RED	POLIAMIDA 6.6	626065 -1
NATURAL	POLIAMIDA 6.6	626065 -0
FINISH	MATERIAL	PART NUMBER