



CYPRESS

PRELIMINARY

CY37128V


UltraLogic™ 3.3V 128-Macrocell ISR™ CLPD

Features

- 128 macrocells in eight logic blocks
- 3.3V In-System Reprogrammable™ (ISR™)
 - JTAG-compliant on-board programming
 - Design changes don't cause pinout changes
 - Design changes don't cause timing changes
- IEEE standard 3.3V operation
 - 3.3V ISR
 - 5V tolerant
- Up to 128 I/Os
 - plus 5 dedicated inputs including 4 clock inputs
- High speed
 - $f_{MAX} = 125 \text{ MHz}$

- $t_{PD} = 10 \text{ ns}$
- $t_S = 5.5 \text{ ns}$
- $t_{CO} = 6.5 \text{ ns}$
- Product-term clocking
- IEEE 1149.1 JTAG boundary scan
- Programmable slew rate control on individual I/Os
- Low power option on individual logic block basis
- User-Programmable Bus Hold capabilities on all I/Os
- Simple Timing Model
- PCI compliant^[1]
- 84–160 pins in TQFP, PLCC and CLCC packages
- Pinout compatible with the CY37128, CY37064/37064V, CY37192/37192V, CY37256/37256V

Logic Block Diagram (160-pin TQFP)



Selection Guide

	CY37128V-125	CY37128V-83
Maximum Propagation Delay, t_{PD} (ns)	10	15
Minimum Set-Up, t_S (ns)	5.5	8.0
Maximum Clock to Output, t_{CO} (ns)	6.5	8.0
Typical Supply Current, I_{CC} (mA) in Low Power Mode	30	30

Note:

1. Due to the 5V tolerant nature of the I/Os, the I/Os are not clamped to V_{CC} .

Functional Description

The CY37128V is an In-System Reprogrammable (ISR) Complex Programmable Logic Device (CPLD) and is part of the Ultra37000™ family of high-density, high-speed CPLDs. Like all members of the Ultra37000 family, the CY37128V is designed to bring the ease of use and high performance of the 22V10 to high-density PLDs.

# of Pins	# Buried Macrocells	# I/O Macrocells	Package Types
84	64	64	PLCC/CLCC
100	64	64	TQFP
160	0	128	TQFP

For a more detailed description of the architecture and features of the CY37128V see the Ultra37000 family data sheet.

Fully Routable with 100% Logic Utilization

The CY37128V is designed with a robust routing architecture which allows utilization of the entire device with a fixed pinout. This makes Ultra37000 optimal for implementing on board design changes using ISR without changing pinouts.

Simple Timing Model

The CY37128V features a very simple timing model with predictable delays. Unlike other high-density CPLD architectures, there are no hidden speed delays such as fanout effects, interconnect delays, or expander delays. The timing model allows for design changes with ISR without causing changes to system performance.

Low Power Operation

Each Logic Block of the CY37128V can be configured as either High-Speed (default) or Low-Power. In the Low-Power mode,

the logic block consumes approximately 50% less power and slows down by t_{LP} .

Output Slew Rate Control

Each output can be configured with either a fast edge rate (default) for high performance, or a slow edge rate for added noise reduction. In the fast edge rate mode, outputs switch at 3V/ns max. and in the slow edge rate mode, outputs switch at 1V/ns max. There is a nominal delay for I/Os using the slow edge rate mode.

In-System Reprogramming

The CY37128V can be programmed in system using IEEE 1149.1 compliant JTAG programming protocol. The CY37128V can also be programmed on a number of traditional parallel programmers including Cypress's *Impulse3™* programmer and industry standard third-party programmers. For an overview of ISR programming, refer to the Ultra37000 Family data sheet and for UltraISR cable and software specifications, refer to InSRkit: ISR Programming data sheet (CY3600i).

User-Programmable Bus Hold


All outputs of the CY37128V can either be configured into bus hold mode or left floating. When in bus hold mode, the undriven outputs retain their last value with a weak latch. This feature allows the designer the flexibility of either eliminating or including external pull-up/pull-down resistors. Enabling this feature affects all I/Os simultaneously.

Design Tools

Development software for the CY37128V is available from Cypress's *Warp™* or third-party bolt-in software packages as well as a number of third-party development packages. Please refer to the *Warp* or third-party tool support data sheets for further information.

Pin Configurations

160-pin TQFP
Top View




37256V-2

Pin Configurations (continued)

84-pin PLCC/CLCC

Top View






Pin Configurations (continued)

100-pin TQFP

Top View



Maximum Ratings

(Above which the useful life may be impaired. For user guidelines, not tested.)

Storage Temperature -65°C to +150°C

Ambient Temperature with

Power Applied -55°C to +125°C

Supply Voltage to Ground Potential -0.5V to +4.6V

DC Voltage Applied to Outputs

in High Z State.....-0.5V to +7.0V

DC Input Voltage-0.5V to +7.0V

DC Program Voltage..... 3.0 to 3.6V

Current into Outputs 8 mA

Static Discharge Voltage >2001V
(per MIL-STD-883, Method 3015)

Latch-Up Current..... >200 mA

Operating Range^[2]

Range	Ambient Temperature ^[2]	Junction Temperature	V _{CC}
Commercial	0°C to +70°C	0°C to +90°C	3.3V ± 0.3V
Industrial	–40°C to +85°C	–40°C to +125°C	3.3V ± 0.3V
Military ^[3]	–55°C to +125°C	–55°C to +130°C	3.3V ± 0.3V

Shaded areas contain advance information.

Electrical Characteristics Over the Operating Range

Parameter	Description	Test Conditions	Min.	Max.	Unit
V _{OH}	Output HIGH Voltage	V _{CC} = Min. I _{OH} = –4 mA (Com'l) ^[4] I _{OH} = –3 mA (Mil) ^[4]	2.4		V
V _{OL}	Output LOW Voltage	V _{CC} = Min. I _{OL} = 8 mA (Com'l) ^[4] I _{OL} = 6 mA (Mil) ^[4]		0.5	V
V _{IH}	Input HIGH Voltage	Guaranteed Input Logical HIGH voltage for all inputs ^[5]	2.0	V _{CCmax}	V
V _{IL}	Input LOW Voltage	Guaranteed Input Logical LOW voltage for all inputs ^[5]	–0.5	0.8	V
I _{IX}	Input Load Current	V _I = GND OR V _{CC}	–10	10	μA
I _{OZ}	Output Leakage Current	V _O = GND or V _{CC} , Output Disabled	–50	50	μA
I _{OS}	Output Short Circuit Current ^[6, 7]	V _{CC} = Max., V _{OUT} = 0.5V	–30	–160	mA
I _{BHL}	Input Bus Hold LOW Sustaining Current	V _{CC} = Min., V _{IL} = 0.8V	+75		μA
I _{BHH}	Input Bus Hold HIGH Sustaining Current	V _{CC} = Min., V _{IH} = 2.0V	–75		μA
I _{BHLO}	Input Bus Hold LOW Overdrive Current	V _{CC} = Max.		+500	μA
I _{BHHO}	Input Bus Hold HIGH Overdrive Current	V _{CC} = Max.		–500	μA

Inductance^[7]

Parameter	Description	Test Conditions	160-Pin TQFP	84-lead CLCC	84-lead PLCC	100-Pin TQFP	Unit
L	Maximum Pin Inductance	V _{IN} = 5.0V at f = 1 MHz	9	5	8	8	nH

Notes:

- Normal Programming Conditions apply across Ambient Temperature Range for specified programming methods. For more information on programming the Ultra37000 family devices see the Ultra37000 family data sheet.
- T_A is the "instant on" case temperature.
- I_{OH} = –2 mA, I_{OL} = 2 mA for TDO.
- These are absolute values with respect to device ground. All overshoots due to system or tester noise are included.
- Not more than one output should be tested at a time. Duration of the short circuit should not exceed 1 second. V_{OUT} = 0.5V has been chosen to avoid test problems caused by tester ground degradation.
- Tested initially and after any design or process changes that may affect these parameters.


Capacitance^[7]

Parameter	Description	Test Conditions	Max.	Unit
$C_{I/O}$	Input/Output Capacitance	$V_{IN} = 3.3V$ at $f = 1\text{ MHz}$ at $T_A = 25^\circ C$	8	pF
C_{CLK}	Clock Signal Capacitance	$V_{IN} = 3.3V$ at $f = 1\text{ MHz}$ at $T_A = 25^\circ C$	12	pF


Endurance Characteristics^[7]





Parameter	Description	Test Conditions	Min.	Typ.	Unit
N	Minimum Reprogramming Cycles	Normal Programming Conditions ^[2]	1,000	10,000	Cycles

AC Test Loads and Waveforms



Equivalent to: THÉVENIN EQUIVALENT



Parameter ^[8]	V_X	Output Waveform—Measurement Level
$t_{ER(-)}$	1.5V	 37128V-10
$t_{ER(+)}$	2.6V	 37128V-11
$t_{EA(+)}$	1.5V	 37128V-12
$t_{EA(-)}$	V_{the}	 37128V-13

(d) Test Waveforms

Note:

8. t_{ER} measured with 5-pF AC Test Load and t_{EA} measured with 35-pF AC Test Load.

Switching Characteristics Over the Operating Range^[9]

Parameter	Description	37128V-125		37128V-83		Unit
		Min.	Max.	Min.	Max.	
Combinatorial Mode Parameters						
t _{PD} ^[10, 11]	Input to Combinatorial Output		10		15	ns
t _{PDL} ^[10, 11]	Input to Output Through Transparent Input or Output Latch		13		18	ns
t _{PDLL} ^[10, 11]	Input to Output Through Transparent Input and Output Latches		15		19	ns
t _{EA} ^[10, 11]	Input to Output Enable		14		19	ns
t _{ER} ^[10]	Input to Output Disable		14		19	ns
Input Register Parameters						
t _{WL}	Clock or Latch Enable Input LOW Time ^[7]	3		4		ns
t _{WH}	Clock or Latch Enable Input HIGH Time ^[7]	3		4		ns
t _{IS}	Input Register or Latch Set-Up Time	2		3		ns
t _{IH}	Input Register or Latch Hold Time	2		3		ns
t _{ICO} ^[10, 11]	Input Register Clock or Latch Enable to Combinatorial Output		12.5		19	ns
t _{ICOL} ^[10, 11]	Input Register Clock or Latch Enable to Output Through Transparent Output Latch		16		21	ns
Synchronous Clocking Parameters						
t _{CO} ^[11]	Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) or Latch Enable to Output		6.5		8.0	ns
t _S ^[10]	Set-Up Time from Input to Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) or Latch Enable	5.5		8.0		ns
t _H	Register or Latch Data Hold Time	0		0		ns
t _{CO2} ^[10, 11]	Output Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) or Latch Enable to Combinatorial Output Delay (Through Logic Array)		14		19	ns
t _{SCS} ^[10]	Output Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) or Latch Enable to Output Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) or Latch Enable (Through Logic Array)	8.0		12		ns
t _{SL} ^[10]	Set-Up Time from Input Through Transparent Latch to Output Register Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) or Latch Enable	10		15		ns
t _{HL}	Hold Time for Input Through Transparent Latch from Output Register Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) or Latch Enable	0		0		ns
Product Term Clocking Parameters						
t _{COPT} ^[10, 11]	Product Term Clock or Latch Enable (PTCLK) to Output		13		15	ns
t _{SPT}	Set-Up Time from Input to Product Term Clock or Latch Enable (PTCLK)	3		4.5		ns
t _{HPT}	Register or Latch Data Hold Time	3		4.5		ns
t _{ISPT} ^[10]	Set-Up Time for Buried Register Used as an Input Register from Input to Product Term Clock or Latch Enable (PTCLK)		-2		-2	ns


Notes:

9. All AC parameters are measured with 16 outputs switching and 35-pF AC Test Load.
10. Logic Blocks operating in low-power mode, add t_{LP} to this spec.
11. Outputs using Slow Output Slew Rate, add t_{SLEW} to this spec.

Switching Characteristics Over the Operating Range^[9] (continued)

Parameter	Description	37128V-125		37128V-83		Unit
		Min.	Max.	Min.	Max.	
t_{IHPT}	Buried Register Used as an Input Register or Latch Data Hold Time		9		14	ns
$t_{CO2PT}^{[10, 11]}$	Product Term Clock or Latch Enable (PTCLK) to Output Delay (Through Logic Array)		19		24	ns
Pipelined Mode Parameters						
$t_{ICS}^{[10]}$	Input Register Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃) to Output Register Synchronous Clock (CLK ₀ , CLK ₁ , CLK ₂ , or CLK ₃)	8		12		ns
Operating Frequency Parameters						
f_{MAX1}	Maximum Frequency with Internal Feedback (Lesser of $1/t_{SCS}$, $1/(t_S + t_H)$, or $1/t_{CO}$) ^[7]	125		83		MHz
f_{MAX2}	Maximum Frequency Data Path in Output Registered/Latched Mode (Lesser of $1/(t_{WL} + t_{WH})$, $1/(t_S + t_H)$, or $1/t_{CO}$)	158		125		MHz
f_{MAX3}	Maximum Frequency with External Feedback (Lesser of $1/(t_{CO} + t_S)$ or $1/(t_{WL} + t_{WH})$)	83		67		MHz
f_{MAX4}	Maximum Frequency in Pipelined Mode (Lesser of $1/(t_{CO} + t_{IS})$, $1/t_{ICS}$, $1/(t_{WL} + t_{WH})$, $1/(t_{IS} + t_{IH})$, or $1/t_{SCS}$)	125		67		MHz
Reset/Preset Parameters						
t_{RW}	Asynchronous Reset Width ^[7]	10		15		ns
$t_{RR}^{[10]}$	Asynchronous Reset Recovery Time ^[7]	12		17		ns
$t_{RO}^{[10, 11]}$	Asynchronous Reset to Output		15		21	ns
t_{PW}	Asynchronous Preset Width ^[7]	10		15		ns
$t_{PR}^{[10]}$	Asynchronous Preset Recovery Time ^[7]	12		17		ns
$t_{PO}^{[10, 11]}$	Asynchronous Preset to Output		15		21	ns
User Option Parameters						
t_{LP}	Low Power Adder		4		4	ns
t_{SLEW}	Slow Output Slew Rate Adder		2		2	ns
JTAG Timing Parameters						
$t_{S JTAG}$	Set-Up Time from TDI and TMS to TCK	0		0		ns
$t_{H JTAG}$	Hold Time on TDI and TMS	20		20		ns
$t_{CO JTAG}$	Falling Edge of TCK to TDO		20		20	ns
f_{JTAG}	Maximum JTAG Tap Controller Frequency		20		20	MHz


Typical I_{CC} Characteristics



The typical pattern is a 16-bit up counter, per logic block, with outputs disabled.
 $V_{CC} = 3.3V$, $T_A = \text{Room Temperature}$


Switching Waveforms

Combinatorial Output




37128V-14

Registered Output with Synchronous Clocking



37128V-15


Registered Output with Product Term Clocking Input Going Through the Array




37128V-16

Switching Waveforms (continued)


Registered Output with Product Term Clocking Input Coming From Adjacent Buried Register



Latched Output




Registered Input




Switching Waveforms (continued)

Clock to Clock




37128V-20

Latched Input



37128V-21


Latched Input and Output



37128V-22


Switching Waveforms (continued)

Asynchronous Reset




37128V-23

Asynchronous Preset



37128V-24

Output Enable/Disable



37128V-25

Ordering Information

Speed (MHz)	Ordering Code	Package Name	Package Type	Operating Range
125	CY37128VP160-125AC	A160	160-Pin Thin Quad Flatpack	Commercial
	CY37128VP100-125AC	A100	100-Pin Thin Quad Flatpack	
	CY37128VP84-125JC	J83	84-Pin Plastic Leaded Chip Carrier	
83	CY37128VP160-83AC	A160	160-Pin Thin Quad Flatpack	Commercial
	CY37128VP100-83AC	A100	100-Pin Thin Quad Flatpack	
	CY37128VP84-83JC	J83	84-Pin Plastic Leaded Chip Carrier	
	CY37128VP160-83AI	A160	160-Pin Thin Quad Flatpack	Industrial
	CY37128VP100-83AI	A100	100-Pin Thin Quad Flatpack	
	CY37128VP84-83JI	J83	84-Pin Plastic Leaded Chip Carrier	
	CY37128VP84-83YMB	Y84	84-Pin Ceramic Leaded Chip Carrier	Military


In-System Reprogramming, ISR, UltraLogic, Ultra37000, InSRkit, *Warp*, and *Impulse3* are trademarks of Cypress Semiconductor Corporation.

Warp2 and *Warp3* are registered trademarks of Cypress Semiconductor Corporation.

Document #: 38-00621-C

Package Diagrams


100-Pin Thin Plastic Quad Flat Pack (TQFP) A100



Package Diagrams (continued)


160-Pin Thin Plastic Quad Flat Pack (TQFP) A160

DIMENSIONS ARE IN MILLIMETERS.



84-Lead Plastic Leaded Chip Carrier J83

DIMENSIONS IN INCHES MIN. MAX.



51-85006-A

Package Diagrams (continued)

84-Pin Ceramic Leaded Chip Carrier Y84

