

## 74ALVCH162373

### Low Voltage 16-Bit Transparent Latch with Bushold and 26Ω Series Resistors in Outputs

#### General Description

The ALVCH162373 contains sixteen non-inverting latches with 3-STATE outputs and is intended for bus oriented applications. The device is byte controlled. The flip-flops appear to be transparent to the data when the Latch enable (LE) is HIGH. When LE is LOW, the data that meets the setup time is latched. Data appears on the bus when the Output Enable (OE) is LOW. When OE is HIGH, the outputs are in a high impedance state.

The ALVCH162373 data inputs include active bushold circuitry, eliminating the need for external pull-up resistors to hold unused or floating data inputs at a valid logic level.

The ALVCH162373 is also designed with 26Ω series resistors in the outputs. This design reduces line noise in applications such as memory address driver, clock drivers and bus transceivers/transmitters.

The 74ALVCH162373 is designed for low voltage (1.65V to 3.6V)  $V_{CC}$  applications with output compatibility up to 3.6V.

The 74ALVCH162373 is fabricated with an advanced CMOS technology to achieve high speed operation while maintaining low CMOS power dissipation.

#### Features


- 1.65V to 3.6V  $V_{CC}$  supply operation
- 3.6V tolerant control inputs and outputs
- Bushold on data inputs eliminates the need for external pull-up/pull-down resistors
- 26Ω series resistors in outputs
- $t_{PD}$  ( $I_n$  to  $O_n$ )
  - 3.8 ns max for 3.0V to 3.6V  $V_{CC}$
  - 5.0 ns max for 2.3V to 2.7V  $V_{CC}$
  - 9.0 ns max for 1.65V to 1.95V  $V_{CC}$
- Uses patented noise/EMI reduction circuitry
- Latchup conforms to JEDEC JED78
- ESD performance:
  - Human body model > 2000V
  - Machine model > 200V

#### Ordering Code:

| Ordering Number | Package Number | Package Description                                                         |
|-----------------|----------------|-----------------------------------------------------------------------------|
| 74ALVCH162373T  | MTD48          | 48-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.


#### Logic Symbol



#### Pin Descriptions

| Pin Names         | Description                      |
|-------------------|----------------------------------|
| $\overline{OE}_n$ | Output Enable Input (Active LOW) |
| $LE_n$            | Latch Enable Input               |
| $I_0$ – $I_{15}$  | Bushold Inputs                   |
| $O_0$ – $O_{15}$  | Outputs                          |

### Connection Diagram



## Truth Tables

| Inputs |                   |           | Outputs   |
|--------|-------------------|-----------|-----------|
| $LE_1$ | $\overline{OE}_1$ | $I_0-I_7$ | $O_0-O_7$ |
| X      | H                 | X         | Z         |
| H      | L                 | L         | L         |
| H      | L                 | H         | H         |
| L      | L                 | X         | $O_0$     |

| Inputs          |                          |                                 | Outputs                         |
|-----------------|--------------------------|---------------------------------|---------------------------------|
| LE <sub>2</sub> | $\overline{\text{OE}}_2$ | I <sub>8</sub> –I <sub>15</sub> | O <sub>8</sub> –O <sub>15</sub> |
| X               | H                        | X                               | Z                               |
| H               | L                        | L                               | L                               |
| H               | L                        | H                               | H                               |
| L               | L                        | X                               | O <sub>0</sub>                  |


H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial (HIGH or LOW, control inputs may not float)  
Z = High Impedance  
O<sub>n</sub> = Previous O<sub>n</sub> before HIGH-to-LOW of Latch Enable

## Functional Description

The 74ALVCH162373 contains sixteen edge D-type latches with 3-STATE outputs. The device is byte controlled with each byte functioning identically, but independent of the other. Control pins can be shorted together to obtain full 16-bit operation. The following description applies to each byte. When the Latch Enable ( $LE_n$ ) input is HIGH, data on the  $I_n$  enters the latches. In this condition the latches are transparent, i.e., a latch output will change state each time

its I input changes. When  $LE_n$  is LOW, the latches store information that was present on the I inputs a setup time preceding the HIGH-to-LOW transition on  $LE_n$ . The 3-STATE outputs are controlled by the Output Enable ( $\overline{OE_n}$ ) input. When  $\overline{OE_n}$  is LOW the standard outputs are in the 2-state mode. When  $\overline{OE_n}$  is HIGH, the standard outputs are in the high impedance mode but this does not interfere with entering new data into the latches.

## Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

**Absolute Maximum Ratings**(Note 1)

|                                                              |                          |
|--------------------------------------------------------------|--------------------------|
| Supply Voltage ( $V_{CC}$ )                                  | -0.5V to +4.6V           |
| DC Input Voltage ( $V_I$ )                                   | -0.5V to 4.6V            |
| Output Voltage ( $V_O$ ) (Note 2)                            | -0.5V to $V_{CC} + 0.5V$ |
| DC Input Diode Current ( $I_{IK}$ )                          |                          |
| $V_I < 0V$                                                   | -50 mA                   |
| DC Output Diode Current ( $I_{OK}$ )                         |                          |
| $V_O < 0V$                                                   | -50 mA                   |
| DC Output Source/Sink Current ( $I_{OH}/I_{OL}$ )            | ±50 mA                   |
| DC $V_{CC}$ or GND Current per Supply Pin ( $I_{CC}$ or GND) | ±100 mA                  |
| Storage Temperature Range ( $T_{STG}$ )                      | -65°C to +150°C          |

**Recommended Operating Conditions** (Note 3)

|                                                 |                |
|-------------------------------------------------|----------------|
| Power Supply                                    |                |
| Operating                                       | 1.65V to 3.6V  |
| Input Voltage ( $V_I$ )                         | 0V to $V_{CC}$ |
| Output Voltage ( $V_O$ )                        | 0V to $V_{CC}$ |
| Free Air Operating Temperature ( $T_A$ )        | -40°C to +85°C |
| Minimum Input Edge Rate ( $\Delta t/\Delta V$ ) |                |
| $V_{IN} = 0.8V$ to $2.0V$ , $V_{CC} = 3.0V$     | 10 ns/V        |

**Note 1:** The Absolute Maximum Ratings are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the Absolute Maximum Ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

**Note 2:**  $I_O$  Absolute Maximum Rating must be observed, limited to 4.6V.

**Note 3:** Floating or unused control inputs must be held HIGH or LOW.

**DC Electrical Characteristics**

| Symbol          | Parameter                                | Conditions                       | $V_{CC}$<br>(V)                       | Min                                | Max                                | Units   |
|-----------------|------------------------------------------|----------------------------------|---------------------------------------|------------------------------------|------------------------------------|---------|
| $V_{IH}$        | HIGH Level Input Voltage                 |                                  | 1.65 - 1.95<br>2.3 - 2.7<br>2.7 - 3.6 | $0.65 \times V_{CC}$<br>1.7<br>2.0 |                                    | V       |
| $V_{IL}$        | LOW Level Input Voltage                  |                                  | 1.65 - 1.95<br>2.3 - 2.7<br>2.7 - 3.6 |                                    | $0.35 \times V_{CC}$<br>0.7<br>0.8 | V       |
| $V_{OH}$        | HIGH Level Output Voltage                | $I_{OH} = -100 \mu A$            | 1.65 - 3.6                            | $V_{CC} - 0.2$                     |                                    | V       |
|                 |                                          | $I_{OH} = -2 \text{ mA}$         | 1.65                                  | 1.2                                |                                    |         |
|                 |                                          | $I_{OH} = -4 \text{ mA}$         | 2.3                                   | 1.9                                |                                    |         |
|                 |                                          | $I_{OH} = -6 \text{ mA}$         | 2.3                                   | 1.7                                |                                    |         |
|                 |                                          |                                  | 3.0                                   | 2.4                                |                                    |         |
|                 |                                          | $I_{OH} = -8 \text{ mA}$         | 2.7                                   | 2                                  |                                    |         |
| $V_{OL}$        | LOW Level Output Voltage                 | $I_{OL} = 100 \mu A$             | 1.65 - 3.6                            |                                    | 0.2                                | V       |
|                 |                                          | $I_{OL} = 2 \text{ mA}$          | 1.65                                  |                                    | 0.45                               |         |
|                 |                                          | $I_{OL} = 4 \text{ mA}$          | 2.3                                   |                                    | 0.4                                |         |
|                 |                                          | $I_{OL} = 6 \text{ mA}$          | 2.3                                   |                                    | 0.55                               |         |
|                 |                                          |                                  | 3.0                                   |                                    | 0.55                               |         |
|                 |                                          | $I_{OL} = 8 \text{ mA}$          | 2.7                                   |                                    | 0.6                                |         |
| $I_I$           | Input Leakage Current                    | $0 \leq V_I \leq 3.6V$           | 3.6                                   |                                    | ±5.0                               | $\mu A$ |
|                 |                                          |                                  |                                       |                                    |                                    |         |
| $I_{I(HOLD)}$   | Bushold Input Minimum Drive Hold Current | $V_{IN} = 0.58V$                 | 1.65                                  | 25                                 |                                    | $\mu A$ |
|                 |                                          | $V_{IN} = 1.07V$                 | 1.65                                  | -25                                |                                    |         |
|                 |                                          | $V_{IN} = 0.7V$                  | 2.3                                   | 45                                 |                                    |         |
|                 |                                          | $V_{IN} = 1.7V$                  | 2.3                                   | -45                                |                                    |         |
|                 |                                          | $V_{IN} = 0.8V$                  | 3.0                                   | 75                                 |                                    |         |
|                 |                                          | $V_{IN} = 2.0V$                  | 3.0                                   | -75                                |                                    |         |
| $I_{OZ}$        | 3-STATE Output Leakage                   | $0 \leq V_O \leq 3.6V$           | 3.6                                   |                                    | ±10                                | $\mu A$ |
| $I_{CC}$        | Quiescent Supply Current                 | $V_I = V_{CC}$ or GND, $I_O = 0$ | 3.6                                   |                                    | 40                                 | $\mu A$ |
| $\Delta I_{CC}$ | Increase in $I_{CC}$ per Input           | $V_{IH} = V_{CC} - 0.6V$         | 3 - 3.6                               |                                    | 750                                | $\mu A$ |

## AC Electrical Characteristics

| Symbol                              | Parameter                       | T <sub>A</sub> = -40°C to +85°C, R <sub>L</sub> = 500Ω |     |                        |     |                               |     |                                |     | Units |
|-------------------------------------|---------------------------------|--------------------------------------------------------|-----|------------------------|-----|-------------------------------|-----|--------------------------------|-----|-------|
|                                     |                                 | C <sub>L</sub> = 50 pF                                 |     |                        |     | C <sub>L</sub> = 30 pF        |     |                                |     |       |
|                                     |                                 | V <sub>CC</sub> = 3.3V ± 0.3V                          |     | V <sub>CC</sub> = 2.7V |     | V <sub>CC</sub> = 2.5V ± 0.2V |     | V <sub>CC</sub> = 1.8V ± 0.15V |     |       |
|                                     |                                 | Min                                                    | Max | Min                    | Max | Min                           | Max | Min                            | Max |       |
| t <sub>PHL</sub> , t <sub>PLH</sub> | Propagation Delay<br>Bus to Bus | 1.3                                                    | 3.8 | 1.5                    | 5.0 | 1.0                           | 4.5 | 1.5                            | 9.0 | ns    |
| t <sub>PHL</sub> , t <sub>PLH</sub> | Propagation Delay<br>LE to Bus  | 1.3                                                    | 4.1 | 1.5                    | 5.4 | 1.0                           | 4.9 | 1.5                            | 9.8 | ns    |
| t <sub>PZL</sub> , t <sub>PZH</sub> | Output Enable Time              | 1.3                                                    | 4.4 | 1.5                    | 5.9 | 1.0                           | 5.4 | 1.5                            | 9.8 | ns    |
| t <sub>PLZ</sub> , t <sub>PHZ</sub> | Output Disable Time             | 1.3                                                    | 4.5 | 1.5                    | 4.9 | 1.0                           | 4.4 | 1.5                            | 7.9 | ns    |
| t <sub>W</sub>                      | Pulse Width                     | 1.5                                                    |     | 1.5                    |     | 1.5                           |     | 4.0                            |     | ns    |
| t <sub>S</sub>                      | Setup Time                      | 1.5                                                    |     | 1.5                    |     | 1.5                           |     | 2.5                            |     | ns    |
| t <sub>H</sub>                      | Hold Time                       | 1.0                                                    |     | 1.0                    |     | 1.0                           |     | 1.0                            |     | ns    |

## Capacitance

| Symbol    | Parameter                     | Conditions                                                 | $T_A = +25^{\circ}\text{C}$ |         | Units |
|-----------|-------------------------------|------------------------------------------------------------|-----------------------------|---------|-------|
|           |                               |                                                            | $V_{CC}$                    | Typical |       |
| $C_{IN}$  | Input Capacitance             | $V_I = 0\text{V or } V_{CC}$                               | 3.3                         | 6       | pF    |
| $C_{OUT}$ | Output Capacitance            | $V_I = 0\text{V or } V_{CC}$                               | 3.3                         | 7       | pF    |
| $C_{PD}$  | Power Dissipation Capacitance | Outputs Enabled<br>$f = 10\text{ MHz}, C_L = 50\text{ pF}$ | 3.3                         | 20      | pF    |
|           |                               |                                                            | 2.5                         | 20      |       |

## AC Loading and Waveforms




FIGURE 1. AC Test Circuit

TABLE 1. Values for Figure 1

| TEST                  | SWITCH |
|-----------------------|--------|
| $t_{PLH}$ , $t_{PHL}$ | Open   |
| $t_{PZL}$ , $t_{PLZ}$ | $V_L$  |
| $t_{PZH}$ , $t_{PHZ}$ | GND    |

TABLE 2. Variable Matrix  
(Input Characteristics:  $f = 1\text{MHz}$ ;  $t_r = t_f = 2\text{ns}$ ;  $Z_0 = 50\Omega$ )

| Symbol   | $V_{CC}$                      |                        |                               |                                |
|----------|-------------------------------|------------------------|-------------------------------|--------------------------------|
|          | $3.3\text{V} \pm 0.3\text{V}$ | $2.7\text{V}$          | $2.5\text{V} \pm 0.2\text{V}$ | $1.8\text{V} \pm 0.15\text{V}$ |
| $V_{mi}$ | $1.5\text{V}$                 | $1.5\text{V}$          | $V_{CC}/2$                    | $V_{CC}/2$                     |
| $V_{mo}$ | $1.5\text{V}$                 | $1.5\text{V}$          | $V_{CC}/2$                    | $V_{CC}/2$                     |
| $V_X$    | $V_{OL} + 0.3\text{V}$        | $V_{OL} + 0.3\text{V}$ | $V_{OL} + 0.15\text{V}$       | $V_{OL} + 0.15\text{V}$        |
| $V_Y$    | $V_{OH} - 0.3\text{V}$        | $V_{OH} - 0.3\text{V}$ | $V_{OH} - 0.15\text{V}$       | $V_{OH} - 0.15\text{V}$        |
| $V_L$    | $6\text{V}$                   | $6\text{V}$            | $V_{CC} \times 2$             | $V_{CC} \times 2$              |




FIGURE 2. Waveform for Inverting and Non-Inverting Functions




FIGURE 3. 3-STATE Output HIGH Enable and Disable Times for Low Voltage Logic




FIGURE 4. 3-STATE Output LOW Enable and Disable Times for Low Voltage Logic




FIGURE 5. Propagation Delay, Pulse Width and  $t_{REC}$  Waveforms





FIGURE 6. Setup Time, Hold Time and Recovery Time for Low Voltage Logic

## Physical Dimensions inches (millimeters) unless otherwise noted



Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
- A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)