

PM

Extremely Low Impedance, High Reliability

series

- High reliability withstanding 5000 hour load life at +105°C (3000/2000 hours for smaller case sizes as specified below).
- Capacitance ranges available based on the numerical values in E12 series under JIS.
- Compliant to the RoHS directive (2011/65/EU).




Low Impedance Long Life

Anti-Solvent
Feature
(Through 100V only)

PM




PW



■ Specifications

Item	Performance Characteristics											
Category Temperature Range	-55 to +105°C (6.3 to 100V), -40 to +105°C (160 to 400V), -25 to +105°C (450V)											
Rated Voltage Range	6.3 to 450V											
Rated Capacitance Range	0.47 to 15000μF											
Capacitance Tolerance	±20% at 120Hz, 20°C											
Leakage Current	Rated Voltage (V)	6.3 to 100					160 to 450					
	Leakage current	After 1 minute's application of rated voltage, leakage current is not more than 0.03CV or 4 (μA), whichever is greater.					CV ≤ 1000 : I = 0.1CV+40 (μA) max. (1 minute's) CV > 1000 : I = 0.04CV+100 (μA) max. (1 minute's)					
Tangent of loss angle (tan δ)	For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF. Measurement frequency : 120Hz at 20°C											
	Rated Voltage (V)	6.3	10	16	25	35	50	63 to 100	160 to 350	400 · 450		
	tan δ (MAX.)	0.22	0.19	0.16	0.14	0.12	0.10	0.08	0.20	0.25		
Stability at Low Temperature	Rated voltage (V)		6.3 · 10	16	25 · 35	50 to 100	160 · 200	250	315 · 350	400	450	120Hz
	Impedance ratio (MAX.)	Z-25°C / Z+20°C	—	—	—	—	—	—	—	—	15	
		Z-40°C / Z+20°C	—	—	—	—	4	6	8	10	—	
		Z-55°C / Z+20°C	4	3	3	2	—	—	—	—	—	
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after D.C. bias plus rated ripple current is applied for 5000 hours (2000 hours for φD=5 and 6.3, 3000 hours for φD=8) at 105°C, the peak voltage shall not exceed the rated voltage.						Capacitance change	Within ±20% of the initial capacitance value				
							tan δ	200% or less than the initial specified value				
							Leakage current	Less than or equal to the initial specified value				
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the characteristic requirements listed at right.						Capacitance change	Within ±20% of the initial capacitance value				
							tan δ	150% or less than the initial specified value				
							Leakage current	Less than or equal to the initial specified value				
Marking	Printed with white color letter on dark brown sleeve.											

■ Radial Lead Type



α	(φD < 10)	1.5
	(φD ≥ 10)	2.0

φD	5	6.3	8	10	12.5	16	18
P	2.0	2.5	3.5	5.0	5.0	7.5	7.5
φd	0.5	0.5	0.6	0.6	0.6*	0.8	0.8

※ In case L > 25 for the φ12.5 dia. unit, lead dia. φd = 0.8mm.

- Please refer to page 20 about the end seal configuration.

Type numbering system (Example : 25V 470µF)

1 2 3 4 5 6 7 8 9 10 11 12
U P M 1 E 4 7 1 M P D

Configuration ※
Capacitance tolerance (±20%)
Rated capacitance (470µF)
Rated voltage (25V)
Series name
Type


Size code

Type	Code
Small Dia	—
Low Profile	6

※ Configuration

φ D	Pb-free leadwire Pb-free PET sleeve
5	DD
6.3	ED
8 · 10	PD
12.5 to 18	HD

● Frequency coefficient of rated ripple current



Please refer to page 20, 21, 22 about the formed or taped product spec.
Please refer to page 4 for the minimum order quantity.

- Dimension table in next page.

■ Dimensions

φD×L (mm)

Cap.(μF)	Code	V(Code) Size code		6.3 (0J)		10 (1A)		16 (1C)		25 (1E)		35 (1V)	
		—	6	—	6	—	6	—	6	—	6	—	6
22	220											5×11	
27	270											5×11	
33	330									5×11		6.3×11	
39	390									5×11		6.3×11	
47	470							5×11		6.3×11		6.3×11	
56	560							5×11		6.3×11		6.3×11	
68	680				5×11			6.3×11		6.3×11		6.3×15	
82	820				5×11			6.3×11		6.3×11		6.3×15	
100	101	5×11			6.3×11			6.3×11		6.3×15		8×11.5	
120	121	5×11			6.3×11			6.3×11		6.3×15		8×15	10×12.5
150	151	6.3×11			6.3×11			6.3×15		8×11.5		8×15	10×12.5
180	181	6.3×11			6.3×11			6.3×15		8×15	10×12.5	8×20	10×15
220	221	6.3×11			6.3×15			8×11.5		8×15	10×12.5	8×20	10×15
270	271	6.3×15			6.3×15			8×15	10×12.5	8×20	10×15	10×20	12.5×15
330	331	6.3×15			8×11.5			8×15	10×12.5	8×20	10×15	10×20	12.5×15
390	391	8×11.5			8×15	10×12.5		8×20	10×15	10×20	12.5×15	10×25	12.5×15
470	471	8×15	10×12.5		8×15	10×12.5		8×20	10×15	10×20	12.5×15	10×31.5	16×15
560	561	8×15	10×12.5		8×20	10×15		10×20	12.5×15	10×25	12.5×15	12.5×20	16×15
680	681	8×20	10×15		8×20	10×15		10×20	12.5×15	10×31.5	16×15	12.5×25	18×15
820	821	8×20	10×15		10×20	12.5×15		10×25	12.5×15	12.5×20	16×15	12.5×25	18×15
1000	102	10×20	12.5×15		10×20	12.5×15		10×31.5	16×15	12.5×25	18×15	12.5×31.5	16×20
1200	122	10×20	12.5×15		10×25	12.5×15		12.5×20	16×15	12.5×25	18×15	12.5×35.5	16×25
1500	152	10×25	12.5×15		10×31.5	16×15		12.5×25	18×15	12.5×31.5	16×20	12.5×40	18×20
1800	182	10×31.5	16×15		12.5×20	16×15		12.5×31.5	16×20	12.5×35.5	16×25	16×31.5	18×25
2200	222	10×31.5	16×15		12.5×25	18×15		12.5×31.5	16×20	12.5×40	18×20	16×35.5	18×31.5
2700	272	12.5×25	18×15		12.5×31.5	16×20		12.5×35.5	16×25	16×31.5	18×25	16×40	18×35.5
3300	332	12.5×25	18×15		12.5×35.5	16×20		12.5×40	18×20	16×35.5	18×31.5	18×40	
3900	392	12.5×31.5	16×20		12.5×40	18×20		16×31.5	18×25	16×40	18×35.5		
4700	472	12.5×35.5	18×20		16×31.5	18×25		16×35.5	18×31.5	18×40			
5600	562	12.5×40	18×20		16×35.5	18×25		16×40	18×35.5				
6800	682	16×31.5	18×25		16×35.5	18×31.5		18×35.5					
8200	822	16×35.5	18×31.5		16×40	18×35.5		18×40					
10000	103	16×40	18×31.5		18×40								
12000	123	18×35.5											
15000	153	18×40											

Cap.(μF)	Code	V(Code) Size code		50 (1H)		63 (1J)		80 (1K)		100 (2A)	
		—	6	—	6	—	6	—	6	—	6
0.47	R47	5×11								5×11	
0.68	R68	5×11								5×11	
1	010	5×11								5×11	
1.5	1R5	5×11								5×11	
2.2	2R2	5×11								5×11	
3.3	3R3	5×11								5×11	
4.7	4R7	5×11								5×11	
6.8	6R8	5×11						5×11		6.3×11	
10	100	5×11			5×11			6.3×11		6.3×11	
12	120	5×11			5×11			6.3×11		6.3×11	
15	150	5×11			6.3×11			6.3×11		6.3×15	
18	180	5×11			6.3×11			6.3×11		6.3×15	
22	220	6.3×11			6.3×11			6.3×15		8×11.5	
27	270	6.3×11			6.3×11			6.3×15		8×15	10×12.5
33	330	6.3×11			6.3×15			8×11.5		8×15	10×12.5
39	390	6.3×11			6.3×15			8×15	10×12.5	8×20	10×15
47	470	6.3×15			8×11.5			8×15	10×12.5	10×20	12.5×15
56	560	6.3×15			8×15	10×12.5		8×20	10×15	10×20	12.5×15
68	680	8×11.5			8×15	10×12.5		10×20	12.5×15	10×25	12.5×15
82	820	8×15	10×12.5		8×20	10×15		10×20	12.5×15	10×31.5	16×15
100	101	8×20	10×15		10×20	12.5×15		10×25	12.5×15	10×31.5	16×15
120	121	8×20	10×15		10×20	12.5×15		10×31.5	16×15	12.5×25	16×15
150	151	10×20	12.5×15		10×25	12.5×15		10×31.5	16×15	12.5×25	18×15
180	181	10×20	12.5×15		10×31.5	16×15		12.5×25	16×15	12.5×31.5	16×20
220	221	10×25	12.5×15		12.5×20	16×15		12.5×31.5	18×15	12.5×35.5	16×25
270	271	10×31.5	16×15		12.5×25	18×15		12.5×31.5	16×20	12.5×40	18×20
330	331	10×31.5	16×15		12.5×25	18×15		12.5×35.5	16×25	16×31.5	18×25
390	391	12.5×25	16×15		12.5×31.5	16×20		12.5×40	18×20	16×35.5	18×31.5
470	471	12.5×25	18×15		12.5×35.5	16×25		16×31.5	18×25	16×40	18×35.5
560	561	12.5×31.5	16×20		12.5×40	18×20		16×35.5	18×31.5	18×35.5	
680	681	12.5×35.5	16×20		16×31.5	18×25		16×40	18×31.5	18×40	
820	821	12.5×40	18×20		16×35.5	18×31.5		18×35.5			
1000	102	16×31.5	18×25		16×40	18×35.5		18×40			
1200	122	16×35.5	18×31.5		18×40						
1500	152	16×40	18×31.5								
1800	182	18×35.5									
2200	222	18×40									

※In case of low profile type, [6] will be put at 12th digit of type numbering system.

Dimension table for 160 to 450V products are shown in 208 page.

■ Standard Ratings

V(Code) Size Code Item Code Cap.(μF)		16 (1C)									
		—					6				
		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
			20°C / 100kHz	−10°C / 100kHz	105°C / $\frac{10\text{kHz}}{200\text{kHz}}$	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / $\frac{10\text{kHz}}{200\text{kHz}}$	105°C / 120Hz
47	470	5 × 11	0.80	1.60	155	92					
56	560	5 × 11	0.65	1.30	175	105					
68	680	6.3 × 11	0.50	1.00	220	135					
82	820	6.3 × 11	0.42	0.84	240	155					
100	101	6.3 × 11	0.35	0.70	265	175					
120	121	6.3 × 11	0.29	0.58	290	195					
150	151	6.3 × 15	0.23	0.46	375	260					
180	181	6.3 × 15	0.20	0.40	405	285					
220	221	8 × 11.5	0.16	0.32	460	335					
270	271	8 × 15	0.14	0.28	550	410	10 × 12.5	0.14	0.28	635	430
330	331	8 × 15	0.12	0.24	595	455	10 × 12.5	0.12	0.24	670	480
390	391	8 × 20	0.10	0.20	730	570	10 × 15	0.10	0.20	730	570
470	471	8 × 20	0.090	0.18	770	615	10 × 15	0.090	0.18	825	615
560	561	10 × 20	0.075	0.15	950	770	12.5 × 15	0.080	0.16	920	745
680	681	10 × 20	0.065	0.13	1060	845	12.5 × 15	0.070	0.14	985	815
820	821	10 × 25	0.055	0.11	1260	1030	12.5 × 15	0.060	0.12	1060	895
1000	102	10 × 31.5	0.047	0.094	1410	1210	16 × 15	0.055	0.11	1270	1090
1200	122	12.5 × 20	0.041	0.082	1430	1250	16 × 15	0.046	0.092	1390	1220
1500	152	12.5 × 25	0.036	0.072	1700	1490	18 × 15	0.041	0.082	1560	1400
1800	182	12.5 × 31.5	0.032	0.064	1880	1690	16 × 20	0.037	0.074	1700	1530
2200	222	12.5 × 31.5	0.028	0.056	2010	1800	16 × 20	0.033	0.066	1800	1620
2700	272	12.5 × 35.5	0.025	0.050	2230	1990	16 × 25	0.030	0.060	2190	1800
3300	332	12.5 × 40	0.023	0.046	2460	2160	18 × 20	0.027	0.054	2090	1880
3900	392	16 × 31.5	0.022	0.044	2510	2220	18 × 25	0.025	0.050	2350	2060
4700	472	16 × 35.5	0.020	0.040	2770	2410	18 × 31.5	0.023	0.046	2720	2240
5600	562	16 × 40	0.019	0.038	3110	2530	18 × 35.5	0.022	0.044	2620	2350
6800	682	18 × 35.5	0.018	0.036	3050	2610					
8200	822	18 × 40	0.017	0.034	3300	2730					

V(Code) Size Code Item Code Cap.(μF)		25 (1E)									
		—					6				
		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
			20°C / 100kHz	−10°C / 100kHz	105°C / $\frac{10\text{kHz}}{200\text{kHz}}$	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / $\frac{10\text{kHz}}{200\text{kHz}}$	105°C / 120Hz
33	330	5 × 11	0.80	1.60	155	88					
39	390	5 × 11	0.65	1.30	175	100					
47	470	6.3 × 11	0.55	1.10	210	125					
56	560	6.3 × 11	0.44	0.88	235	140					
68	680	6.3 × 11	0.36	0.72	260	160					
82	820	6.3 × 11	0.30	0.60	285	180					
100	101	6.3 × 15	0.24	0.48	370	245					
120	121	6.3 × 15	0.20	0.40	405	275					
150	151	8 × 11.5	0.16	0.32	460	320					
180	181	8 × 15	0.14	0.28	550	390	10 × 12.5	0.15	0.30	635	395
220	221	8 × 15	0.11	0.22	625	455	10 × 12.5	0.13	0.26	670	435
270	271	8 × 20	0.095	0.19	750	560	10 × 15	0.11	0.22	700	525
330	331	8 × 20	0.085	0.17	795	610	10 × 15	0.095	0.19	825	575
390	391	10 × 20	0.070	0.14	985	770	12.5 × 15	0.080	0.16	920	720
470	471	10 × 20	0.065	0.13	1060	810	12.5 × 15	0.070	0.14	985	785
560	561	10 × 25	0.055	0.11	1260	990	12.5 × 15	0.060	0.12	1060	860
680	681	10 × 31.5	0.046	0.092	1420	1180	16 × 15	0.055	0.11	1270	1050
820	821	12.5 × 20	0.041	0.082	1440	1210	16 × 15	0.049	0.098	1340	1130
1000	102	12.5 × 25	0.036	0.072	1700	1430	18 × 15	0.043	0.086	1520	1310
1200	122	12.5 × 25	0.032	0.064	1760	1550	18 × 15	0.039	0.078	1600	1400
1500	152	12.5 × 31.5	0.029	0.058	1980	1780	16 × 20	0.034	0.068	1770	1590
1800	182	12.5 × 35.5	0.026	0.052	2230	1960	16 × 25	0.031	0.062	2190	1780
2200	222	12.5 × 40	0.024	0.048	2460	2120	18 × 20	0.028	0.056	2050	1840
2700	272	16 × 31.5	0.022	0.044	2510	2220	18 × 25	0.025	0.050	2350	2060
3300	332	16 × 35.5	0.020	0.040	2770	2410	18 × 31.5	0.023	0.046	2720	2240
3900	392	16 × 40	0.019	0.038	3110	2530	18 × 35.5	0.021	0.042	3050	2420
4700	472	18 × 40	0.018	0.036	3300	2660					

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

PM series

■ Standard Ratings

Cap.(μF)		V(Code) Size code Item Code	35 (1V)									
			—				6					
			Case size ΦD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size ΦD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
				20°C / 100kHz	−10°C / 100kHz	105°C / ^{10kHz to} 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / ^{10kHz to} 200kHz	105°C / 120Hz
22	220		5 × 11	0.75	1.50	160	85					
27	270		5 × 11	0.60	1.20	180	99					
33	330		6.3 × 11	0.49	0.98	225	125					
39	390		6.3 × 11	0.41	0.82	245	140					
47	470		6.3 × 11	0.34	0.68	270	160					
56	560		6.3 × 11	0.28	0.56	295	180					
68	680		6.3 × 15	0.24	0.48	370	230					
82	820		6.3 × 15	0.19	0.38	415	265					
100	101		8 × 11.5	0.16	0.32	460	305					
120	121		8 × 15	0.14	0.28	550	370	10 × 12.5	0.15	0.30	635	375
150	151		8 × 15	0.12	0.24	595	415	10 × 12.5	0.12	0.24	680	435
180	181		8 × 20	0.10	0.20	730	520	10 × 15	0.11	0.22	700	500
220	221		8 × 20	0.085	0.17	795	580	10 × 15	0.090	0.18	825	560
270	271		10 × 20	0.070	0.14	985	735	12.5 × 15	0.080	0.16	920	690
330	331		10 × 20	0.060	0.12	1060	810	12.5 × 15	0.065	0.13	1020	780
390	391		10 × 25	0.055	0.11	1260	955	12.5 × 15	0.060	0.12	1060	825
470	471		10 × 31.5	0.046	0.092	1450	1130	16 × 15	0.055	0.11	1270	1010
560	561		12.5 × 20	0.041	0.082	1430	1160	16 × 15	0.048	0.096	1360	1100
680	681		12.5 × 25	0.036	0.072	1700	1370	18 × 15	0.042	0.084	1540	1270
820	821		12.5 × 25	0.032	0.064	1760	1490	18 × 15	0.038	0.076	1620	1370
1000	102		12.5 × 31.5	0.029	0.058	1980	1710	16 × 20	0.034	0.068	1770	1530
1200	122		12.5 × 35.5	0.026	0.052	2230	1920	16 × 25	0.031	0.062	2190	1740
1500	152		12.5 × 40	0.024	0.048	2460	2120	18 × 20	0.028	0.056	2050	1840
1800	182		16 × 31.5	0.022	0.044	2510	2220	18 × 25	0.025	0.050	2350	2060
2200	222		16 × 35.5	0.020	0.040	2770	2410	18 × 31.5	0.023	0.046	2720	2240
2700	272		16 × 40	0.018	0.036	3110	2610	18 × 35.5	0.021	0.042	3050	2420
3300	332		18 × 40	0.017	0.034	3300	2730					

Cap.(μF)		V(Code) Size code Item Code	50 (1H)									
			—				6					
			Case size ΦD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size ΦD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
				20°C / 100kHz	−10°C / 100kHz	105°C / ^{10kHz to} 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / ^{10kHz to} 200kHz	105°C / 120Hz
0.47	R47		5 × 11	23.0	46.0	22	11					
0.68	R68		5 × 11	16.0	32.0	28	14					
1	010		5 × 11	11.0	22.0	36	18					
1.5	1R5		5 × 11	7.50	15.0	45	22					
2.2	2R2		5 × 11	5.00	10.0	54	27					
3.3	3R3		5 × 11	3.30	6.60	66	33					
4.7	4R7		5 × 11	2.20	4.40	81	40					
6.8	6R8		5 × 11	1.80	3.60	91	45					
10	100		5 × 11	1.40	2.80	115	57					
12	120		5 × 11	1.20	2.40	125	62					
15	150		5 × 11	0.93	1.86	145	72					
18	180		5 × 11	0.80	1.60	165	79					
22	220		6.3 × 11	0.65	1.30	195	100					
27	270		6.3 × 11	0.53	1.06	215	115					
33	330		6.3 × 11	0.43	0.86	240	135					
39	390		6.3 × 11	0.36	0.72	260	150					
47	470		6.3 × 15	0.30	0.60	330	195					
56	560		6.3 × 15	0.25	0.50	360	220					
68	680		8 × 11.5	0.20	0.40	415	255					
82	820		8 × 15	0.17	0.34	505	320	10 × 12.5	0.18	0.36	530	330
100	101		8 × 20	0.14	0.28	620	410	10 × 15	0.16	0.32	580	385
120	121		8 × 20	0.12	0.24	755	455	10 × 15	0.13	0.26	755	435
150	151		10 × 20	0.10	0.20	820	570	12.5 × 15	0.11	0.22	785	545
180	181		10 × 20	0.085	0.17	945	635	12.5 × 15	0.095	0.19	845	605
220	221		10 × 25	0.075	0.15	1150	760	12.5 × 15	0.080	0.16	920	670
270	271		10 × 31.5	0.065	0.13	1200	900	16 × 15	0.070	0.14	1120	840
330	331		10 × 31.5	0.055	0.11	1300	995	16 × 15	0.060	0.12	1210	925
390	391		12.5 × 25	0.048	0.096	1440	1120	16 × 15	0.055	0.11	1270	990
470	471		12.5 × 25	0.044	0.088	1500	1190	18 × 15	0.046	0.092	1470	1170
560	561		12.5 × 31.5	0.040	0.080	1720	1360	16 × 20	0.044	0.088	1550	1260
680	681		12.5 × 35.5	0.036	0.072	1900	1530	16 × 20	0.040	0.080	1630	1350
820	821		12.5 × 40	0.033	0.066	2120	1700	18 × 20	0.036	0.072	1810	1530
1000	102		16 × 31.5	0.030	0.060	2150	1830	18 × 25	0.033	0.066	2020	1730
1200	122		16 × 35.5	0.028	0.056	2320	1990	18 × 31.5	0.031	0.062	2140	1880
1500	152		16 × 40	0.026	0.052	2650	2170	18 × 31.5	0.029	0.058	2340	1990
1800	182		18 × 35.5	0.025	0.050	2620	2210					
2200	222		18 × 40	0.024	0.048	2790	2300					

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard Ratings

Cap.(μF)		V(Code) Size code	63 (1J)									
			—					6				
			Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
				20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
Code	Item											
10	100	5 × 11	1.06	2.12	135	67						
12	120	5 × 11	0.93	1.86	145	72						
15	150	6.3 × 11	0.73	1.46	185	92						
18	180	6.3 × 11	0.63	1.26	195	100						
22	220	6.3 × 11	0.52	1.04	215	110						
27	270	6.3 × 11	0.43	0.86	240	130						
33	330	6.3 × 15	0.35	0.70	305	170						
39	390	6.3 × 15	0.30	0.60	330	190						
47	470	8 × 11.5	0.25	0.50	365	215						
56	560	8 × 15	0.21	0.42	450	275	10 × 12.5	0.23	0.46	450	275	
68	680	8 × 15	0.17	0.34	500	315	10 × 12.5	0.19	0.38	495	310	
82	820	8 × 20	0.15	0.30	600	385	10 × 15	0.16	0.32	580	375	
100	101	10 × 20	0.12	0.24	750	495	12.5 × 15	0.14	0.28	695	460	
120	121	10 × 20	0.10	0.20	820	555	12.5 × 15	0.12	0.24	750	510	
150	151	10 × 25	0.090	0.18	950	665	12.5 × 15	0.095	0.19	845	590	
180	181	10 × 31.5	0.075	0.15	1110	790	16 × 15	0.080	0.16	1050	750	
220	221	12.5 × 20	0.065	0.13	1140	835	16 × 15	0.070	0.14	1120	820	
270	271	12.5 × 25	0.055	0.11	1340	1000	18 × 15	0.060	0.12	1290	965	
330	331	12.5 × 25	0.049	0.098	1420	1090	18 × 15	0.050	0.10	1410	1080	
390	391	12.5 × 31.5	0.043	0.086	1620	1260	16 × 20	0.047	0.094	1500	1170	
470	471	12.5 × 35.5	0.039	0.078	1780	1420	16 × 25	0.042	0.084	1700	1350	
560	561	12.5 × 40	0.035	0.070	1950	1580	18 × 20	0.039	0.078	1730	1400	
680	681	16 × 31.5	0.032	0.064	2050	1700	18 × 25	0.035	0.070	1940	1610	
820	821	16 × 35.5	0.029	0.058	2220	1880	18 × 31.5	0.032	0.064	2110	1780	
1000	102	16 × 40	0.027	0.054	2370	2050	18 × 35.5	0.029	0.058	2280	1970	
1200	122	18 × 40	0.025	0.050	2510	2210						

Cap. (μF)		V(Code)	Size code	Item	80 (1K)									
					—						6			
					Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φ D × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
						20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
4.7	4R7	5 × 11	4.20	11.00	53	26								
6.8	6R8	5 × 11	2.60	7.00	68	34								
10	100	6.3 × 11	1.70	4.60	87	43								
12	120	6.3 × 11	1.40	3.80	96	48								
15	150	6.3 × 11	1.20	3.20	104	52								
18	180	6.3 × 11	1.00	2.70	150	58								
22	220	6.3 × 15	0.77	2.10	180	71								
27	270	6.3 × 15	0.63	1.70	220	80								
33	330	8 × 11.5	0.53	1.40	275	132								
39	390	8 × 15	0.46	1.20	300	156	10 × 12.5	0.49	1.30	380	155			
47	470	8 × 15	0.39	1.10	360	175	10 × 12.5	0.42	1.10	410	174			
56	560	8 × 20	0.34	0.92	490	208	10 × 15	0.36	0.97	500	202			
68	680	10 × 20	0.28	0.76	570	264	12.5 × 15	0.31	0.84	520	249			
82	820	10 × 20	0.25	0.68	620	284	12.5 × 15	0.27	0.73	560	273			
100	101	10 × 25	0.21	0.57	795	347	12.5 × 15	0.23	0.62	605	308			
120	121	10 × 31.5	0.18	0.49	870	406	16 × 15	0.20	0.54	663	444			
150	151	10 × 31.5	0.15	0.41	955	459	16 × 15	0.18	0.47	699	484			
180	181	12.5 × 25	0.13	0.35	1040	520	16 × 15	0.15	0.41	766	543			
220	221	12.5 × 31.5	0.12	0.32	1160	595	18 × 15	0.13	0.35	881	643			
270	271	12.5 × 31.5	0.10	0.27	1270	667	16 × 20	0.11	0.30	1240	742			
330	331	12.5 × 35.5	0.088	0.24	1450	767	16 × 25	0.099	0.27	1440	874			
390	391	12.5 × 40	0.078	0.21	1610	822	18 × 20	0.089	0.24	1450	908			
470	471	16 × 31.5	0.069	0.19	1790	1150	18 × 25	0.080	0.22	1650	1060			
560	561	16 × 35.5	0.062	0.17	2000	1300	18 × 31.5	0.072	0.19	1750	1210			
680	681	16 × 40	0.055	0.15	2200	1470	18 × 31.5	0.065	0.18	1850	1300			
820	821	18 × 35.5	0.049	0.13	2250	1590								
1000	102	18 × 40	0.044	0.12	2370	1790								

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard Ratings

Cap. (μF)	V(Code)	Size code	Item	100 (2A)									
				—				6					
				Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)	
					20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
0.47	R47	5 × 11	43.0	116.0	17	8							
0.68	R68	5 × 11	23.0	62.0	23	11							
1	010	5 × 11	17.0	46.0	27	13							
1.5	1R5	5 × 11	10.0	27.0	35	17							
2.2	2R2	5 × 11	6.60	18.0	43	21							
3.3	3R3	5 × 11	4.10	11.0	54	27							
4.7	4R7	6.3 × 11	2.80	7.60	68	34							
6.8	6R8	6.3 × 11	1.90	5.10	83	41							
10	100	6.3 × 11	1.20	3.20	104	52							
12	120	6.3 × 11	1.00	2.70	150	57							
15	150	6.3 × 15	0.81	2.20	180	65							
18	180	6.3 × 15	0.67	1.80	220	73							
22	220	8 × 11.5	0.55	1.50	275	122							
27	270	8 × 15	0.47	1.30	300	146	10 × 12.5	0.50	1.40	380	145		
33	330	8 × 15	0.38	1.00	360	169	10 × 12.5	0.42	1.10	410	166		
39	390	8 × 20	0.33	0.89	490	202	10 × 15	0.36	0.97	500	193		
47	470	10 × 20	0.28	0.76	570	252	12.5 × 15	0.31	0.84	520	239		
56	560	10 × 20	0.24	0.65	620	274	12.5 × 15	0.27	0.73	560	258		
68	680	10 × 25	0.21	0.57	795	326	12.5 × 15	0.23	0.62	605	289		
82	820	10 × 31.5	0.18	0.49	870	386	16 × 15	0.19	0.51	681	433		
100	101	10 × 31.5	0.15	0.41	955	438	16 × 15	0.17	0.46	719	475		
120	121	12.5 × 25	0.13	0.35	1040	519	16 × 15	0.14	0.38	793	531		
150	151	12.5 × 25	0.11	0.30	1120	553	18 × 15	0.12	0.32	917	635		
180	181	12.5 × 31.5	0.098	0.26	1270	641	16 × 20	0.11	0.30	1240	706		
220	221	12.5 × 35.5	0.087	0.23	1450	730	16 × 25	0.093	0.25	1440	854		
270	271	12.5 × 40	0.072	0.19	1610	843	18 × 20	0.080	0.22	1450	918		
330	331	16 × 31.5	0.062	0.17	1790	1160	18 × 25	0.070	0.19	1650	1080		
390	391	16 × 35.5	0.053	0.14	2000	1340	18 × 31.5	0.062	0.17	1850	1240		
470	471	16 × 40	0.047	0.13	2200	1530	18 × 35.5	0.056	0.15	1970	1410		
560	561	18 × 35.5	0.041	0.11	2250	1680							
680	681	18 × 40	0.036	0.097	2300	1910							

※ In case of low profile type, 6 will be put at 12th digit of type numbering system.

Cap.(μF)	V(Code)	160		200		250		315		350		400		450	
		2C		2D		2E		2F		2V		2G		2W	
1	010	8 × 11.5	19	8 × 11.5	19	8 × 11.5	19	8 × 11.5	19	10 × 12.5	21	10 × 12.5	17	10 × 15	17
2.2	2R2	8 × 11.5	30	8 × 11.5	30	10 × 12.5	32	10 × 12.5	32	10 × 15	34	10 × 15	28	10 × 20	28
3.3	3R3	10 × 12.5	50	10 × 12.5	50	10 × 15	52	10 × 15	52	10 × 20	54	10 × 20	47	12.5 × 20	48
4.7	4R7	10 × 12.5	57	10 × 15	60	10 × 15	60	10 × 20	65	10 × 20	65	12.5 × 20	55	12.5 × 25	55
10	100	10 × 15	90	10 × 20	95	12.5 × 20	98	12.5 × 20	98	12.5 × 25	100	12.5 × 25	85	16 × 25	90
22	220	12.5 × 20	140	12.5 × 25	145	16 × 25	150	16 × 25	150	16 × 25	150	16 × 31.5	130	16 × 35.5	135
33	330	12.5 × 25	175	16 × 25	180	16 × 25	180	16 × 31.5	185	16 × 35.5	190	18 × 35.5	170	18 × 40	170
47	470	16 × 25	220	16 × 25	220	16 × 31.5	225	18 × 35.5	235	18 × 40	240			Case size φD × L (mm) ※	
100	101	16 × 35.5	330	18 × 40	345	18 × 40	345								

※ Rated ripple current (mAmps) at 105°C 120Hz