













	1	2	3	4	5	6	7																																																																																											
A	A xx-LC-TT CKT: 06, 08, 14, 16,18,20  CKT: 24,28,32,40  A xx-LC/7-T CKT: 24, 28  PCB LAYOUT <table><tr><th>CKT</th><th>A±0.20</th><th>B±0.20</th></tr><tr><td>06</td><td>7.62</td><td>5.08</td></tr><tr><td>08</td><td>10.16</td><td>7.62</td></tr><tr><td>14</td><td>17.78</td><td>15.24</td></tr><tr><td>16</td><td>20.32</td><td>17.78</td></tr><tr><td>18</td><td>22.86</td><td>20.32</td></tr><tr><td>20</td><td>25.40</td><td>22.86</td></tr></table> PCB LAYOUT <table><tr><th>CKT</th><th>A±0.20</th><th>B±0.20</th></tr><tr><td>24</td><td>30.48</td><td>27.94</td></tr><tr><td>28</td><td>35.56</td><td>33.02</td></tr><tr><td>32</td><td>40.64</td><td>38.10</td></tr><tr><td>40</td><td>50.80</td><td>48.26</td></tr></table> PCB LAYOUT <table><tr><th>CKT</th><th>A±0.20</th><th>B±0.20</th></tr><tr><td>24</td><td>30.48</td><td>27.94</td></tr><tr><td>28</td><td>35.56</td><td>33.02</td></tr></table> MATERIAL: Contact : Phosphor Bronze thickness 0.15mm Plating : Contact Plating, Tin plated 60u"~80u" (Lead free plating) Insulator : PBT-4830 , UL 94V-0 SPECIFICATIONS: Current Rating : 1A Dielectric withstanding Voltage : 1000v RMS/minute Insulator resistance : 5000 Megohms min. Contact resistance : 20 milliohms initial 30 milliohms after test. Operating temperatures : -55°c to 85°c Insertion force : 340g(12 oz) max.per contact. Withdrawal force : 80g(2.82 oz) min.per contact							CKT	A±0.20	B±0.20	06	7.62	5.08	08	10.16	7.62	14	17.78	15.24	16	20.32	17.78	18	22.86	20.32	20	25.40	22.86	CKT	A±0.20	B±0.20	24	30.48	27.94	28	35.56	33.02	32	40.64	38.10	40	50.80	48.26	CKT	A±0.20	B±0.20	24	30.48	27.94	28	35.56	33.02	A																																													
CKT	A±0.20	B±0.20																																																																																																
06	7.62	5.08																																																																																																
08	10.16	7.62																																																																																																
14	17.78	15.24																																																																																																
16	20.32	17.78																																																																																																
18	22.86	20.32																																																																																																
20	25.40	22.86																																																																																																
CKT	A±0.20	B±0.20																																																																																																
24	30.48	27.94																																																																																																
28	35.56	33.02																																																																																																
32	40.64	38.10																																																																																																
40	50.80	48.26																																																																																																
CKT	A±0.20	B±0.20																																																																																																
24	30.48	27.94																																																																																																
28	35.56	33.02																																																																																																
B	 							B																																																																																										
C	 							C																																																																																										
D	PCB LAYOUT <table><tr><th>CKT</th><th>A±0.20</th><th>B±0.20</th></tr><tr><td>06</td><td>7.62</td><td>5.08</td></tr><tr><td>08</td><td>10.16</td><td>7.62</td></tr><tr><td>14</td><td>17.78</td><td>15.24</td></tr><tr><td>16</td><td>20.32</td><td>17.78</td></tr><tr><td>18</td><td>22.86</td><td>20.32</td></tr><tr><td>20</td><td>25.40</td><td>22.86</td></tr></table> PCB LAYOUT <table><tr><th>CKT</th><th>A±0.20</th><th>B±0.20</th></tr><tr><td>24</td><td>30.48</td><td>27.94</td></tr><tr><td>28</td><td>35.56</td><td>33.02</td></tr><tr><td>32</td><td>40.64</td><td>38.10</td></tr><tr><td>40</td><td>50.80</td><td>48.26</td></tr></table> PCB LAYOUT <table><tr><th>CKT</th><th>A±0.20</th><th>B±0.20</th></tr><tr><td>24</td><td>30.48</td><td>27.94</td></tr><tr><td>28</td><td>35.56</td><td>33.02</td></tr></table>							CKT	A±0.20	B±0.20	06	7.62	5.08	08	10.16	7.62	14	17.78	15.24	16	20.32	17.78	18	22.86	20.32	20	25.40	22.86	CKT	A±0.20	B±0.20	24	30.48	27.94	28	35.56	33.02	32	40.64	38.10	40	50.80	48.26	CKT	A±0.20	B±0.20	24	30.48	27.94	28	35.56	33.02	D																																													
CKT	A±0.20	B±0.20																																																																																																
06	7.62	5.08																																																																																																
08	10.16	7.62																																																																																																
14	17.78	15.24																																																																																																
16	20.32	17.78																																																																																																
18	22.86	20.32																																																																																																
20	25.40	22.86																																																																																																
CKT	A±0.20	B±0.20																																																																																																
24	30.48	27.94																																																																																																
28	35.56	33.02																																																																																																
32	40.64	38.10																																																																																																
40	50.80	48.26																																																																																																
CKT	A±0.20	B±0.20																																																																																																
24	30.48	27.94																																																																																																
28	35.56	33.02																																																																																																
E	MATERIAL: Contact : Phosphor Bronze thickness 0.15mm Plating : Contact Plating, Tin plated 60u"~80u" (Lead free plating) Insulator : PBT-4830 , UL 94V-0							E																																																																																										
F	SPECIFICATIONS: Current Rating : 1A Dielectric withstanding Voltage : 1000v RMS/minute Insulator resistance : 5000 Megohms min. Contact resistance : 20 milliohms initial 30 milliohms after test. Operating temperatures : -55°c to 85°c Insertion force : 340g(12 oz) max.per contact. Withdrawal force : 80g(2.82 oz) min.per contact							F																																																																																										
G	RoHS compliant <table><tr><td>Scale</td><td>1:1</td><td></td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Customer-No.</td></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>24.03.1999</td><td>Hellwig</td></tr><tr><td>X.</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td>Approved</td><td>05.11.2009</td><td>Hellwig</td></tr><tr><td>X.X</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±X</td><td>③</td><td>Correct dimensions</td><td>05.11.2009</td><td>Dean</td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td>②</td><td>Update</td><td>21.07.2009</td><td>Dean</td><td></td><td></td><td></td><td></td></tr><tr><td>X.°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.X°</td><td>±X°</td><td>①</td><td>Drawn</td><td>24.03.1999</td><td>Hellwig</td><td></td><td></td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td><td></td><td></td></tr></table>							Scale	1:1						Date	Name	Customer-No.	TOLERANCE							Drawn	24.03.1999	Hellwig	X.	±X						Approved	05.11.2009	Hellwig	X.X	±X									X.XX	±X	③	Correct dimensions	05.11.2009	Dean					DIM	TOL	②	Update	21.07.2009	Dean					X.°	±X°									X.X°	±X°	①	Drawn	24.03.1999	Hellwig					Angle	TOL	Id.	Modification	Date	Name					G
Scale	1:1						Date	Name	Customer-No.																																																																																									
TOLERANCE							Drawn	24.03.1999	Hellwig																																																																																									
X.	±X						Approved	05.11.2009	Hellwig																																																																																									
X.X	±X																																																																																																	
X.XX	±X	③	Correct dimensions	05.11.2009	Dean																																																																																													
DIM	TOL	②	Update	21.07.2009	Dean																																																																																													
X.°	±X°																																																																																																	
X.X°	±X°	①	Drawn	24.03.1999	Hellwig																																																																																													
Angle	TOL	Id.	Modification	Date	Name																																																																																													
H	ASSMANN components Drawing-No. ASS 0810 CO Replace ASS 0333A CO ASS 0333B CO rev03 Sheet							H																																																																																										
	1	2	3	4	5	6	7																																																																																											